

JCR-B-6R Information

Heisener.com

Part Number JCR-B-6R
Manufacturer Eaton

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CYLINDRICAL

Package Cylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









JCR-B-6R Specifications

Manufacturer Part NumberJCR-B-6RManufacturerEatonCategoryCircuit ProtectionElectrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesJCR-BFuse TypeCartridgeCurrent Rating170AVoltage Rating - AC7200V (7.2kV)Voltage Rating - DC-Response Time-ApplicationsMotor ProtectionFeaturesIndicatingClassRApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage50kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension17.88" Dia x 19.25" L (454.10mm x 488.90mm)		
CategoryCircuit ProtectionPackageCylindrical, Specialty FusesSeriesJCR-BFuse TypeCartridgeCurrent Rating170AVoltage Rating - AC7200V (7.2kV)Voltage Rating - DC-Response Time-ApplicationsMotor ProtectionFeaturesIndicatingClassRApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage50kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension17.88" Dia x 19.25" L (454.10mm x 488.90mm)	Manufacturer Part Number	JCR-B-6R
Electrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series JCR-B Fuse Type Cartridge Current Rating 170A Voltage Rating - AC 7200V (7.2kV) Voltage Rating - DC Response Time - Applications Motor Protection Features Indicating Class R Approvals UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Electrical, Specialty Fuses Cylindrical, Blade Terminal (Bolt) Size / Dimension ICLass Series Series Cylindrical, Blade Terminal (Bolt) Size / Dimension IT.88" Dia x 19.25" L (454.10mm x 488.90mm)	Manufacturer	Eaton
PackageCylindrical, Blade Terminal (Bolt)SeriesJCR-BFuse TypeCartridgeCurrent Rating170AVoltage Rating - AC7200V (7.2kV)Voltage Rating - DC-Response Time-ApplicationsMotor ProtectionFeaturesIndicatingClassRApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage50kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension17.88" Dia x 19.25" L (454.10mm x 488.90mm)	Category	Circuit Protection
Series JCR-B Fuse Type Cartridge Current Rating 170A Voltage Rating - AC 7200V (7.2kV) Voltage Rating - DC - Response Time - Applications Motor Protection Features Indicating Class R Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage 50kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 17.88" Dia x 19.25" L (454.10mm x 488.90mm)		Electrical, Specialty Fuses
Fuse Type Cartridge Current Rating 170A Voltage Rating - AC 7200V (7.2kV) Voltage Rating - DC - Response Time Applications Motor Protection Features Indicating Class R Approvals UR Operating Temperature Breaking Capacity @ Rated Voltage 50kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 17.88" Dia x 19.25" L (454.10mm x 488.90mm)	Package	Cylindrical, Blade Terminal (Bolt)
Current Rating Voltage Rating - AC 7200V (7.2kV) Voltage Rating - DC	Series	JCR-B
Voltage Rating - AC Voltage Rating - DC Response Time Applications Motor Protection Indicating Class R Approvals UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 7200V (7.2kV) 7200V (7.2kV) 7200V (7.2kV) 10 10 10 10 10 10 10 10 10 1	Fuse Type	Cartridge
Voltage Rating - DC Response Time Applications Motor Protection Features Indicating Class R Approvals UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Size / Dimension	Current Rating	170A
Response Time Applications Motor Protection Features Indicating Class R Approvals UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension	Voltage Rating - AC	7200V (7.2kV)
Applications Motor Protection Features Indicating Class R Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage 50kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 17.88" Dia x 19.25" L (454.10mm x 488.90mm)	Voltage Rating - DC	-
Features Indicating Class R Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage 50kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 17.88" Dia x 19.25" L (454.10mm x 488.90mm)	Response Time	-
Class R Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage 50kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 17.88" Dia x 19.25" L (454.10mm x 488.90mm)	Applications	Motor Protection
Approvals Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension UR - CUR Cylindrical, Blade Terminal (Bolt) 17.88" Dia x 19.25" L (454.10mm x 488.90mm)	Features	Indicating
Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 17.88" Dia x 19.25" L (454.10mm x 488.90mm)	Class	R
Breaking Capacity @ Rated Voltage 50kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 17.88" Dia x 19.25" L (454.10mm x 488.90mm)	Approvals	UR
Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 17.88" Dia x 19.25" L (454.10mm x 488.90mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 17.88" Dia x 19.25" L (454.10mm x 488.90mm)	Breaking Capacity @ Rated Voltage	50kA
Size / Dimension 17.88" Dia x 19.25" L (454.10mm x 488.90mm)	Mounting Type	Bolt Mount
	Package / Case	Cylindrical, Blade Terminal (Bolt)
	Size / Dimension	17.88" Dia x 19.25" L (454.10mm x 488.90mm)
Report errors?		Report errors?

JCR-B-6R Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

JCR-B-6R Payment Methods



















JCR-B-6R Shipping Methods













If you have any question about JCR-B-6R, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com