

### **JCY-80E Information**

Heisener.com

Part Number JCY-80E
Manufacturer Eaton

**Category** Circuit Protection

Electrical, Specialty Fuses

**Description** FUSE CARTRIDGE 5.5KV NON STD

Package Cartridge, Non-Standard

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **JCY-80E Specifications**

Manufacturer Part NumberJCY-80EManufacturerEatonCategoryCircuit ProtectionPackageCartridge, Non-StandardSeriesJCYFuse TypeCartridgeCurrent Rating80AVoltage Rating - AC5500V (5.5kV)Voltage Rating - DC-Response Time-ApplicationsTransformer ProtectionFeaturesIndicatingClassEApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage40kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension2.000" Dia x 11.190" L (50.80mm x 284.18mm)		
Category         Circuit Protection           Electrical, Specialty Fuses           Package         Cartridge, Non-Standard           Series         JCY           Fuse Type         Cartridge           Current Rating         80A           Voltage Rating - AC         5500V (5.5kV)           Voltage Rating - DC         -           Response Time         -           Applications         Transformer Protection           Features         Indicating           Class         E           Approvals         -           Operating Temperature         -           Breaking Capacity @ Rated Voltage         40kA           Mounting Type         Holder           Package / Case         Cartridge, Non-Standard           Size / Dimension         2,000" Dia x 11.190" L (50.80mm x 284.18mm)	Manufacturer Part Number	JCY-80E
PackageElectrical, Specialty FusesPackageCartridge, Non-StandardSeriesJCYFuse TypeCartridgeCurrent Rating80AVoltage Rating - AC5500V (5.5kV)Voltage Rating - DC-Response Time-ApplicationsTransformer ProtectionFeaturesIndicatingClassEApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage40kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension2.000" Dia x 11.190" L (50.80mm x 284.18mm)	Manufacturer	Eaton
PackageCartridge, Non-StandardSeriesJCYFuse TypeCartridgeCurrent Rating80AVoltage Rating - AC5500V (5.5kV)Voltage Rating - DC-Response Time-ApplicationsTransformer ProtectionFeaturesIndicatingClassEApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage40kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension2.000" Dia x 11.190" L (50.80mm x 284.18mm)	Category	Circuit Protection
SeriesJCYFuse TypeCartridgeCurrent Rating80AVoltage Rating - AC5500V (5.5kV)Voltage Rating - DC-Response Time-ApplicationsTransformer ProtectionFeaturesIndicatingClassEApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage40kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension2.000" Dia x 11.190" L (50.80mm x 284.18mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating80AVoltage Rating - AC5500V (5.5kV)Voltage Rating - DC-Response Time-ApplicationsTransformer ProtectionFeaturesIndicatingClassEApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage40kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension2.000" Dia x 11.190" L (50.80mm x 284.18mm)	Package	Cartridge, Non-Standard
Current Rating 80A  Voltage Rating - AC 5500V (5.5kV)  Voltage Rating - DC -  Response Time -  Applications Transformer Protection  Features Indicating  Class E  Approvals -  Operating Temperature -  Breaking Capacity @ Rated Voltage 40kA  Mounting Type Holder  Package / Case Cartridge, Non-Standard  Size / Dimension 2500V (5.5kV)  -  Converting Temperature -  Breaking Capacity @ Rated Voltage A0kA  Cartridge, Non-Standard  Size / Dimension 2.000" Dia x 11.190" L (50.80mm x 284.18mm)	Series	JCY
Voltage Rating - AC  Voltage Rating - DC  Response Time  Applications  Transformer Protection  Features  Indicating  Class  E  Approvals  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Size / Dimension  5500V (5.5kV)  -  0404  -  Cartridge, Non-Standard  Size / Dimension  5500V (5.5kV)  -  6404  -  Cartridge, Non-Standard  Size / Dimension  5500V (5.5kV)  -  6404  -  6404  Cartridge, Non-Standard  Size / Dimension  5500V (5.5kV)  -  6500V (5.5kV)  -  6600V (5.5kV)  -  6700V (5.5k	Fuse Type	Cartridge
Voltage Rating - DC  Response Time  Applications  Transformer Protection  Features  Indicating  Class  E  Approvals  - Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Size / Dimension  - Class  Cutridge, Non-Standard  Size / Dimension  - Company Capacity (Capacity (C	Current Rating	80A
Response Time - Applications Transformer Protection  Features Indicating  Class E  Approvals -  Operating Temperature -  Breaking Capacity @ Rated Voltage 40kA  Mounting Type Holder  Package / Case Cartridge, Non-Standard  Size / Dimension 2.000" Dia x 11.190" L (50.80mm x 284.18mm)	Voltage Rating - AC	5500V (5.5kV)
Applications Features Indicating Class E Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension Transformer Protection Indicating E All Cartridge, Non-Standard 2.000" Dia x 11.190" L (50.80mm x 284.18mm)	Voltage Rating - DC	-
Features Indicating  Class E  Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 40kA  Mounting Type Holder  Package / Case Cartridge, Non-Standard Size / Dimension 2.000" Dia x 11.190" L (50.80mm x 284.18mm)	Response Time	-
Class E Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 40kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 2.000" Dia x 11.190" L (50.80mm x 284.18mm)	Applications	Transformer Protection
Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 40kA  Mounting Type Holder  Package / Case Cartridge, Non-Standard Size / Dimension 2.000" Dia x 11.190" L (50.80mm x 284.18mm)	Features	Indicating
Operating Temperature  Breaking Capacity @ Rated Voltage  40kA  Mounting Type  Holder  Package / Case  Cartridge, Non-Standard  Size / Dimension  2.000" Dia x 11.190" L (50.80mm x 284.18mm)	Class	E
Breaking Capacity @ Rated Voltage 40kA  Mounting Type Holder  Package / Case Cartridge, Non-Standard  Size / Dimension 2.000" Dia x 11.190" L (50.80mm x 284.18mm)	Approvals	-
Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 2.000" Dia x 11.190" L (50.80mm x 284.18mm)	Operating Temperature	-
Package / Case Cartridge, Non-Standard Size / Dimension 2.000" Dia x 11.190" L (50.80mm x 284.18mm)	Breaking Capacity @ Rated Voltage	40kA
Size / Dimension 2.000" Dia x 11.190" L (50.80mm x 284.18mm)	Mounting Type	Holder
·	Package / Case	Cartridge, Non-Standard
Report errors?	Size / Dimension	2.000" Dia x 11.190" L (50.80mm x 284.18mm)
		Report errors?

### **JCY-80E Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **JCY-80E Payment Methods**





















### **JCY-80E Shipping Methods**













If you have any question about JCY-80E, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com