

JD3-0001NL

JD3-0001NL Information





Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



JD3-0001NL Specifications

Manufacturer Part Number JD3-0001NL Manufacturer Pulse Electronics Network Category Connectors, Interconnects Modular Connectors - Jacks With Magnetics Modular Connectors - Jacks With Magnetics Package - Series PULSEJACK? JD3 Connector Type R45 Number of Ports 1 Number of Rows 1 Applications 1/10/1000 Base-T, AutoMDIX Monufing Type Modular Connector AutoMDIX Orientation Nofe' (16.87mm) Height Above Board Jose Constit LED Volor Does Notal LED Number of Crores per Jack 8 Shielding Shielded Factures Board Lock Tab Direction Vers Selectable Contact Finish Gold Operating Temperature Orie Contact		
CategoryConnectors, Interconnects Modular Connectors - Jacks With MagneticsPackage-SeriesPULSEJACK? JD3Connector TypeRJ45Number of Ports1Number of Rows1Applications10/100/1000 Base-T, AutoMDIXMounting TypeOrientalOrientationVerticalTerminationSolderHeight Above BoardSolderNumber of Cores per Jack8ShieldingSnieldedShieldingSolar LockTerturesSolar LockShieldingSolar LockTerturesSolar LockShieldingSolar LockShieldingSolar LockShieldingSolar LockShieldingSolar LockTortuctionSolar LockShieldingSolar Loc	Manufacturer Part Number	JD3-0001NL
HeatModular Connectors - Jacks With MagneticsPackage-SeriesPULSEJACK? JD3Connector TypeRJ45Number of Ports1Number of Rows1Applications10/100/1000 Base-T, AutoMDIXMouting TypeVerticalOrientationSolderHeight Above Board0.664" (16.87mm)LED ColorSolderNumber of Cores per Jack8ShieldingShieldedFraturesBoard LockTab DirectionUser SelectableContact MaterialPhosphor BronzeContact FinishGoldOreaning Temperature0°C ~ 0°C	Manufacturer	Pulse Electronics Network
Package-SeriesPULSEJACK? JD3Connector TypeRJ45Number of Ports1Number of Rows1Applications10/100/100 Base-T, AutoMDIXMounting TypeThrough HoleOrientationVerticalTerminationSolderHeight Above Board0.664" (16.87mm)LED ColorDoes Not Contain LEDNumber of Cores per Jack8ShieldingShieldaFeaturesBoard LockTorta UtationalUser SelectableContact MaterialGoldContact FinishGoldOrenating Temperature0% ~ 70°C	Category	Connectors, Interconnects
SeriesPULSEJACK? JD3Connector TypeRJ45Number of Ports1Number of Rows1Applications1/00/1000 Base-T, AutoMDIXMounting TypeThrough HoleOrientationVerticalTerminationSolderHeight Above Board0.664" (16.87mm)LED ColorDoes Not Contain LEDNumber of Cores per Jack8ShieldingSolderTeaturesBoard LockTotato MaterialUser SelectableContact MaterialGoldContar FinishGoldOre - 70°CN°C		Modular Connectors - Jacks With Magnetics
Connector TypeR45Number of Ports1Number of Rows1Applications10/100/ Base-T, AutoMDIXMounting TypeMortogh HoleOrientationVerticalOrientationSolderTermination0.664" (16.87mm)LED ColorDoes Not Contain LEDNumber of Cores per Jack8ShieldingShieldedFeaturesBoard LockTotact MaterialUser SelectableContact MaterialGoldOrientatingGoldOrientationGoldOrientationGoldOrientationGoldOrientationGoldOrientationOrientationOrientationGoldOrientationOrientationOrientationOrientationOrientationGoldOrientation <t< td=""><td>Package</td><td>-</td></t<>	Package	-
Number of Ports1Number of Rows1Applications10/100/100 Base-T, AutoMDIXApplicationsThrough HoleOrientationVerticalOrientationSolderTerminationSolderHeight Above Board0.664" (16.87mm)LED ColorDoes Not Contain LEDNumber of Cores per Jack8ShieldingSineldedFeaturesBoard LockTab DirectionUser SelectableContact MaterialMosphor BronzeOrient FinishGoldOperating Temperature0°C ~ 70°C	Series	PULSEJACK? JD3
Number of RowsIApplications10/100/ Base-T, AutoMDIXApplicationsNirough HoleMounting TypeVerticalOrientationVerticalTerminationSolderHeight Above Board0.664" (16.87mm)LED ColorDoes Not Contain LEDNumber of Cores per Jack8ShieldingBoard LockFeaturesBoard LockTob DirectionUser SelectableContact MaterialGoldContact FinishGoldOperating Temperature0°C ~ 0°C	Connector Type	RJ45
Applications10/100/ Base-T, AutoMDIXMounting TypeThrough HoleOrientationVerticalTerminationSolderHeight Above Board0.664" (16.87mm)LED ColorDoes Not Contain LEDNumber of Cores per Jack8ShieldingShieldedFeaturesBoard LockTotact MaterialUser SelectableContact MaterialPhosphor BronzeContact FinishGoldOperating Temperature0°C ~ 0°C	Number of Ports	1
Mounting TypeThrough HoleMounting TypeVerticalOrientationVerticalTerminationSolderHeight Above Board0.664" (16.87mm)LED ColorDoes Not Contain LEDNumber of Cores per Jack8ShieldingShieldedFeaturesBoard LockTab DirectionUser SelectableContact MaterialPhosphor BronzeContact FinishGoldOperating Temperature0°C ~ 70°C	Number of Rows	1
OrientationVerticalTerminationSolderHeight Above Board0.664" (16.87mm)LED ColorDoes Not Contain LEDNumber of Cores per Jack8ShieldingShieldedFeaturesBoard LockTab DirectionUser SelectableContact MaterialPhosphor BronzeContact FinishGoldOperating Temperature0°C ~ 70°C	Applications	10/100/1000 Base-T, AutoMDIX
TerminationSolderHeight Above Board0.664" (16.87mm)LED ColorDoes Not Contain LEDNumber of Cores per Jack8ShieldingShieldedFeaturesBoard LockTab DirectionUser SelectableContact MaterialPhosphor BronzeContact FinishGoldOperating Temperature0°C ~ 70°C	Mounting Type	Through Hole
Height Above Board0.664" (16.87mm)LED ColorDoes Not Contain LEDNumber of Cores per Jack8ShieldingShieldedFeaturesBoard LockTab DirectionUser SelectableContact MaterialPhosphor BronzeContact FinishGoldOperating Temperature0°C ~ 70°C	Orientation	Vertical
LED ColorDoes Not Contain LEDNumber of Cores per Jack8ShieldingShieldedFeaturesBoard LockTab DirectionUser SelectableContact MaterialPhosphor BronzeContact FinishGoldOperating Temperature0°C ~ 70°C	Termination	Solder
Number of Cores per Jack8ShieldingShieldedFeaturesBoard LockTab DirectionUser SelectableContact MaterialPhosphor BronzeContact FinishGoldOperating Temperature0°C ~ 70°C	Height Above Board	0.664" (16.87mm)
ShieldingShieldedFeaturesBoard LockTab DirectionUser SelectableContact MaterialPhosphor BronzeContact FinishGoldOperating Temperature0°C ~ 70°C	LED Color	Does Not Contain LED
FeaturesBoard LockTab DirectionUser SelectableContact MaterialPhosphor BronzeContact FinishGoldOperating Temperature0°C ~ 70°C	Number of Cores per Jack	8
Tab DirectionUser SelectableContact MaterialPhosphor BronzeContact FinishGoldOperating Temperature0°C ~ 70°C	Shielding	Shielded
Contact MaterialPhosphor BronzeContact FinishGoldOperating Temperature0°C ~ 70°C	Features	Board Lock
Contact FinishGoldOperating Temperature0°C ~ 70°C	Tab Direction	User Selectable
Operating Temperature $0^{\circ}C \sim 70^{\circ}C$	Contact Material	Phosphor Bronze
	Contact Finish	Gold
Report errors?	Operating Temperature	0° C ~ 70° C
		Report errors?

E-mail: salesdept@heisener.com

JD3-0001NL Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE GUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about JD3-0001NL, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com