



JE1AXN-DC9V Information

Heisener.com

Part Number JE1AXN-DC9V

Manufacturer Panasonic Electric Works

Category Relays

Power Relays, Over 2 Amps

Description RELAY GENERAL PURPOSE SPST 5A 9V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com





Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









JE1AXN-DC9V Specifications

Manufacturer Part NumberJE1AXN-DC9VManufacturerPanasonic Electric WorksCategoryRelaysPackage-SeriesJE-XRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current44.4mACoil Voltage9VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)5ASwitching Voltage250VAC, 30VDC - MaxTurn On Voltage (Max)6.3 VDCTurn Off Voltage (Min)0.9 VDCOperate Time10msRelease Time2msFeatures-Mounting TypeThrough HoleTermination StylePC Pin		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesJE-XRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current44.4mACoil Voltage9VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)5ASwitching Voltage250VAC, 30VDC - MaxTurn On Voltage (Max)6.3 VDCTurn Off Voltage (Min)0.9 VDCOperate Time10msRelease Time2msFeatures-Mounting TypeThrough Hole	Manufacturer Part Number	JE1AXN-DC9V
Package - Series JE-X Relay Type General Purpose Coil Type Non Latching Coil Current 44.4mA Coil Voltage 9VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 5A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 6.3 VDC Turn Off Voltage (Min) 0.9 VDC Operate Time 10ms Release Time 2ms Features - Mounting Type Turno Hurpose Power Relays, Over 2 Amps - Operate Time 10ms Package - Through Hole	Manufacturer	Panasonic Electric Works
Package-SeriesJE-XRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current44.4mACoil Voltage9VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)5ASwitching Voltage250VAC, 30VDC - MaxTurn On Voltage (Max)6.3 VDCTurn Off Voltage (Min)0.9 VDCOperate Time10msRelease Time2msFeatures-Mounting TypeThrough Hole	Category	Relays
Series JE-X Relay Type General Purpose Coil Type Non Latching Coil Current 44.4mA Coil Voltage 9VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 5A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 6.3 VDC Turn Off Voltage (Min) 0.9 VDC Operate Time 10ms Release Time 2ms Features - Mounting Type Through Hole		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 44.4mA Coil Voltage 9VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 5A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 6.3 VDC Turn Off Voltage (Min) 0.9 VDC Operate Time 10ms Release Time 2ms Features - Mounting Type Through Hole	Package	-
Coil TypeNon LatchingCoil Current44.4mACoil Voltage9VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)5ASwitching Voltage250VAC, 30VDC - MaxTurn On Voltage (Max)6.3 VDCTurn Off Voltage (Min)0.9 VDCOperate Time10msRelease Time2msFeatures-Mounting TypeThrough Hole	Series	JE-X
Coil Current 44.4mA Coil Voltage 9VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 5A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 6.3 VDC Turn Off Voltage (Min) 0.9 VDC Operate Time 10ms Release Time 2ms Features - Mounting Type Through Hole	Relay Type	General Purpose
Coil Voltage 9VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 5A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 6.3 VDC Turn Off Voltage (Min) 0.9 VDC Operate Time 10ms Release Time 2ms Features Mounting Type Through Hole	Coil Type	Non Latching
Contact Form SPST-NO (1 Form A) Contact Rating (Current) 5A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 6.3 VDC Turn Off Voltage (Min) 0.9 VDC Operate Time 10ms Release Time 2ms Features Mounting Type Through Hole	Coil Current	44.4mA
Contact Rating (Current) Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 6.3 VDC Turn Off Voltage (Min) 0.9 VDC Operate Time 10ms Release Time 2ms Features - Mounting Type Through Hole	Coil Voltage	9VDC
Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 6.3 VDC Turn Off Voltage (Min) 0.9 VDC Operate Time 10ms Release Time 2ms Features - Mounting Type Through Hole	Contact Form	SPST-NO (1 Form A)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 10ms Release Time 2ms Features - Mounting Type Through Hole	Contact Rating (Current)	5A
Turn Off Voltage (Min) Operate Time 10ms Release Time 2ms Features - Mounting Type Through Hole	Switching Voltage	250VAC, 30VDC - Max
Operate Time 10ms Release Time 2ms Features - Mounting Type Through Hole	Turn On Voltage (Max)	6.3 VDC
Release Time 2ms Features - Mounting Type Through Hole	Turn Off Voltage (Min)	0.9 VDC
Features - Through Hole	Operate Time	10ms
Mounting Type Through Hole	Release Time	2ms
	Features	-
Termination Style PC Pin	Mounting Type	Through Hole
	Termination Style	PC Pin
Report errors?		Report errors?

JE1AXN-DC9V Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

JE1AXN-DC9V Payment Methods



















JE1AXN-DC9V Shipping Methods













If you have any question about JE1AXN-DC9V, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com