

JFS1500-24 Information



For Reference Only

Part Number JFS1500-24

Manufacturer TDK-Lambda Americas Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Converters

Description AC/DC CONVERTER 24V 1500W

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









JFS1500-24 Specifications

Manufacturer Part Number JFS 1500-24 Manufacturer TDK-Lambda Americas Inc. Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series JFS Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 62.5A Power (Watts) 1500W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 75% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Load Sharing, PFC, Remote On/Off, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 11.06" L x 4.87" W x 2.00" H (280.9mm x 123.6mm x 50.8mm)		
Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series JFS Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 62.5A Power (Watts) 1500W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 75% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Load Sharing, PFC, Remote On/Off, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 11.06" L x 4.87" W x 2.00" H (280.9mm x 123.6mm x 50.8mm)	Manufacturer Part Number	JFS1500-24
Package - Series JFS Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 62.5A Power (Watts) 1500W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 75% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Load Sharing, PFC, Remote On/Off, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 11.06" L x 4.87" W x 2.00" H (280.9mm x 123.6mm x 50.8mm)	Manufacturer	TDK-Lambda Americas Inc.
Package - Series JFS Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 62.5A Power (Watts) 1500W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 75% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Load Sharing, PFC, Remote On/Off, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 11.06" L x 4.87" W x 2.00" H (280.9mm x 123.6mm x 50.8mm)	Category	Power Supplies - External/Internal (Off-Board)
Series JFS Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 62.5A Power (Watts) 1500W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 75% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Load Sharing, PFC, Remote On/Off, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 11.06" L x 4.87" W x 2.00" H (280.9mm x 123.6mm x 50.8mm)		AC DC Converters
Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 62.5A Power (Watts) 1500W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 75% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Load Sharing, PFC, Remote On/Off, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 11.06" L x 4.87" W x 2.00" H (280.9mm x 123.6mm x 50.8mm)	Package	-
Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 62.5A Power (Watts) 1500W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 75% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Load Sharing, PFC, Remote On/Off, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 11.06" L x 4.87" W x 2.00" H (280.9mm x 123.6mm x 50.8mm)	Series	JFS
Voltage - Input85 ~ 265 VACVoltage - Output 124VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)62.5APower (Watts)1500WApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency75%Operating Temperature-20°C ~ 70°C (With Derating)FeaturesAdjustable Output, Load Sharing, PFC, Remote On/Off, Remote Sense, Universal InputMounting TypeChassis MountSize / Dimension11.06" L x 4.87" W x 2.00" H (280.9mm x 123.6mm x 50.8mm)	Type	Enclosed
Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 62.5A Power (Watts) 1500W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 75% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Load Sharing, PFC, Remote On/Off, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 11.06" L x 4.87" W x 2.00" H (280.9mm x 123.6mm x 50.8mm)	Number of Outputs	1
Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Load Sharing, PFC, Remote On/Off, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 11.06" L x 4.87" W x 2.00" H (280.9mm x 123.6mm x 50.8mm)	Voltage - Input	85 ~ 265 VAC
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Load Sharing, PFC, Remote On/Off, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 11.06" L x 4.87" W x 2.00" H (280.9mm x 123.6mm x 50.8mm)	Voltage - Output 1	24V
Voltage - Output 4 Current - Output (Max) 62.5A Power (Watts) 1500W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 75% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Load Sharing, PFC, Remote On/Off, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 11.06" L x 4.87" W x 2.00" H (280.9mm x 123.6mm x 50.8mm)	Voltage - Output 2	-
Current - Output (Max) 62.5A Power (Watts) 1500W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 75% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Load Sharing, PFC, Remote On/Off, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 11.06" L x 4.87" W x 2.00" H (280.9mm x 123.6mm x 50.8mm)	Voltage - Output 3	-
Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 75% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Load Sharing, PFC, Remote On/Off, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 11.06" L x 4.87" W x 2.00" H (280.9mm x 123.6mm x 50.8mm)	Voltage - Output 4	-
Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 75% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Load Sharing, PFC, Remote On/Off, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 11.06" L x 4.87" W x 2.00" H (280.9mm x 123.6mm x 50.8mm)	Current - Output (Max)	62.5A
Voltage - Isolation 3kV (3000V) Efficiency 75% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Load Sharing, PFC, Remote On/Off, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 11.06" L x 4.87" W x 2.00" H (280.9mm x 123.6mm x 50.8mm)	Power (Watts)	1500W
Efficiency 75% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Load Sharing, PFC, Remote On/Off, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 11.06" L x 4.87" W x 2.00" H (280.9mm x 123.6mm x 50.8mm)	Applications	ITE (Commercial)
Operating Temperature -20°C ~ 70°C (With Derating) Adjustable Output, Load Sharing, PFC, Remote On/Off, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 11.06" L x 4.87" W x 2.00" H (280.9mm x 123.6mm x 50.8mm)	Voltage - Isolation	3kV (3000V)
Features Adjustable Output, Load Sharing, PFC, Remote On/Off, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 11.06" L x 4.87" W x 2.00" H (280.9mm x 123.6mm x 50.8mm)	Efficiency	75%
Mounting Type Chassis Mount Size / Dimension 11.06" L x 4.87" W x 2.00" H (280.9mm x 123.6mm x 50.8mm)	Operating Temperature	-20°C ~ 70 °C (With Derating)
Size / Dimension 11.06" L x 4.87" W x 2.00" H (280.9mm x 123.6mm x 50.8mm)	Features	Adjustable Output, Load Sharing, PFC, Remote On/Off, Remote Sense, Universal Input
	Mounting Type	Chassis Mount
Report errors?	Size / Dimension	11.06" L x 4.87" W x 2.00" H (280.9mm x 123.6mm x 50.8mm)
		Report errors?

JFS1500-24 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

JFS1500-24 Payment Methods



















JFS1500-24 Shipping Methods













If you have any question about JFS1500-24, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com