

JJS-15LS Information

Heisener.com

Part Number JJS-15LS Manufacturer Eaton

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CRTRDGE 15A 600VAC NON STD

Package Cartridge, Non-Standard

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









JJS-15LS Specifications

Manufacturer Part Number Manufacturer Eaton Category Circuit Protection Electrical, Specialty Fuses Package Cartridge, Non-Standard Series Limitron? JJS Fuse Type Cartridge Current Rating 15A Voltage Rating - AC Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class T Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension Eaton Circuit Protection Electrical, Specialty Fuses Cartridge, Non-Standard O.560" Dia x 1.500" W (14.22mm x 38.10mm) Featurers?		
Category Circuit Protection Electrical, Specialty Fuses Package Cartridge, Non-Standard Series Limitron? JJS Fuse Type Cartridge Current Rating 15A Voltage Rating - AC 600V Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class T Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge Cartridge, Non-Standard Size / Dimension Circuit Protection Electrical, Specialty Fuses Electrical, Industrial Features - CE, CSA, UL Operating Temperature - Cartridge, Non-Standard Size / Dimension Circuit Protection Electrical, Specialty Fuses Cartridge, Non-Standard O.560" Dia x 1.500" W (14.22mm x 38.10mm)	Manufacturer Part Number	JJS-15LS
Bectrical, Specialty Fuses Package Cartridge, Non-Standard Limitron? JJS Fuse Type Cartridge Current Rating 15A Voltage Rating - AC 600V Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class T Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension Electricale, Non-Standard Size / Dimension	Manufacturer	Eaton
Package Cartridge, Non-Standard Series Limitron? JJS Fuse Type Cartridge Current Rating 15A Voltage Rating - AC 600V Voltage Rating - DC - Response Time Fast Applications Electrical, Industrial Features - Class T Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage Doka Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension (21 to 2 to 3 to 4	Category	Circuit Protection
Series Limitron? JJS Fuse Type Cartridge Current Rating 15A Voltage Rating - AC 600V Voltage Rating - DC - Response Time Fast Applications Electrical, Industrial Features - Class T Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.560" Dia x 1.500" W (14.22mm x 38.10mm)		Electrical, Specialty Fuses
Fuse Type Current Rating 15A Voltage Rating - AC 600V Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class T Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension Cartridge Co0V - Cartridge Fast - Cartridge C	Package	Cartridge, Non-Standard
Current Rating Voltage Rating - AC 600V Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class T Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 15A 600V 600V 600V 600V 600V 600V 600V 600	Series	Limitron? JJS
Voltage Rating - AC Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class T Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 600V 60	Fuse Type	Cartridge
Voltage Rating - DC Response Time Applications Electrical, Industrial Features - Class T Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension Fast Fast - Clettrical, Industrial - CE, CSA, UL CONSA CE, CSA, UL CE, CSA, UL CONSA CONS	Current Rating	15A
Response Time Applications Electrical, Industrial Features - Class T Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension Fast Electrical, Industrial CE, CSA, UL CE, CSA, UL CE, CSA, UL CE, CSA, UL COPERATION OF COMMENT OF CO	Voltage Rating - AC	600V
Applications Electrical, Industrial Features - Class T Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.560" Dia x 1.500" W (14.22mm x 38.10mm)	Voltage Rating - DC	-
Features - Class T Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.560" Dia x 1.500" W (14.22mm x 38.10mm)	Response Time	Fast
Class T Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.560" Dia x 1.500" W (14.22mm x 38.10mm)	Applications	Electrical, Industrial
Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension CE, CSA, UL - CUL CHA CON	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension O.560" Dia x 1.500" W (14.22mm x 38.10mm)	Class	Т
Breaking Capacity @ Rated Voltage 200kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.560" Dia x 1.500" W (14.22mm x 38.10mm)	Approvals	CE, CSA, UL
Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.560" Dia x 1.500" W (14.22mm x 38.10mm)	Operating Temperature	-
Package / Case Cartridge, Non-Standard Size / Dimension 0.560" Dia x 1.500" W (14.22mm x 38.10mm)	Breaking Capacity @ Rated Voltage	200kA
Size / Dimension 0.560" Dia x 1.500" W (14.22mm x 38.10mm)	Mounting Type	Holder
	Package / Case	Cartridge, Non-Standard
Report errors?	Size / Dimension	0.560" Dia x 1.500" W (14.22mm x 38.10mm)
		Report errors?

JJS-15LS Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

JJS-15LS Payment Methods





















JJS-15LS Shipping Methods













If you have any question about JJS-15LS, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com