

Heisener.com

### **JJS-2 Information**

Part Number JJS-2 Manufacturer Eaton

Category Circuit Protection

Electrical, Specialty Fuses

**Description** FUSE CARTRIDGE 2A 600VAC NON STD

Package Cartridge, Non-Standard

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **JJS-2 Specifications**

Manufacturer Part NumberJJS-2ManufacturerEatonCategoryCircuit ProtectionBeackageCartridge, Non-StandardSeriesLimitron? JJSFuse TypeCartridgeCurrent Rating2AVoltage Rating - AC600VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-ClassTApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.560" Dia x 1.500" W (14.22mm x 38.10mm)		
CategoryCircuit ProtectionPackageCartridge, Non-StandardSeriesLimitron? JJSFuse TypeCartridgeCurrent Rating2AVoltage Rating - AC600VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-ClassTApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.560" Dia x 1.500" W (14.22mm x 38.10mm)	Manufacturer Part Number	JJS-2
PackageCartridge, Non-StandardSeriesLimitron? JJSFuse TypeCartridgeCurrent Rating2AVoltage Rating - AC600VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-ClassTApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.560" Dia x 1.500" W (14.22mm x 38.10mm)	Manufacturer	Eaton
PackageCartridge, Non-StandardSeriesLimitron? JJSFuse TypeCartridgeCurrent Rating2AVoltage Rating - AC600VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-ClassTApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.560" Dia x 1.500" W (14.22mm x 38.10mm)	Category	Circuit Protection
SeriesLimitron? JJSFuse TypeCartridgeCurrent Rating2AVoltage Rating - AC600VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-ClassTApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.560" Dia x 1.500" W (14.22mm x 38.10mm)		Electrical, Specialty Fuses
Fuse Type Current Rating 2A Voltage Rating - AC Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class T Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension  Cartridge Co0V  Cartridge Certridge Cartridge Cartridge Cartridge Cartridge, Non-Standard Size / Dimension  Cartridge Coov Cartridge	Package	Cartridge, Non-Standard
Current Rating Voltage Rating - AC  Voltage Rating - DC  Response Time Fast  Applications Electrical, Industrial  Features - Class T  Approvals CE, CSA, UL  Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension  2A  600V	Series	Limitron? JJS
Voltage Rating - AC  Voltage Rating - DC  Response Time  Fast  Applications  Electrical, Industrial  Features  - Class  T  Approvals  CE, CSA, UL  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Size / Dimension  600V  60	Fuse Type	Cartridge
Voltage Rating - DC  Response Time Fast  Applications Electrical, Industrial  Features - Class T  Approvals CE, CSA, UL  Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder  Package / Case Size / Dimension  - Casting Capacity @ Rated Voltage Cartridge, Non-Standard Size / Dimension  - Casting Capacity @ (14.22mm x 38.10mm)	Current Rating	2A
Response Time Fast Applications Electrical, Industrial Features - Class T Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.560" Dia x 1.500" W (14.22mm x 38.10mm)	Voltage Rating - AC	600V
Applications Electrical, Industrial  Features - Class T  Approvals CE, CSA, UL  Operating Temperature - Breaking Capacity @ Rated Voltage 200kA  Mounting Type Holder  Package / Case Cartridge, Non-Standard Size / Dimension 0.560" Dia x 1.500" W (14.22mm x 38.10mm)	Voltage Rating - DC	-
Features - Class T  Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.560" Dia x 1.500" W (14.22mm x 38.10mm)	Response Time	Fast
Class T Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.560" Dia x 1.500" W (14.22mm x 38.10mm)	Applications	Electrical, Industrial
Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.560" Dia x 1.500" W (14.22mm x 38.10mm)	Features	-
Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Cartridge, Non-Standard  Size / Dimension  O.560" Dia x 1.500" W (14.22mm x 38.10mm)	Class	T
Breaking Capacity @ Rated Voltage 200kA  Mounting Type Holder  Package / Case Cartridge, Non-Standard  Size / Dimension 0.560" Dia x 1.500" W (14.22mm x 38.10mm)	Approvals	CE, CSA, UL
Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.560" Dia x 1.500" W (14.22mm x 38.10mm)	Operating Temperature	-
Package / Case Cartridge, Non-Standard Size / Dimension 0.560" Dia x 1.500" W (14.22mm x 38.10mm)	Breaking Capacity @ Rated Voltage	200kA
Size / Dimension 0.560" Dia x 1.500" W (14.22mm x 38.10mm)	Mounting Type	Holder
· · ·	Package / Case	Cartridge, Non-Standard
D ( 0	Size / Dimension	0.560" Dia x 1.500" W (14.22mm x 38.10mm)
Report errors?		Report errors?

#### **JJS-2 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **JJS-2 Payment Methods**





















# **JJS-2 Shipping Methods**













If you have any question about JJS-2, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com