

Heisener.com

JKS-8 Information

Part Number JKS-8 Manufacturer Eaton

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CARTRIDGE NON STD

Package Cartridge, Non-Standard

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









JKS-8 Specifications

| Manufacturer Part NumberJKS-8ManufacturerEatonCategoryCircuit ProtectionBeckageCartridge, Non-StandardSeriesLimitron? JKSFuse TypeCartridgeCurrent Rating8AVoltage Rating - AC600VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-ClassJApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.810" Dia x 2.250" L (20.57mm x 57.15mm)Report errors? | | |
|--|-----------------------------------|---|
| CategoryCircuit Protection Electrical, Specialty FusesPackageCartridge, Non-StandardSeriesLimitron? JKSFuse TypeCartridgeCurrent Rating8AVoltage Rating - AC600VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-ClassJApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.810" Dia x 2.250" L (20.57mm x 57.15mm) | Manufacturer Part Number | JKS-8 |
| PackageElectrical, Specialty FusesPackageCartridge, Non-StandardSeriesLimitron? JKSFuse TypeCartridgeCurrent Rating8AVoltage Rating - AC600VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-ClassJApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.810" Dia x 2.250" L (20.57mm x 57.15mm) | Manufacturer | Eaton |
| PackageCartridge, Non-StandardSeriesLimitron? JKSFuse TypeCartridgeCurrent Rating8AVoltage Rating - AC600VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-ClassJApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.810" Dia x 2.250" L (20.57mm x 57.15mm) | Category | Circuit Protection |
| SeriesLimitron? JKSFuse TypeCartridgeCurrent Rating8AVoltage Rating - AC600VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-ClassJApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.810" Dia x 2.250" L (20.57mm x 57.15mm) | | Electrical, Specialty Fuses |
| Fuse Type Current Rating 8A Voltage Rating - AC 600V Voltage Rating - DC | Package | Cartridge, Non-Standard |
| Current Rating Voltage Rating - AC 600V Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class J Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 8A 600V | Series | Limitron? JKS |
| Voltage Rating - AC Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class J Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 600V 60 | Fuse Type | Cartridge |
| Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class J Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension - Cartridge, Non-Standard Size / Dimension - Size / Dimension - Six / Si | Current Rating | 8A |
| Response Time Applications Electrical, Industrial Features - Class J Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension Fast Electrical, Industrial CE, CSA, UL - CE, C | Voltage Rating - AC | 600V |
| Applications Electrical, Industrial Features - Class J Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.810" Dia x 2.250" L (20.57mm x 57.15mm) | Voltage Rating - DC | - |
| Features - Class J S S J S S S S S S S S S S S S S S S | Response Time | Fast |
| Class J Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.810" Dia x 2.250" L (20.57mm x 57.15mm) | Applications | Electrical, Industrial |
| Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension CE, CSA, UL - CREATING CAPACITY CONTROL OF CONTROL OF CAPACITY CAPACIT | Features | - |
| Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.810" Dia x 2.250" L (20.57mm x 57.15mm) | Class | J |
| Breaking Capacity @ Rated Voltage 200kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.810" Dia x 2.250" L (20.57mm x 57.15mm) | Approvals | CE, CSA, UL |
| Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.810" Dia x 2.250" L (20.57mm x 57.15mm) | Operating Temperature | - |
| Package / Case Cartridge, Non-Standard Size / Dimension 0.810" Dia x 2.250" L (20.57mm x 57.15mm) | Breaking Capacity @ Rated Voltage | 200kA |
| Size / Dimension 0.810" Dia x 2.250" L (20.57mm x 57.15mm) | Mounting Type | Holder |
| | Package / Case | Cartridge, Non-Standard |
| Report errors? | Size / Dimension | 0.810" Dia x 2.250" L (20.57mm x 57.15mm) |
| | | Report errors? |

JKS-8 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

JKS-8 Payment Methods





















JKS-8 Shipping Methods













If you have any question about JKS-8, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com