



### **JLLN035.T Information**

Heisener.com

Part Number JLLN035.T

Manufacturer Littelfuse Inc.

Category Circuit Protection

Electrical, Specialty Fuses

**Description** FUSE CARTRIDGE 35A 300VAC/160VDC

Package Cartridge, Non-Standard

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **JLLN035.T Specifications**

Manufacturer Part NumberJLLN035.TManufacturerLittelfuse Inc.CategoryCircuit ProtectionElectrical, Specialty FusesPackageCartridge, Non-StandardSeriesPOWR-GARD? JLLNFuse TypeCartridgeCurrent Rating35AVoltage Rating - AC300VVoltage Rating - DC160VResponse TimeFastApplicationsElectrical, IndustrialFeatures-ClassTApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.563" Dia x 0.874" L (14.30mm x 22.20mm)Report errors?		
CategoryCircuit Protection Electrical, Specialty FusesPackageCartridge, Non-StandardSeriesPOWR-GARD? JLLNFuse TypeCartridgeCurrent Rating35AVoltage Rating - AC300VVoltage Rating - DC160VResponse TimeFastApplicationsElectrical, IndustrialFeatures-ClassTApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.563" Dia x 0.874" L (14.30mm x 22.20mm)	Manufacturer Part Number	JLLN035.T
Electrical, Specialty Fuses  Package Cartridge, Non-Standard  Series POWR-GARD? JLLN  Fuse Type Cartridge  Current Rating 35A  Voltage Rating - AC 300V  Voltage Rating - DC 160V  Response Time Fast  Applications Electrical, Industrial  Features - Class T  Approvals CE, CSA, UR  Operating Temperature - Breaking Capacity @ Rated Voltage County (Package / Case Cartridge, Non-Standard Size / Dimension (9.563" Dia x 0.874" L (14.30mm x 22.20mm)	Manufacturer	Littelfuse Inc.
PackageCartridge, Non-StandardSeriesPOWR-GARD? JLLNFuse TypeCartridgeCurrent Rating35AVoltage Rating - AC300VVoltage Rating - DC160VResponse TimeFastApplicationsElectrical, IndustrialFeatures-ClassTApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.563" Dia x 0.874" L (14.30mm x 22.20mm)	Category	Circuit Protection
SeriesPOWR-GARD? JLLNFuse TypeCartridgeCurrent Rating35AVoltage Rating - AC300VVoltage Rating - DC160VResponse TimeFastApplicationsElectrical, IndustrialFeatures-ClassTApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.563" Dia x 0.874" L (14.30mm x 22.20mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating35AVoltage Rating - AC300VVoltage Rating - DC160VResponse TimeFastApplicationsElectrical, IndustrialFeatures-ClassTApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.563" Dia x 0.874" L (14.30mm x 22.20mm)	Package	Cartridge, Non-Standard
Current Rating Voltage Rating - AC 300V Voltage Rating - DC 160V Response Time Fast Applications Electrical, Industrial Features - Class T Approvals CE, CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension  35A 300V 300V 300V 300V 300V 400V 500V 500V 500V 500V 500V 500V 5	Series	POWR-GARD? JLLN
Voltage Rating - AC  Voltage Rating - DC  160V  Response Time Fast  Applications Electrical, Industrial  Features - Class T  Approvals CE, CSA, UR  Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder  Package / Case Size / Dimension  300V  160V	Fuse Type	Cartridge
Voltage Rating - DC  Response Time Fast  Applications Electrical, Industrial  Features - Class T  Approvals CE, CSA, UR  Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder  Package / Case Size / Dimension  160V  Fast Fast CE, CSA  Electrical, Industrial  CE, CSA  T  CE, CSA, UR  CE, CSA, UR  CE, CSA, UR  COPITATION OF TABLE OF	Current Rating	35A
Response Time Applications Electrical, Industrial Features - Class T Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension Fast Electrical, Industrial  CE, CSA, UR -	Voltage Rating - AC	300V
Applications Electrical, Industrial  Features - Class T  Approvals CE, CSA, UR  Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC  Mounting Type Holder  Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 0.874" L (14.30mm x 22.20mm)	Voltage Rating - DC	160V
Features - Class T   Approvals CE, CSA, UR   Operating Temperature -  Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC   Mounting Type Holder   Package / Case Cartridge, Non-Standard   Size / Dimension 0.563" Dia x 0.874" L (14.30mm x 22.20mm)	Response Time	Fast
Class T Approvals CE, CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 0.874" L (14.30mm x 22.20mm)	Applications	Electrical, Industrial
Approvals CE, CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 0.874" L (14.30mm x 22.20mm)	Features	-
Operating Temperature  Breaking Capacity @ Rated Voltage  200kA AC, 20kA DC  Mounting Type  Holder  Package / Case  Cartridge, Non-Standard  Size / Dimension  0.563" Dia x 0.874" L (14.30mm x 22.20mm)	Class	T
Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC  Mounting Type Holder  Package / Case Cartridge, Non-Standard  Size / Dimension 0.563" Dia x 0.874" L (14.30mm x 22.20mm)	Approvals	CE, CSA, UR
Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 0.874" L (14.30mm x 22.20mm)	Operating Temperature	-
Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 0.874" L (14.30mm x 22.20mm)	Breaking Capacity @ Rated Voltage	200kA AC, 20kA DC
Size / Dimension 0.563" Dia x 0.874" L (14.30mm x 22.20mm)	Mounting Type	Holder
	Package / Case	Cartridge, Non-Standard
Report errors?	Size / Dimension	0.563" Dia x 0.874" L (14.30mm x 22.20mm)
		Report errors?

#### **JLLN035.T Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **JLLN035.T Payment Methods**



















### **JLLN035.T Shipping Methods**













If you have any question about JLLN035.T, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com