

### **JLLN070.V Information**

( Heisener.com

Part NumberJLLN070.VManufacturerLittelfuse Inc.CategoryCircuit Protection

Electrical, Specialty Fuses

**Description** FUSE CARTRIDGE 70A 300VAC/125VDC

Package Cylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **JLLN070.V Specifications**

Manufacturer Part NumberJLLN070.VManufacturerLittelfuse Inc.CategoryCircuit Protection Electrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? JLLNFuse TypeCartridgeCurrent Rating70AVoltage Rating - AC300VVoltage Rating - DC125VResponse TimeFastApplicationsElectrical, IndustrialFeatures-ClassTApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.811" Dia x 0.843" L (20.60mm x 21.40mm)		
Category Electrical, Specialty Fuses  Package Cylindrical, Blade Terminal (Bolt) Series POWR-GARD? JLLN Fuse Type Cartridge Current Rating 70A Voltage Rating - AC Voltage Rating - DC 125V Response Time Fast Applications Electrical, Industrial Features - Class T Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension  Circuit Protection Electrical, Specialty Fuses Cylindrical, Blade Terminal (Bolt) Size / Dimension  Circuit Protection Electrical, Specialty Fuses Captridge Captridge Captridge Captridge Cylindrical, Blade Terminal (Bolt) Size / Dimension  Cylindrical, Blade Terminal (Bolt)	Manufacturer Part Number	JLLN070.V
Electrical, Specialty Fuses  Package Cylindrical, Blade Terminal (Bolt)  Series POWR-GARD? JLLN  Fuse Type Cartridge  Current Rating 70A  Voltage Rating - AC 300V  Voltage Rating - DC 125V  Response Time Fast  Applications Electrical, Industrial  Features - Class T  Approvals CE, CSA, UL  Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC  Mounting Type Bolt Mount  Package / Case Cylindrical, Blade Terminal (Bolt)  Size / Dimension 0.811" Dia x 0.843" L (20.60mm x 21.40mm)	Manufacturer	Littelfuse Inc.
PackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? JLLNFuse TypeCartridgeCurrent Rating70AVoltage Rating - AC300VVoltage Rating - DC125VResponse TimeFastApplicationsElectrical, IndustrialFeatures-ClassTApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.811" Dia x 0.843" L (20.60mm x 21.40mm)	Category	Circuit Protection
SeriesPOWR-GARD? JLLNFuse TypeCartridgeCurrent Rating70AVoltage Rating - AC300VVoltage Rating - DC125VResponse TimeFastApplicationsElectrical, IndustrialFeatures-ClassTApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.811" Dia x 0.843" L (20.60mm x 21.40mm)		Electrical, Specialty Fuses
Fuse Type Current Rating 70A  Voltage Rating - AC 300V  Voltage Rating - DC 125V  Response Time Fast Applications Electrical, Industrial Features - Class T  Approvals CE, CSA, UL  Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension  Cartridge Cartridge Cartridge Cartridge Cartridge Cond ADA  OVA  ADA  CE, CSA  CSA, UL  CE, CSA, UL  COLSA  CUINDRICA  COLSA  CO	Package	Cylindrical, Blade Terminal (Bolt)
Current Rating Voltage Rating - AC 300V Voltage Rating - DC 125V Response Time Fast Applications Electrical, Industrial Features - Class T Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Size / Dimension Follows Size / Dimension Size / Dimens	Series	POWR-GARD? JLLN
Voltage Rating - AC  Voltage Rating - DC  125V  Response Time Fast  Applications Electrical, Industrial  Features - Class T  Approvals CE, CSA, UL  Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Size / Dimension  300V  125V  125V  125V  Fast  Clectrical, Industrial  CE, CSA, UL  CE, CSA, UL  CE, CSA, UL  CYLINGTON  CE, CSA, UL  CONA AC, 20kA DC  Bolt Mount  CYLINGTON  CYLINGTON  0.811" Dia x 0.843" L (20.60mm x 21.40mm)	Fuse Type	Cartridge
Voltage Rating - DC  Response Time Fast  Applications Electrical, Industrial  Features - Class T  Approvals CE, CSA, UL  Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension  125V	Current Rating	70A
Response Time Applications Electrical, Industrial Features - Class T Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Fast Electrical, Industrial Fast CE, CSA, UL CE, CSA, U	Voltage Rating - AC	300V
Applications Electrical, Industrial  Features - Class T  Approvals CE, CSA, UL  Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC  Mounting Type Bolt Mount  Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.811" Dia x 0.843" L (20.60mm x 21.40mm)	Voltage Rating - DC	125V
Features - Class T   Approvals CE, CSA, UL   Operating Temperature -  Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC   Mounting Type Bolt Mount   Package / Case Cylindrical, Blade Terminal (Bolt)   Size / Dimension 0.811" Dia x 0.843" L (20.60mm x 21.40mm)	Response Time	Fast
Class T Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.811" Dia x 0.843" L (20.60mm x 21.40mm)	Applications	Electrical, Industrial
Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.811" Dia x 0.843" L (20.60mm x 21.40mm)	Features	-
Operating Temperature  Breaking Capacity @ Rated Voltage  200kA AC, 20kA DC  Mounting Type  Bolt Mount  Package / Case  Cylindrical, Blade Terminal (Bolt)  Size / Dimension  0.811" Dia x 0.843" L (20.60mm x 21.40mm)	Class	T
Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC  Mounting Type Bolt Mount  Package / Case Cylindrical, Blade Terminal (Bolt)  Size / Dimension 0.811" Dia x 0.843" L (20.60mm x 21.40mm)	Approvals	CE, CSA, UL
Mounting Type  Bolt Mount  Package / Case  Cylindrical, Blade Terminal (Bolt)  Size / Dimension  0.811" Dia x 0.843" L (20.60mm x 21.40mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.811" Dia x 0.843" L (20.60mm x 21.40mm)	Breaking Capacity @ Rated Voltage	200kA AC, 20kA DC
Size / Dimension 0.811" Dia x 0.843" L (20.60mm x 21.40mm)	Mounting Type	Bolt Mount
	Package / Case	Cylindrical, Blade Terminal (Bolt)
Report errors?	Size / Dimension	0.811" Dia x 0.843" L (20.60mm x 21.40mm)
× ·		Report errors?

#### **JLLN070.V Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# **JLLN070.V** Payment Methods



















## **JLLN070.V Shipping Methods**













If you have any question about JLLN070.V, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com