



JLLN1200X Information

Heisener.com

Part NumberJLLN1200XManufacturerLittelfuse Inc.CategoryCircuit Protection

Electrical, Specialty Fuses

Description FUSE CRTRDGE 1.2KA 300VAC/125VDC

Package Cylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









JLLN1200X Specifications

Manufacturer Part NumberJLLN1200XManufacturerLittelfuse Inc.CategoryCircuit ProtectionBecktical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? JLLNFuse TypeCartridgeCurrent Rating1.2kAVoltage Rating - AC300VVoltage Rating - DC125VResponse TimeFastApplicationsElectrical, IndustrialFeatures-ClassTApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension2.500" Dia x 1.032" L (63.50mm x 26.20mm)		
Category Electrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series POWR-GARD? JLLN Fuse Type Cartridge Current Rating 1.2kA Voltage Rating - AC 300V Voltage Rating - DC 125V Response Time Fast Applications Electrical, Industrial Features - Class T Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Circuit Protection Electrical, Specialty Fuses Cylindrical, Blade Terminal (Bolt) Size / Dimension Circuit Protection Electrical, Specialty Fuses Captridge Captridge Captridge Captridge Cylindrical, Blade Terminal (Bolt) Size / Dimension Cylindrical, Blade Terminal (Bolt)	Manufacturer Part Number	JLLN1200X
Electrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series POWR-GARD? JLLN Fuse Type Cartridge Current Rating 1.2kA Voltage Rating - AC 300V Voltage Rating - DC 125V Response Time Fast Applications Electrical, Industrial Features - Class T Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage COKA AC, 20kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.500" Dia x 1.032" L (63.50mm x 26.20mm)	Manufacturer	Littelfuse Inc.
PackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? JLLNFuse TypeCartridgeCurrent Rating1.2kAVoltage Rating - AC300VVoltage Rating - DC125VResponse TimeFastApplicationsElectrical, IndustrialFeatures-ClassTApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension2.500" Dia x 1.032" L (63.50mm x 26.20mm)	Category	Circuit Protection
SeriesPOWR-GARD? JLLNFuse TypeCartridgeCurrent Rating1.2kAVoltage Rating - AC300VVoltage Rating - DC125VResponse TimeFastApplicationsElectrical, IndustrialFeatures-ClassTApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension2.500" Dia x 1.032" L (63.50mm x 26.20mm)		Electrical, Specialty Fuses
Fuse Type Current Rating 1.2kA Voltage Rating - AC 300V Voltage Rating - DC 125V Response Time Fast Applications Electrical, Industrial Features - Class T Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Cartridge 1.2kA Cartridge 1.2kA Cartridge 1.2kA 300V 125V Response Fast Features CE, CSA CU	Package	Cylindrical, Blade Terminal (Bolt)
Current Rating Voltage Rating - AC 300V Voltage Rating - DC 125V Response Time Fast Applications Electrical, Industrial Features - Class T Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Size / Dimension 1.2kA 300V 125V Response Time Fast Fast CE, CSA COL	Series	POWR-GARD? JLLN
Voltage Rating - AC Voltage Rating - DC 125V Response Time Fast Applications Electrical, Industrial Features - Class T Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Size / Dimension 300V 200V 200V AU 200V 300V 200V 300V AU 200V 300V AU 200V 300V 300V 400 400 400 400 400	Fuse Type	Cartridge
Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class T Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 125V	Current Rating	1.2kA
Response Time Applications Electrical, Industrial Features - Class T Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Fast Electrical, Industrial Feature - CE, CSA, UL OPERATION OF THE PROPERTY	Voltage Rating - AC	300V
Applications Electrical, Industrial Features - Class T Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.500" Dia x 1.032" L (63.50mm x 26.20mm)	Voltage Rating - DC	125V
Features - Class T Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.500" Dia x 1.032" L (63.50mm x 26.20mm)	Response Time	Fast
Class T Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.500" Dia x 1.032" L (63.50mm x 26.20mm)	Applications	Electrical, Industrial
Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.500" Dia x 1.032" L (63.50mm x 26.20mm)	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.500" Dia x 1.032" L (63.50mm x 26.20mm)	Class	T
Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.500" Dia x 1.032" L (63.50mm x 26.20mm)	Approvals	CE, CSA, UL
Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.500" Dia x 1.032" L (63.50mm x 26.20mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.500" Dia x 1.032" L (63.50mm x 26.20mm)	Breaking Capacity @ Rated Voltage	200kA AC, 20kA DC
Size / Dimension 2.500" Dia x 1.032" L (63.50mm x 26.20mm)	Mounting Type	Bolt Mount
	Package / Case	Cylindrical, Blade Terminal (Bolt)
Report errors?	Size / Dimension	2.500" Dia x 1.032" L (63.50mm x 26.20mm)
		Report errors?

JLLN1200X Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

JLLN1200X Payment Methods



















JLLN1200X Shipping Methods













If you have any question about JLLN1200X, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com