

JLLN250.X Information

Heisener.com

For Reference Only

Part Number JLLN250.X

Manufacturer Littelfuse Inc.

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CRTRDGE 250A 300VAC/125VDC

Package Cylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









JLLN250.X Specifications

Manufacturer Part NumberJLLN250.XManufacturerLittelfuse Inc.CategoryCircuit ProtectionElectrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? JLLNFuse TypeCartridgeCurrent Rating250AVoltage Rating - AC300VVoltage Rating - DC125VResponse TimeFastApplicationsElectrical, IndustrialFeatures-ClassTApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.311" Dia x 0.827" L (33.30mm x 21.00mm)Report errors?		
CategoryCircuit Protection Electrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? JLLNFuse TypeCartridgeCurrent Rating250AVoltage Rating - AC300VVoltage Rating - DC125VResponse TimeFastApplicationsElectrical, IndustrialFeatures-ClassTApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.311" Dia x 0.827" L (33.30mm x 21.00mm)	Manufacturer Part Number	JLLN250.X
Electrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series POWR-GARD? JLLN Fuse Type Cartridge Current Rating 250A Voltage Rating - AC 300V Voltage Rating - DC 125V Response Time Fast Applications Electrical, Industrial Features - Class T Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.311" Dia x 0.827" L (33.30mm x 21.00mm)	Manufacturer	Littelfuse Inc.
PackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? JLLNFuse TypeCartridgeCurrent Rating250AVoltage Rating - AC300VVoltage Rating - DC125VResponse TimeFastApplicationsElectrical, IndustrialFeatures-ClassTApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.311" Dia x 0.827" L (33.30mm x 21.00mm)	Category	Circuit Protection
Series POWR-GARD? JLLN Fuse Type Cartridge Current Rating 250A Voltage Rating - AC 300V Voltage Rating - DC 125V Response Time Fast Applications Electrical, Industrial Features - Class T Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.311" Dia x 0.827" L (33.30mm x 21.00mm)		Electrical, Specialty Fuses
Fuse Type Current Rating 250A Voltage Rating - AC 300V Voltage Rating - DC 125V Response Time Fast Applications Electrical, Industrial Features - Class T Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Cartridge Cartridge Cartridge Cartridge Cartridge Capacity @ Cartridge Capacity @ Rated Voltage Capacity @ Rated Voltage Cylindrical, Blade Terminal (Bolt) Size / Dimension Cartridge Capacity @ Cartridge Capacity @ Capacity	Package	Cylindrical, Blade Terminal (Bolt)
Current Rating Voltage Rating - AC 300V Voltage Rating - DC 125V Response Time Fast Applications Electrical, Industrial Features - Class T Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Size / Dimension 250A 200V 200V 200V 200V 200V 200V 200V 200KA AC, 20KA DC Bolt Mount Cylindrical, Blade Terminal (Bolt) 1.311" Dia x 0.827" L (33.30mm x 21.00mm)	Series	POWR-GARD? JLLN
Voltage Rating - AC Voltage Rating - DC 125V Response Time Fast Applications Electrical, Industrial Features - Class T Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 300V 300V 300V 300V 300V 300V 400 405 405 405 405 405 405 405 405 405	Fuse Type	Cartridge
Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class T Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.311" Dia x 0.827" L (33.30mm x 21.00mm)	Current Rating	250A
Response Time Applications Electrical, Industrial Features - Class T Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Fast Electrical, Industrial CE, CSA, UL CE, CSA, UL Operating Temperature - Substituting Type Cylindrical, Blade Terminal (Bolt) 1.311" Dia x 0.827" L (33.30mm x 21.00mm)	Voltage Rating - AC	300V
Applications Electrical, Industrial Features - Class T Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.311" Dia x 0.827" L (33.30mm x 21.00mm)	Voltage Rating - DC	125V
Features - Class T Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.311" Dia x 0.827" L (33.30mm x 21.00mm)	Response Time	Fast
Class T Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.311" Dia x 0.827" L (33.30mm x 21.00mm)	Applications	Electrical, Industrial
Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.311" Dia x 0.827" L (33.30mm x 21.00mm)	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.311" Dia x 0.827" L (33.30mm x 21.00mm)	Class	T
Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.311" Dia x 0.827" L (33.30mm x 21.00mm)	Approvals	CE, CSA, UL
Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.311" Dia x 0.827" L (33.30mm x 21.00mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.311" Dia x 0.827" L (33.30mm x 21.00mm)	Breaking Capacity @ Rated Voltage	200kA AC, 20kA DC
Size / Dimension 1.311" Dia x 0.827" L (33.30mm x 21.00mm)	Mounting Type	Bolt Mount
	Package / Case	Cylindrical, Blade Terminal (Bolt)
Report errors?	Size / Dimension	1.311" Dia x 0.827" L (33.30mm x 21.00mm)
		Report errors?

JLLN250.X Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

JLLN250.X Payment Methods



















JLLN250.X Shipping Methods













If you have any question about JLLN250.X, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com