



JLLS001.T Information

Heisener.com

Part Number JLLS001.T

Manufacturer Littelfuse Inc.

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CARTRIDGE 1A 600VAC/300VDC

Package Cartridge, Non-Standard

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









JLLS001.T Specifications

Manufacturer Part NumberJLLS001.TManufacturerLittelfuse Inc.CategoryCircuit ProtectionPackageCartridge, Non-StandardSeriesPOWR-GARD? JLLSFuse TypeCartridgeCurrent Rating1AVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeFastApplicationsElectrical, IndustrialFeatures-ClassTApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.563" Dia x 1.500" L (14.30mm x 38.10mm)Report errors?		
Category Electrical, Specialty Fuses Package Cartridge, Non-Standard Series POWR-GARD? JLLS Fuse Type Cartridge Current Rating 1A Voltage Rating - AC Voltage Rating - DC Seponse Time Fast Applications Electrical, Industrial Features - Class T Approvals CE, CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension Cirridge Cartridge Cartridge Cartridge Cartridge Cartridge Cartridge Cartridge, Non-Standard Size / Dimension Cartridge, Non-Standard Size / Dimension Cartridge, Non-Standard Size / Dimension	Manufacturer Part Number	JLLS001.T
Electrical, Specialty Fuses Package Cartridge, Non-Standard Series POWR-GARD? JLLS Fuse Type Cartridge Current Rating 1A Voltage Rating - AC 600V Voltage Rating - DC 300V Response Time Fast Applications Electrical, Industrial Features - Class T Approvals CE, CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage 200kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 1.500" L (14.30mm x 38.10mm)	Manufacturer	Littelfuse Inc.
PackageCartridge, Non-StandardSeriesPOWR-GARD? JLLSFuse TypeCartridgeCurrent Rating1AVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeFastApplicationsElectrical, IndustrialFeatures-ClassTApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.563" Dia x 1.500" L (14.30mm x 38.10mm)	Category	Circuit Protection
SeriesPOWR-GARD? JLLSFuse TypeCartridgeCurrent Rating1AVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeFastApplicationsElectrical, IndustrialFeatures-ClassTApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.563" Dia x 1.500" L (14.30mm x 38.10mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating1AVoltage Rating - AC600 VVoltage Rating - DC300 VResponse TimeFastApplicationsElectrical, IndustrialFeatures-ClassTApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.563" Dia x 1.500" L (14.30mm x 38.10mm)	Package	Cartridge, Non-Standard
Current Rating Voltage Rating - AC 600V Voltage Rating - DC 300V Response Time Fast Applications Electrical, Industrial Features - Class T Approvals CE, CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 1A 600V 60	Series	POWR-GARD? JLLS
Voltage Rating - AC Voltage Rating - DC 300V Response Time Fast Applications Electrical, Industrial Features - Class T Approvals CE, CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 600V	Fuse Type	Cartridge
Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class T Approvals CE, CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 300V 300V 300V 300V Fast Electrical, Industrial CE, CSA, UR CE, CSA, UR CE, CSA, UR CE, CSA, UR COPITATION OF TABLE OF TA	Current Rating	1A
Response Time Applications Electrical, Industrial Features - Class T Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension Fast Electrical, Industrial CE, CSA, UR -	Voltage Rating - AC	600V
Applications Electrical, Industrial Features - Class T Approvals CE, CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 1.500" L (14.30mm x 38.10mm)	Voltage Rating - DC	300V
Features - Class T Approvals CE, CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 1.500" L (14.30mm x 38.10mm)	Response Time	Fast
Class T Approvals CE, CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 1.500" L (14.30mm x 38.10mm)	Applications	Electrical, Industrial
Approvals CE, CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension CE, CSA, UR - Cuthor Company Canadary - Canadary Capacity @ Rated Voltage Canadary Capacity @ Rated Voltage Control Capacity Capaci	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 1.500" L (14.30mm x 38.10mm)	Class	T
Breaking Capacity @ Rated Voltage 200kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 1.500" L (14.30mm x 38.10mm)	Approvals	CE, CSA, UR
Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 1.500" L (14.30mm x 38.10mm)	Operating Temperature	-
Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 1.500" L (14.30mm x 38.10mm)	Breaking Capacity @ Rated Voltage	200kA
Size / Dimension 0.563" Dia x 1.500" L (14.30mm x 38.10mm)	Mounting Type	Holder
	Package / Case	Cartridge, Non-Standard
Report errors?	Size / Dimension	0.563" Dia x 1.500" L (14.30mm x 38.10mm)
		Report errors?

JLLS001.T Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

JLLS001.T Payment Methods



















JLLS001.T Shipping Methods













If you have any question about JLLS001.T, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com