

JLLS080.V Information

Categ

Part Number JLLS080.V

Manufacturer Littelfuse Inc.

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CARTRIDGE 80A 600VAC/300VDC

Package Cylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









JLLS080.V Specifications

Manufacturer Part NumberJLLS080.VManufacturerLittelfuse Inc.CategoryCircuit ProtectionBecktical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? JLLSFuse TypeCartridgeCurrent Rating80AVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeFastApplicationsElectrical, IndustrialFeatures-ClassTApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.811" Dia x 1.642" L (20.60mm x 41.70mm)		
Category Electrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series POWR-GARD? JLLS Fuse Type Cartridge Current Rating 80A Voltage Rating - AC Voltage Rating - DC 800V Voltage Rating - DC 800V Response Time Fast Applications Electrical, Industrial Features - Class T Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Circuit Protection Electrical, Specialty Fuses Cylindrical, Blade Terminal (Bolt) Size / Dimension Circuit Protection Electrical, Industrial Capacity @ Rated Voltage Bolt Mount Size / Dimension Circuit Protection Electrical, Industrial Capacity @ Rated Voltage CE, CSA, UL Operating Temperature - Class CUIndrical, Blade Terminal (Bolt) Size / Dimension	Manufacturer Part Number	JLLS080.V
Electrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series POWR-GARD? JLLS Fuse Type Cartridge Current Rating 80A Voltage Rating - AC 600V Voltage Rating - DC 300V Response Time Fast Applications Electrical, Industrial Features - Class T Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.811" Dia x 1.642" L (20.60mm x 41.70mm)	Manufacturer	Littelfuse Inc.
PackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? JLLSFuse TypeCartridgeCurrent Rating80AVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeFastApplicationsElectrical, IndustrialFeatures-ClassTApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.811" Dia x 1.642" L (20.60mm x 41.70mm)	Category	Circuit Protection
SeriesPOWR-GARD? JLLSFuse TypeCartridgeCurrent Rating80AVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeFastApplicationsElectrical, IndustrialFeatures-ClassTApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.811" Dia x 1.642" L (20.60mm x 41.70mm)		Electrical, Specialty Fuses
Fuse Type Current Rating 80A Voltage Rating - AC 600V Voltage Rating - DC 300V Response Time Fast Applications Electrical, Industrial Features - Class T Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Cartridge ApA Cartridge Cartridge ADA 80A 600V CE, CSA CE, CSA CU CUIndrical, Blade Terminal (Bolt) Size / Dimension Cartridge ADA Size / Dimension Cartridge ADA Size / Dimension	Package	Cylindrical, Blade Terminal (Bolt)
Current Rating Voltage Rating - AC 600V Voltage Rating - DC 300V Response Time Fast Applications Electrical, Industrial Features - Class T Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Size / Dimension 80A 80A 80A 80A 80A 80A 80A 80	Series	POWR-GARD? JLLS
Voltage Rating - AC Voltage Rating - DC 300V Response Time Fast Applications Electrical, Industrial Features - Class T Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Size / Dimension 600V 60	Fuse Type	Cartridge
Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class T Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Size / Dimension Size / Siz	Current Rating	80A
Response Time Applications Electrical, Industrial Features - Class T Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Fast Electrical, Industrial CE, CSA, UL - Black CE, CSA, UL -	Voltage Rating - AC	600V
Applications Electrical, Industrial Features - Class T Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.811" Dia x 1.642" L (20.60mm x 41.70mm)	Voltage Rating - DC	300V
Features - Class T Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.811" Dia x 1.642" L (20.60mm x 41.70mm)	Response Time	Fast
Class T Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.811" Dia x 1.642" L (20.60mm x 41.70mm)	Applications	Electrical, Industrial
Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.811" Dia x 1.642" L (20.60mm x 41.70mm)	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.811" Dia x 1.642" L (20.60mm x 41.70mm)	Class	T
Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.811" Dia x 1.642" L (20.60mm x 41.70mm)	Approvals	CE, CSA, UL
Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.811" Dia x 1.642" L (20.60mm x 41.70mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.811" Dia x 1.642" L (20.60mm x 41.70mm)	Breaking Capacity @ Rated Voltage	200kA
Size / Dimension 0.811" Dia x 1.642" L (20.60mm x 41.70mm)	Mounting Type	Bolt Mount
	Package / Case	Cylindrical, Blade Terminal (Bolt)
Report errors?	Size / Dimension	0.811" Dia x 1.642" L (20.60mm x 41.70mm)
		Report errors?

JLLS080.V Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

JLLS080.V Payment Methods





















JLLS080.V Shipping Methods













If you have any question about JLLS080.V, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com