

## JLLS500.X Information

Heisener.com

Part Number JLLS500.X

Manufacturer Littelfuse Inc.

Category Circuit Protection

Electrical, Specialty Fuses

**Description** FUSE CRTRDGE 500A 600VAC/300VDC

Package Cylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **JLLS500.X Specifications**

Manufacturer Part Number  Manufacturer  Littelfuse Inc.  Category  Circuit Protection  Electrical, Specialty Fuses  Package  Cylindrical, Blade Terminal (Bolt)  Series  POWR-GARD? JLLS  Fuse Type  Cartridge  Current Rating  500A  Voltage Rating - AC  600V  Voltage Rating - DC  Response Time  Fast  Applications  Electrical, Industrial  Features  - Class  T  Approvals  CE, CSA, UL  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Bolt Mount  Package / Case  Cylindrical, Blade Terminal (Bolt)  Size / Dimension  Littelfuse Inc.  Littelfuse I		
Category  Circuit Protection  Electrical, Specialty Fuses  Package  Cylindrical, Blade Terminal (Bolt)  Series  POWR-GARD? JLLS  Fuse Type  Cartridge  Current Rating  500A  Voltage Rating - AC  600V  Voltage Rating - DC  300V  Response Time  Fast  Applications  Electrical, Industrial  Features  - Class  T  Approvals  CE, CSA, UL  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Bolt Mount  Package / Case  Cylindrical, Blade Terminal (Bolt)  Size / Dimension  Circuit Protection  Electrical, Specialty Fuses  Electrical, Industrial  CE, CSA, UL  Operating Temperature  - Breaking Capacity @ Rated Voltage  COUKA  Size / Dimension  Circuit Protection  Electrical, Slade Terminal (Bolt)  Size / Dimension  Circuit Protection  Electrical, Blade Terminal (Bolt)  CIRCUIT CARROW AU  CIRCUI	Manufacturer Part Number	JLLS500.X
Beakage Cylindrical, Blade Terminal (Bolt) Series POWR-GARD? JLLS Fuse Type Cartridge Current Rating 500A Voltage Rating - AC 600V Voltage Rating - DC 300V Response Time Fast Applications Electrical, Industrial Features - Class T Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Electrical, Indust val. 44.80mm)	Manufacturer	Littelfuse Inc.
Package Cylindrical, Blade Terminal (Bolt)  Series POWR-GARD? JLLS  Fuse Type Cartridge  Current Rating 500A  Voltage Rating - AC 600V  Voltage Rating - DC 300V  Response Time Fast  Applications Electrical, Industrial  Features -  Class T  Approvals CE, CSA, UL  Operating Temperature -  Breaking Capacity @ Rated Voltage 200kA  Mounting Type Bolt Mount  Package / Case Cylindrical, Blade Terminal (Bolt)  Size / Dimension 2.063" Dia x 1.764" L (52.40mm x 44.80mm)	Category	Circuit Protection
SeriesPOWR-GARD? JLLSFuse TypeCartridgeCurrent Rating500AVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeFastApplicationsElectrical, IndustrialFeatures-ClassTApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension2.063" Dia x 1.764" L (52.40mm x 44.80mm)		Electrical, Specialty Fuses
Fuse Type Current Rating 500A Voltage Rating - AC 600V Voltage Rating - DC 300V Response Time Fast Applications Electrical, Industrial Features - Class T Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension  Canon Cartridge Converting Capacity Ca	Package	Cylindrical, Blade Terminal (Bolt)
Current Rating  Voltage Rating - AC  600V  Voltage Rating - DC  300V  Response Time  Fast  Applications  Electrical, Industrial  Features  - Class  T  Approvals  CE, CSA, UL  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Bolt Mount  Package / Case  Size / Dimension  500A  600V	Series	POWR-GARD? JLLS
Voltage Rating - AC  Voltage Rating - DC  300V  Response Time  Fast  Applications  Electrical, Industrial  Features  - Class  T  Approvals  CE, CSA, UL  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Bolt Mount  Package / Case  Cylindrical, Blade Terminal (Bolt)  Size / Dimension  600V  600V	Fuse Type	Cartridge
Voltage Rating - DC  Response Time Fast  Applications Electrical, Industrial  Features - Class T  Approvals CE, CSA, UL  Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension  300V  Fast  Fast  Ce, CSA  CE, CSA, UL  CE, CSA, UL  CE, CSA, UL  CE, CSA, UL  COJERT Temperature CE, CSA, UL  CE, CSA,	Current Rating	500A
Response Time Applications Electrical, Industrial Features - Class T Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension  Fast Fast Fast Fast Foature - Clex CSA, UL CE, CSA,	Voltage Rating - AC	600V
Applications Electrical, Industrial  Features - Class T  Approvals CE, CSA, UL  Operating Temperature - Breaking Capacity @ Rated Voltage 200kA  Mounting Type Bolt Mount  Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.063" Dia x 1.764" L (52.40mm x 44.80mm)	Voltage Rating - DC	300V
Features - Class T T CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Bolt Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.063" Dia x 1.764" L (52.40mm x 44.80mm)	Response Time	Fast
Class T Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.063" Dia x 1.764" L (52.40mm x 44.80mm)	Applications	Electrical, Industrial
Approvals  CE, CSA, UL  Operating Temperature  - Breaking Capacity @ Rated Voltage  Bolt Mount  Package / Case  Cylindrical, Blade Terminal (Bolt)  Size / Dimension  CE, CSA, UL  CUL  CUL  CON  CON  CON  CON  CON  CON  CON  CO	Features	-
Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Bolt Mount  Package / Case  Cylindrical, Blade Terminal (Bolt)  Size / Dimension  2.063" Dia x 1.764" L (52.40mm x 44.80mm)	Class	Т
Breaking Capacity @ Rated Voltage 200kA  Mounting Type Bolt Mount  Package / Case Cylindrical, Blade Terminal (Bolt)  Size / Dimension 2.063" Dia x 1.764" L (52.40mm x 44.80mm)	Approvals	CE, CSA, UL
Mounting Type  Bolt Mount  Package / Case  Cylindrical, Blade Terminal (Bolt)  Size / Dimension  2.063" Dia x 1.764" L (52.40mm x 44.80mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.063" Dia x 1.764" L (52.40mm x 44.80mm)	Breaking Capacity @ Rated Voltage	200kA
Size / Dimension 2.063" Dia x 1.764" L (52.40mm x 44.80mm)	Mounting Type	Bolt Mount
	Package / Case	Cylindrical, Blade Terminal (Bolt)
Report errors?	Size / Dimension	2.063" Dia x 1.764" L (52.40mm x 44.80mm)
		Report errors?

### **JLLS500.X Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# **JLLS500.X Payment Methods**


































If you have any question about JLLS500.X, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com