

JM1AN-TMP-DC12V

JM1AN-TMP-DC12V Information



For Reference Only

Part Number JM1AN-TMP-DC12V

Manufacturer Panasonic Electric Works

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE SPST 20A 12V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









JM1AN-TMP-DC12V Specifications

| Manufacturer Part Number JMIAN-TMP-DC12V Manufacturer Panasonic Electric Works Category Relays Power Relays, Over 2 Amps Package - Series JM Relay Type General Purpose Coil Type Non Latching Coil Current 75mA Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 20A Switching Voltage 250VAC - Max Turn On Voltage (Max) 8.4 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 20ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.250" (6.3mm) | | |
|--|--------------------------|--|
| CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesJMRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current75mACoil Voltage12VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)20ASwitching Voltage250VAC - MaxTurn On Voltage (Max)8.4 VDCTurn Off Voltage (Min)1.2 VDCOperate Time20msRelease Time10msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin, Quick Connect - 0.250" (6.3mm) | Manufacturer Part Number | JM1AN-TMP-DC12V |
| Package - Series JM Relay Type General Purpose Coil Type Non Latching Coil Current 75mA Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 20A Switching Voltage 250VAC - Max Turn On Voltage (Max) 8.4 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 20ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.250" (6.3mm) | Manufacturer | Panasonic Electric Works |
| Package-SeriesJMRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current75mACoil Voltage12VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)20ASwitching Voltage250VAC - MaxTurn On Voltage (Max)8.4 VDCTurn Off Voltage (Min)1.2 VDCOperate Time20msRelease Time10msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin, Quick Connect - 0.250" (6.3mm) | Category | Relays |
| Series JM Relay Type General Purpose Coil Type Non Latching Coil Current 75mA Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 20A Switching Voltage 250VAC - Max Turn On Voltage (Max) 8.4 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 20ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.250" (6.3mm) | | Power Relays, Over 2 Amps |
| Relay Type General Purpose Coil Type Non Latching Coil Current 75mA Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 20A Switching Voltage 250VAC - Max Turn On Voltage (Max) 8.4 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 20ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.250" (6.3mm) | Package | - |
| Coil TypeNon LatchingCoil Current75mACoil Voltage12VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)20ASwitching Voltage250VAC - MaxTurn On Voltage (Max)8.4 VDCTurn Off Voltage (Min)1.2 VDCOperate Time20msRelease Time10msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin, Quick Connect - 0.250" (6.3mm) | Series | JM |
| Coil Current Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 20A Switching Voltage 250VAC - Max Turn On Voltage (Max) 8.4 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 20ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.250" (6.3mm) | Relay Type | General Purpose |
| Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 20A Switching Voltage 250VAC - Max Turn On Voltage (Max) 8.4 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 20ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.250" (6.3mm) | Coil Type | Non Latching |
| Contact Form SPST-NO (1 Form A) Contact Rating (Current) 20A Switching Voltage 250VAC - Max Turn On Voltage (Max) 8.4 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 20ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.250" (6.3mm) | Coil Current | 75mA |
| Contact Rating (Current) Switching Voltage 250VAC - Max Turn On Voltage (Max) 8.4 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 20ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.250" (6.3mm) | Coil Voltage | 12VDC |
| Switching Voltage Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 20ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style 250VAC - Max 8.4 VDC 1.2 VDC 20ms Sealed - Flux Protection Through Hole PC Pin, Quick Connect - 0.250" (6.3mm) | Contact Form | SPST-NO (1 Form A) |
| Turn On Voltage (Max) Turn Off Voltage (Min) 1.2 VDC Operate Time 20ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style 8.4 VDC 1.2 VDC Oms POPIN, Quick Connect - 0.250" (6.3mm) | Contact Rating (Current) | 20A |
| Turn Off Voltage (Min) 1.2 VDC Operate Time 20ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.250" (6.3mm) | Switching Voltage | 250VAC - Max |
| Operate Time 20ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.250" (6.3mm) | Turn On Voltage (Max) | 8.4 VDC |
| Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.250" (6.3mm) | Turn Off Voltage (Min) | 1.2 VDC |
| Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.250" (6.3mm) | Operate Time | 20ms |
| Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.250" (6.3mm) | Release Time | 10ms |
| Termination Style PC Pin, Quick Connect - 0.250" (6.3mm) | Features | Sealed - Flux Protection |
| · | Mounting Type | Through Hole |
| Report errors? | Termination Style | PC Pin, Quick Connect - 0.250" (6.3mm) |
| | | Report errors? |

JM1AN-TMP-DC12V Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

JM1AN-TMP-DC12V Payment Methods



















JM1AN-TMP-DC12V Shipping Methods













If you have any question about JM1AN-TMP-DC12V, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com