

JM1AN-TMP-DC5V-F

JM1AN-TMP-DC5V-F Information



For Reference Only

Part Number JM1AN-TMP-DC5V-F Manufacturer Panasonic Electric Works

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE SPST 20A 5V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









JM1AN-TMP-DC5V-F Specifications

Manufacturer Part Number JMIAN-TMP-DC5V-F Manufacturer Panasonic Electric Works Category Relays Power Relays, Over 2 Amps Package - Series JM Relay Type General Purpose Coil Type Non Latching Coil Current 180mA Coil Voltage 5VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 20A Switching Voltage 250VAC - Max Turn On Voltage (Max) 3.5 VDC Turn Off Voltage (Min) 0.5 VDC Operate Time 20ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.250" (6.3mm)		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesJMRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current180mACoil Voltage5VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)20ASwitching Voltage250VAC - MaxTurn On Voltage (Max)3.5 VDCTurn Off Voltage (Min)0.5 VDCOperate Time20msRelease Time10msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin, Quick Connect - 0.250" (6.3mm)	Manufacturer Part Number	JM1AN-TMP-DC5V-F
Package - Series JM Relay Type General Purpose Coil Type Non Latching Coil Current 180mA Coil Voltage 5VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 20A Switching Voltage 250VAC - Max Turn On Voltage (Max) 3.5 VDC Turn Off Voltage (Min) 0.5 VDC Operate Time 20ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.250" (6.3mm)	Manufacturer	Panasonic Electric Works
Package-SeriesJMRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current180mACoil Voltage5VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)20ASwitching Voltage250VAC - MaxTurn On Voltage (Max)3.5 VDCTurn Off Voltage (Min)0.5 VDCOperate Time20msRelease Time10msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin, Quick Connect - 0.250" (6.3mm)	Category	Relays
Series JM Relay Type General Purpose Coil Type Non Latching Coil Current 180mA Coil Voltage 5VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 20A Switching Voltage 250VAC - Max Turn On Voltage (Max) 3.5 VDC Turn Off Voltage (Min) 0.5 VDC Operate Time 20ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.250" (6.3mm)		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 180mA Coil Voltage 5VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 20A Switching Voltage 250VAC - Max Turn On Voltage (Max) 3.5 VDC Turn Off Voltage (Min) 0.5 VDC Operate Time 20ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.250" (6.3mm)	Package	-
Coil TypeNon LatchingCoil Current180mACoil Voltage5VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)20ASwitching Voltage250VAC - MaxTurn On Voltage (Max)3.5 VDCTurn Off Voltage (Min)0.5 VDCOperate Time20msRelease Time10msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin, Quick Connect - 0.250" (6.3mm)	Series	JM
Coil Current Coil Voltage 5VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 20A Switching Voltage 250VAC - Max Turn On Voltage (Max) 3.5 VDC Turn Off Voltage (Min) 0.5 VDC Operate Time 20ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.250" (6.3mm)	Relay Type	General Purpose
Coil Voltage 5VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 20A Switching Voltage 250VAC - Max Turn On Voltage (Max) 3.5 VDC Turn Off Voltage (Min) 0.5 VDC Operate Time 20ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.250" (6.3mm)	Coil Type	Non Latching
Contact Form SPST-NO (1 Form A) Contact Rating (Current) 20A Switching Voltage 250VAC - Max Turn On Voltage (Max) 3.5 VDC Turn Off Voltage (Min) 0.5 VDC Operate Time 20ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.250" (6.3mm)	Coil Current	180mA
Contact Rating (Current) Switching Voltage 250VAC - Max Turn On Voltage (Max) 3.5 VDC Turn Off Voltage (Min) 0.5 VDC Operate Time 20ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.250" (6.3mm)	Coil Voltage	5VDC
Switching Voltage Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 20ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style 250VAC - Max 3.5 VDC 0.5 VDC 10ms 20ms 10ms Peatures Peatures Sealed - Flux Protection Through Hole PC Pin, Quick Connect - 0.250" (6.3mm)	Contact Form	SPST-NO (1 Form A)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 20ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style 3.5 VDC 0.5 VDC 20ms 20ms Formination Style PC Pin, Quick Connect - 0.250" (6.3mm)	Contact Rating (Current)	20A
Turn Off Voltage (Min) Operate Time 20ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.250" (6.3mm)	Switching Voltage	250VAC - Max
Operate Time 20ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.250" (6.3mm)	Turn On Voltage (Max)	3.5 VDC
Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.250" (6.3mm)	Turn Off Voltage (Min)	0.5 VDC
Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.250" (6.3mm)	Operate Time	20ms
Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.250" (6.3mm)	Release Time	10ms
Termination Style PC Pin, Quick Connect - 0.250" (6.3mm)	Features	Sealed - Flux Protection
	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin, Quick Connect - 0.250" (6.3mm)
		Report errors?

JM1AN-TMP-DC5V-F Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

JM1AN-TMP-DC5V-F Payment Methods



















JM1AN-TMP-DC5V-F Shipping Methods













If you have any question about JM1AN-TMP-DC5V-F, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com