

JMAC-26XL Information

w.helsener.com

For Reference Only

Part Number JMAC-26XL

Manufacturer TE Connectivity Aerospace, Defense and Marine

Category Relays

Signal Relays, Up to 2 Amps

Description RELAY GEN PURPOSE DPDT 1A 26.5V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









JMAC-26XL Specifications

Manufacturer Part Number JMAC-26XL Manufacturer TE Connectivity Aerospace, Defense and Marine Category Relays Package - Series Military, MIL-R-39016/9, MA, CII Relay Type General Purpose Coil Type Non Latching Coil Current - Coil Voltage 26.5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 28VDC - Nom Turn On Voltage (Max) 14.2 VDC Turn Off Voltage (Min) 1.37 VDC Operate Time 2ms Release Time 1.5ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin		
CategoryRelaysPackage-SeriesMilitary, MIL-R-39016/9, MA, CIIRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current-Coil Voltage26.5 VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage28 VDC - NomTurn On Voltage (Max)14.2 VDCTurn Off Voltage (Min)1.37 VDCOperate Time2msRelease Time1.5msFeaturesSealed - HermeticallyMounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	JMAC-26XL
Package-SeriesMilitary, MIL-R-39016/9, MA, CIIRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current-Coil Voltage26.5VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage28VDC - NomTurn On Voltage (Max)14.2 VDCTurn Off Voltage (Min)1.37 VDCOperate Time2msRelease Time1.5msFeaturesSealed - HermeticallyMounting TypeThrough HoleTermination StylePC Pin	Manufacturer	TE Connectivity Aerospace, Defense and Marine
Package - Military, MIL-R-39016/9, MA, CII Relay Type General Purpose Coil Type Non Latching Coil Current - Coil Voltage 26.5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 28VDC - Nom Turn On Voltage (Max) 14.2 VDC Turn Off Voltage (Min) 1.37 VDC Operate Time 2ms Release Time 1.5ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin	Category	Relays
SeriesMilitary, MIL-R-39016/9, MA, CIIRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current-Coil Voltage26.5 VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage28 VDC - NomTurn On Voltage (Max)14.2 VDCTurn Off Voltage (Min)1.37 VDCOperate Time2msRelease Time1.5msFeaturesSealed - HermeticallyMounting TypeThrough HoleTermination StylePC Pin		Signal Relays, Up to 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current-Coil Voltage26.5VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage28VDC - NomTurn On Voltage (Max)14.2 VDCTurn Off Voltage (Min)1.37 VDCOperate Time2msRelease Time1.5msFeaturesSealed - HermeticallyMounting TypeThrough HoleTermination StylePC Pin	Package	-
Coil Type Non Latching Coil Current - Coil Voltage 26.5 VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 28VDC - Nom Turn On Voltage (Max) 14.2 VDC Turn Off Voltage (Min) 1.37 VDC Operate Time 2ms Release Time 1.5ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin	Series	Military, MIL-R-39016/9, MA, CII
Coil Current Coil Voltage 26.5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 28VDC - Nom Turn On Voltage (Max) 14.2 VDC Turn Off Voltage (Min) 1.37 VDC Operate Time 2ms Release Time 1.5ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin	Relay Type	General Purpose
Coil Voltage 26.5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 28VDC - Nom Turn On Voltage (Max) 14.2 VDC Turn Off Voltage (Min) 1.37 VDC Operate Time 2ms Release Time 1.5ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin	Coil Type	Non Latching
Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 28VDC - Nom Turn On Voltage (Max) 14.2 VDC Turn Off Voltage (Min) 1.37 VDC Operate Time 2ms Release Time 1.5ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style	Coil Current	-
Contact Rating (Current) Switching Voltage 28VDC - Nom Turn On Voltage (Max) 14.2 VDC Turn Off Voltage (Min) 1.37 VDC Operate Time 2ms Release Time 1.5ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin	Coil Voltage	26.5VDC
Switching Voltage 28VDC - Nom Turn On Voltage (Max) 14.2 VDC Turn Off Voltage (Min) 1.37 VDC Operate Time 2ms Release Time 1.5ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max) 14.2 VDC Turn Off Voltage (Min) 1.37 VDC Operate Time 2ms Release Time 1.5ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin	Contact Rating (Current)	1A
Turn Off Voltage (Min) Operate Time 2ms Release Time 1.5ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin	Switching Voltage	28VDC - Nom
Operate Time2msRelease Time1.5msFeaturesSealed - HermeticallyMounting TypeThrough HoleTermination StylePC Pin	Turn On Voltage (Max)	14.2 VDC
Release Time 1.5ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	1.37 VDC
Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin	Operate Time	2ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	1.5ms
Termination Style PC Pin	Features	Sealed - Hermetically
·	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
		Report errors?

JMAC-26XL Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

JMAC-26XL Payment Methods





















JMAC-26XL Shipping Methods













If you have any question about JMAC-26XL, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com