



## **JMACT-26XM Information**



For Reference Only

Part Number JMACT-26XM

Manufacturer TE Connectivity Aerospace, Defense and Marine

Category Relays

Signal Relays, Up to 2 Amps

**Description** RELAY GEN PURPOSE DPDT 1A 26.5V

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **JMACT-26XM Specifications**

Manufacturer Part NumberJMACT-26XMManufacturerTE Connectivity Aerospace, Defense and MarineCategoryRelaysPackage-SeriesMilitary, MIL-R-28776/1, MA, CIIRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current17mACoil Voltage26.5VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage28VDC - NomTurn On Voltage (Max)14.2 VDCTurn Off Voltage (Min)1.37 VDCOperate Time2msRelease Time7.5msFeaturesSealed - HermeticallyMounting TypeThrough HoleTarmination Stude10.0 Rich		
Category Relays Signal Relays, Up to 2 Amps Package - Series Military, MIL-R-28776/1, MA, CII Relay Type General Purpose Coil Type Non Latching Coil Current 17mA Coil Voltage 26.5 VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 28VDC - Nom Turn On Voltage (Max) 14.2 VDC Turn Off Voltage (Min) 1.37 VDC Operate Time 2ms Release Time 7.5ms Features Sealed - Hermetically Mounting Type Through Hole	Manufacturer Part Number	JMACT-26XM
Package - Series Military, MIL-R-28776/1, MA, CII Relay Type General Purpose Coil Type Non Latching Coil Current 17mA Coil Voltage 26.5 VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 28VDC - Nom Turn On Voltage (Max) 14.2 VDC Turn Off Voltage (Min) 1.37 VDC Operate Time 2ms Release Time 7.5ms Features Sealed - Hermetically Mounting Type Through Hole	Manufacturer	TE Connectivity Aerospace, Defense and Marine
Package - Series Military, MIL-R-28776/1, MA, CII Relay Type General Purpose Coil Type Non Latching Coil Current 17mA Coil Voltage 26.5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 28VDC - Nom Turn On Voltage (Max) 14.2 VDC Turn Off Voltage (Min) 1.37 VDC Operate Time 2ms Release Time 7.5ms Features Sealed - Hermetically Mounting Type Trhrough Hole	Category	Relays
Series Military, MIL-R-28776/1, MA, CII Relay Type General Purpose Coil Type Non Latching Coil Current 17mA Coil Voltage 26.5 VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 28VDC - Nom Turn On Voltage (Max) 14.2 VDC Turn Off Voltage (Min) 1.37 VDC Operate Time 2ms Release Time 7.5ms Features Sealed - Hermetically Mounting Type Through Hole		Signal Relays, Up to 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current17mACoil Voltage26.5 VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage28 VDC - NomTurn On Voltage (Max)14.2 VDCTurn Off Voltage (Min)1.37 VDCOperate Time2msRelease Time7.5msFeaturesSealed - HermeticallyMounting TypeThrough Hole	Package	-
Coil Type Non Latching Coil Current 17mA Coil Voltage 26.5 VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 28VDC - Nom Turn On Voltage (Max) 14.2 VDC Turn Off Voltage (Min) 1.37 VDC Operate Time 2ms Release Time 7.5ms Features Sealed - Hermetically Mounting Type Through Hole	Series	Military, MIL-R-28776/1, MA, CII
Coil Current 17mA Coil Voltage 26.5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 28VDC - Nom Turn On Voltage (Max) 14.2 VDC Turn Off Voltage (Min) 1.37 VDC Operate Time 2ms Release Time 7.5ms Features Sealed - Hermetically Mounting Type Through Hole	Relay Type	General Purpose
Coil Voltage 26.5VDC  Contact Form DPDT (2 Form C)  Contact Rating (Current) 1A  Switching Voltage 28VDC - Nom  Turn On Voltage (Max) 14.2 VDC  Turn Off Voltage (Min) 1.37 VDC  Operate Time 2ms  Release Time 7.5ms  Features Sealed - Hermetically  Mounting Type Through Hole	Coil Type	Non Latching
Contact Form DPDT (2 Form C)  Contact Rating (Current)  Switching Voltage  28VDC - Nom  Turn On Voltage (Max)  14.2 VDC  Turn Off Voltage (Min)  1.37 VDC  Operate Time  2ms  Release Time  7.5ms  Features  Sealed - Hermetically  Mounting Type  Through Hole	Coil Current	17mA
Contact Rating (Current)  Switching Voltage  28VDC - Nom  Turn On Voltage (Max)  14.2 VDC  Turn Off Voltage (Min)  1.37 VDC  Operate Time  2ms  Release Time  7.5ms  Features  Sealed - Hermetically  Mounting Type  Through Hole	Coil Voltage	26.5VDC
Switching Voltage 28VDC - Nom  Turn On Voltage (Max) 14.2 VDC  Turn Off Voltage (Min) 1.37 VDC  Operate Time 2ms  Release Time 7.5ms  Features Sealed - Hermetically  Mounting Type Through Hole	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max)  14.2 VDC  Turn Off Voltage (Min)  1.37 VDC  Operate Time  2ms  Release Time  7.5ms  Features  Sealed - Hermetically  Mounting Type  Through Hole	Contact Rating (Current)	1A
Turn Off Voltage (Min)  Operate Time  2ms  Release Time  7.5ms  Features  Sealed - Hermetically  Mounting Type  Through Hole	Switching Voltage	28VDC - Nom
Operate Time 2ms Release Time 7.5ms Features Sealed - Hermetically Mounting Type Through Hole	Turn On Voltage (Max)	14.2 VDC
Release Time 7.5ms Features Sealed - Hermetically Mounting Type Through Hole	Turn Off Voltage (Min)	1.37 VDC
Features Sealed - Hermetically Mounting Type Through Hole	Operate Time	2ms
Mounting Type Through Hole	Release Time	7.5ms
	Features	Sealed - Hermetically
Townington Style	Mounting Type	Through Hole
remination style PC PIII	Termination Style	PC Pin
Report errors?		Report errors?

### **JMACT-26XM Guarantees**



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **JMACT-26XM Payment Methods**





















### **JMACT-26XM Shipping Methods**













If you have any question about JMACT-26XM, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com