



JMSWD-5XM Information



For Reference Only

Part Number JMSWD-5XM

Manufacturer TE Connectivity Aerospace, Defense and Marine

Category Relays

Signal Relays, Up to 2 Amps

Description RELAY GENERAL PURPOSE DPDT 1A 5V

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









JMSWD-5XM Specifications

Manufacturer Part Number JMSWD-5XM Manufacturer TE Connectivity Aerospace, Defense and Marine Category Relays Package - Series Military, MIL-R-39016/16, MS, CII Relay Type General Purpose Coil Type Non Latching Coil Current 50mA Coil Voltage 5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 28VDC - Nom Turn On Voltage (Max) 2.6 VDC Turn Off Voltage (Min) 0.23 VDC Operate Time 4ms Release Time 7.5ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin		
Category Relays Signal Relays, Up to 2 Amps Package - Series Military, MIL-R-39016/16, MS, CII Relay Type General Purpose Coil Type Non Latching Coil Current 50mA Coil Voltage 5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 28VDC - Nom Turn On Voltage (Max) 2.6 VDC Operate Time 4ms Release Time 7.5ms Features Sealed - Hermetically Mounting Type Tron On Voltage (Max) Through Hole	Manufacturer Part Number	JMSWD-5XM
Package - Series Military, MIL-R-39016/16, MS, CII Relay Type General Purpose Coil Type Non Latching Coil Current 50mA Coil Voltage 5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 28VDC - Nom Turn On Voltage (Max) 2.6 VDC Turn Off Voltage (Min) 0.23 VDC Operate Time 4ms Release Time 7.5ms Features Sealed - Hermetically Mounting Type Through Hole	Manufacturer	TE Connectivity Aerospace, Defense and Marine
Package - Series Military, MIL-R-39016/16, MS, CII Relay Type General Purpose Coil Type Non Latching Coil Current 50mA Coil Voltage 5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 28VDC - Nom Turn On Voltage (Max) 2.6 VDC Turn Off Voltage (Min) 0.23 VDC Operate Time 4ms Release Time 7.5ms Features Sealed - Hermetically Mounting Type Trhrough Hole	Category	Relays
Series Military, MIL-R-39016/16, MS, CII Relay Type General Purpose Coil Type Non Latching Coil Current 50mA Coil Voltage 5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 28VDC - Nom Turn On Voltage (Max) 2.6 VDC Turn Off Voltage (Min) 0.23 VDC Operate Time 4ms Release Time 7.5ms Features Sealed - Hermetically Mounting Type Through Hole		Signal Relays, Up to 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current50mACoil Voltage5VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage28VDC - NomTurn On Voltage (Max)2.6 VDCTurn Off Voltage (Min)0.23 VDCOperate Time4msRelease Time7.5msFeaturesSealed - HermeticallyMounting TypeThrough Hole	Package	-
Coil Type Non Latching Coil Current 50mA Coil Voltage 5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 28VDC - Nom Turn On Voltage (Max) 2.6 VDC Turn Off Voltage (Min) 0.23 VDC Operate Time 4ms Release Time 7.5ms Features Sealed - Hermetically Mounting Type Through Hole	Series	Military, MIL-R-39016/16, MS, CII
Coil Current 50mA Coil Voltage 5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 28VDC - Nom Turn On Voltage (Max) 2.6 VDC Turn Off Voltage (Min) 0.23 VDC Operate Time 4ms Release Time 7.5ms Features Sealed - Hermetically Mounting Type Through Hole	Relay Type	General Purpose
Coil Voltage 5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 28VDC - Nom Turn On Voltage (Max) 2.6 VDC Turn Off Voltage (Min) 0.23 VDC Operate Time 4ms Release Time 7.5ms Features Sealed - Hermetically Mounting Type Through Hole	Coil Type	Non Latching
Contact Form DPDT (2 Form C) Contact Rating (Current) Switching Voltage 28VDC - Nom Turn On Voltage (Max) 2.6 VDC Turn Off Voltage (Min) 0.23 VDC Operate Time 4ms Release Time 7.5ms Features Sealed - Hermetically Mounting Type Through Hole	Coil Current	50mA
Contact Rating (Current) Switching Voltage 28VDC - Nom Turn On Voltage (Max) 2.6 VDC Turn Off Voltage (Min) 0.23 VDC Operate Time 4ms Release Time 7.5ms Features Sealed - Hermetically Mounting Type Through Hole	Coil Voltage	5VDC
Switching Voltage 28VDC - Nom Turn On Voltage (Max) 2.6 VDC Turn Off Voltage (Min) 0.23 VDC Operate Time 4ms Release Time 7.5ms Features Sealed - Hermetically Mounting Type Through Hole	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max) 2.6 VDC Turn Off Voltage (Min) 0.23 VDC Operate Time 4ms Release Time 7.5ms Features Sealed - Hermetically Mounting Type Through Hole	Contact Rating (Current)	1A
Turn Off Voltage (Min) Operate Time 4ms Release Time 7.5ms Features Sealed - Hermetically Mounting Type Through Hole	Switching Voltage	28VDC - Nom
Operate Time 4ms Release Time 7.5ms Features Sealed - Hermetically Mounting Type Through Hole	Turn On Voltage (Max)	2.6 VDC
Release Time 7.5ms Features Sealed - Hermetically Mounting Type Through Hole	Turn Off Voltage (Min)	0.23 VDC
Features Sealed - Hermetically Mounting Type Through Hole	Operate Time	4ms
Mounting Type Through Hole	Release Time	7.5ms
	Features	Sealed - Hermetically
Termination Style PC Pin	Mounting Type	Through Hole
Torini de la companya	Termination Style	PC Pin
Report errors?		Report errors?

JMSWD-5XM Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

JMSWD-5XM Payment Methods





















JMSWD-5XM Shipping Methods













If you have any question about JMSWD-5XM, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com