

# JMXHH1G12FSUDSG

### JMXHH1G12FSUDSG Information



| Part Number  | JMXHH1G12FSUDSG                                     |  |
|--------------|---|--|
| Manufacturer | Souriau   |  |
| Category     | Connectors, Interconnects<br>Circular Connectors    |  |
| Description  | CONN RCPT FMALE 12POS GOLD SOLDR                    |  |
| Package      | -   |  |
|              | For the pricing/inventory/lead time, please contact |  |
|              | us  |  |
|              | Website: https://www.heisener.com                   |  |
|              | E-mail: salesdept@heisener.com                      |  |



Request a Quote

For Reference Only

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## JMXHH1G12FSUDSG Specifications

| ManufacturerSouriauCategoryConnectors, InterconnectsCircular ConnectorsPackage-SeriesJMXConnector TypeReceptacle, Female SocketsNumber of Positions12Shell Size - Insert1-12Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Rear Side NutTerminationGolder CupFastening TypePush-PullOrientationGIngress ProtectionHoles Dust Tight, WaterproofShell Material, FinishFolgetherimide (PEI)Contact Finish-Yoltage - Rated-Voltage - Rated-Current Rating2,5A  |                          |                                       |
|--|--------------------------|---------------------------------------|
| CategoryConnectors, InterconnectsPackage-Package-SeriesJMXConnector TypeReceptacle, Female SocketsNumber of Positions12Shell Size - Insert1-12Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Rear Side NutTerminationSolder CupFastening TypePush-PullOrientationGIngress ProtectionPolyetherimide (PEI)Contact Finish-Features-Voltage - Rated-Voltage - Rated-Current Rating5.5A   | Manufacturer Part Number | JMXHH1G12FSUDSG                       |
| Circular ConnectorsPackage-SeriesJMXConnector TypeReceptacle, Female SocketsNumber of Positions12Shell Size - Insert1-12Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Rear Side NutTerminationSolder CupFastening TypePush-PullOrientationGIngress ProtectionIP68 - Dust Tight, WaterproofShell Material, FinishPolyetherimide (PEI)Contact Finish-Yoltage - Rated-Voltage - Rated-Current Rating2.5A   | Manufacturer             | Souriau                               |
| Package-SeriesJMXConnector TypeReceptacle, Female SocketsNumber of Positions12Shell Size - Insert1-12Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Rear Side NutTerminationSolder CupFastening TypePush-PullOrientationIP68 - Dust Tight, WaterproofIngress ProtectionIP68 - Dust Tight, WaterproofShell Material, FinishOlyetherimide (PEI)Contact FinishGoldYoltage - Rated-Kurent Rating-Statenting- </td <td>Category</td> <td>Connectors, Interconnects</td> | Category                 | Connectors, Interconnects             |
| SeriesJMXConnector TypeReceptacle, Female SocketsNumber of Positions12Shell Size - Insert1-12Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Rear Side NutTerminationSolder CupFastening TypePush-PullOrientationGIngress ProtectionPf68 - Dust Tight, WaterproofShell Material, FinishOldertermide (PEI)Contact FinishGoldFastening2.5A  |                          | Circular Connectors                   |
| Connector TypeReceptacle, Female SocketsNumber of Positions12Shell Size - Insert1-12Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Rear Side NutTerminationSolder CupFastening TypePush-PullOrientationGIngress ProtectionIP68 - Dust Tight, WaterproofShell Material, FinishGoldContact FinishGoldFastures-Voltage - Rated-Current Rating2.5A   | Package                  | -                                     |
| Number of Positions12Shell Size - Insert1-12Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Rear Side NutTerminationSolder CupFastening TypePush-PullOrientationGIngress ProtectionIP68 - Dust Tight, WaterproofShell Material, FinishPolyetherimide (PEI)Contact FinishGoldFeatures-Voltage - Rated-Current Rating2.5A   | Series                   | JMX                                   |
| Shell Size - Insert1-12Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Rear Side NutTerminationSolder CupFastening TypePush-PullOrientationGIngress ProtectionIP68 - Dust Tight, WaterproofShell Material, FinishPolyetherimide (PEI)Contact FinishGoldFeatures-Voltage - Rated-Current Rating2.5A  | Connector Type           | Receptacle, Female Sockets            |
| Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Rear Side NutTerminationSolder CupFastening TypePush-PullOrientationGIngress ProtectionIP68 - Dust Tight, WaterproofShell Material, FinishPolyetherimide (PEI)Contact FinishGoldFeatures-Voltage - Rated-Current Rating2.5A   | Number of Positions      | 12                                    |
| Mounting TypePanel Mount, Bulkhead - Rear Side NutTerminationSolder CupFastening TypePush-PullOrientationGIngress ProtectionIP68 - Dust Tight, WaterproofShell Material, FinishPolyetherimide (PEI)Contact FinishGoldFeatures-Voltage - Rated-Current Rating2.5A   | Shell Size - Insert      | 1-12                                  |
| TerminationSolder CupFastening TypePush-PullOrientationGIngress ProtectionIP68 - Dust Tight, WaterproofShell Material, FinishPolyetherimide (PEI)Contact FinishGoldFeatures-Voltage - Rated-Current Rating2.5A   | Shell Size, MIL          | -                                     |
| Fastening TypePush-PullOrientationGIngress ProtectionIP68 - Dust Tight, WaterproofShell Material, FinishPolyetherimide (PEI)Contact FinishGoldFeatures-Voltage - Rated-Current Rating2.5A  | Mounting Type            | Panel Mount, Bulkhead - Rear Side Nut |
| OrientationGIngress ProtectionIP68 - Dust Tight, WaterproofShell Material, FinishPolyetherimide (PEI)Contact FinishGoldFeatures-Voltage - Rated-Current Rating2.5A   | Termination              | Solder Cup                            |
| Ingress ProtectionIP68 - Dust Tight, WaterproofShell Material, FinishPolyetherimide (PEI)Contact FinishGoldFeatures-Voltage - Rated-Current Rating2.5A   | Fastening Type           | Push-Pull                             |
| Shell Material, FinishPolyetherimide (PEI)Contact FinishGoldFeatures-Voltage - Rated-Current Rating2.5A  | Orientation              | G                                     |
| Contact FinishGoldFeatures-Voltage - Rated-Current Rating2.5A  | Ingress Protection       | IP68 - Dust Tight, Waterproof         |
| Features-Voltage - Rated-Current Rating2.5A  | Shell Material, Finish   | Polyetherimide (PEI)                  |
| Voltage - Rated-Current Rating2.5A   | Contact Finish           | Gold                                  |
| Current Rating 2.5A  | Features                 | -                                     |
| -  | Voltage - Rated          | -                                     |
| Report errors?   | Current Rating           | 2.5A                                  |
|  |                          | Report errors?                        |

### JMXHH1G12FSUDSG Guarantees



**Quality Guarantees** 

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### JMXHH1G12FSUDSG Payment Methods



If you have any question about JMXHH1G12FSUDSG, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com