

# **JQ1AP-5V-F Information**



For Reference Only

Part Number JQ1AP-5V-F

Manufacturer Panasonic Electric Works

**Category** Relays

Power Relays, Over 2 Amps

**Description** RELAY GEN PURPOSE SPST 10A 5V

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **JQ1AP-5V-F Specifications**

Manufacturer Part Number  Manufacturer  Panasonic Electric Works  Relays  Power Relays, Over 2 Amps  Package  - Series  JQ  Relay Type  General Purpose  Coil Current  40mA  Coil Voltage  5VDC  Contact Form  SPST-NO (1 Form A)  Contact Rating (Current)  10A  Switching Voltage  250VAC, 110VDC - Max  Turn On Voltage (Min)  Operate Time  Peatures  Mounting Type  Through Hole  Termination Style  Panasonic Electric Works  Relays  Power Relays  Power Relays  Over 2 Amps  Over 2 Amps  Power Relays  Over 2 Amps  Over 2 Amps  Power Relays  Over 10 Amps  Over 10 Am		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesJQRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current40mACoil Voltage5VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)10ASwitching Voltage250VAC, 110VDC - MaxTurn On Voltage (Max)4 VDCTurn Off Voltage (Min)0.25 VDCOperate Time20msRelease Time10msFeaturesInsulation - Class EMounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	JQ1AP-5V-F
Package-SeriesJQRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current40mACoil Voltage5VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)10ASwitching Voltage250VAC, 110VDC - MaxTurn On Voltage (Max)4 VDCTurn Off Voltage (Min)0.25 VDCOperate Time20msRelease Time10msFeaturesInsulation - Class EMounting TypeThrough HoleTermination StylePC Pin	Manufacturer	Panasonic Electric Works
Package         -           Series         JQ           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         40mA           Coil Voltage         5VDC           Contact Form         SPST-NO (1 Form A)           Contact Rating (Current)         10A           Switching Voltage         250VAC, 110VDC - Max           Turn On Voltage (Max)         4 VDC           Turn Off Voltage (Min)         0.25 VDC           Operate Time         20ms           Release Time         10ms           Features         Insulation - Class E           Mounting Type         Through Hole           Termination Style         PC Pin	Category	Relays
SeriesJQRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current40mACoil Voltage5VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)10ASwitching Voltage250VAC, 110VDC - MaxTurn On Voltage (Max)4 VDCTurn Off Voltage (Min)0.25 VDCOperate Time20msRelease Time10msFeaturesInsulation - Class EMounting TypeThrough HoleTermination StylePC Pin		Power Relays, Over 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current40mACoil Voltage5VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)10ASwitching Voltage250VAC, 110VDC - MaxTurn On Voltage (Max)4 VDCTurn Off Voltage (Min)0.25 VDCOperate Time20msRelease Time10msFeaturesInsulation - Class EMounting TypeThrough HoleTermination StylePC Pin	Package	-
Coil TypeNon LatchingCoil Current40mACoil Voltage5VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)10ASwitching Voltage250VAC, 110VDC - MaxTurn On Voltage (Max)4 VDCTurn Off Voltage (Min)0.25 VDCOperate Time20msRelease Time10msFeaturesInsulation - Class EMounting TypeThrough HoleTermination StylePC Pin	Series	JQ
Coil Current 40mA Coil Voltage 5VDC  Contact Form SPST-NO (1 Form A) Contact Rating (Current) 10A Switching Voltage 250VAC, 110VDC - Max Turn On Voltage (Max) 4 VDC Turn Off Voltage (Min) 0.25 VDC Operate Time 20ms Release Time 10ms Features Insulation - Class E Mounting Type Through Hole Termination Style PC Pin	Relay Type	General Purpose
Coil Voltage 5VDC  Contact Form SPST-NO (1 Form A)  Contact Rating (Current) 10A  Switching Voltage 250VAC, 110VDC - Max  Turn On Voltage (Max) 4 VDC  Turn Off Voltage (Min) 0.25 VDC  Operate Time 20ms  Release Time 10ms  Features Insulation - Class E  Mounting Type Through Hole  Termination Style PC Pin	Coil Type	Non Latching
Contact Form SPST-NO (1 Form A)  Contact Rating (Current) 10A  Switching Voltage 250VAC, 110VDC - Max  Turn On Voltage (Max) 4 VDC  Turn Off Voltage (Min) 0.25 VDC  Operate Time 20ms  Release Time 10ms  Features Insulation - Class E  Mounting Type Through Hole  Termination Style PC Pin	Coil Current	40mA
Contact Rating (Current)  Switching Voltage  250VAC, 110VDC - Max  Turn On Voltage (Max)  4 VDC  Turn Off Voltage (Min)  0.25 VDC  Operate Time  20ms  Release Time  10ms  Features  Insulation - Class E  Mounting Type  Through Hole  Termination Style	Coil Voltage	5VDC
Switching Voltage 250VAC, 110VDC - Max  Turn On Voltage (Max) 4 VDC  Turn Off Voltage (Min) 0.25 VDC  Operate Time 20ms  Release Time 10ms  Features Insulation - Class E  Mounting Type Through Hole  Termination Style PC Pin	Contact Form	SPST-NO (1 Form A)
Turn On Voltage (Max)  4 VDC  Turn Off Voltage (Min)  0.25 VDC  Operate Time  20ms  Release Time  10ms  Features  Insulation - Class E  Mounting Type  Through Hole  Termination Style  PC Pin	Contact Rating (Current)	10A
Turn Off Voltage (Min)  Operate Time  20ms  Release Time  10ms  Features  Insulation - Class E  Mounting Type  Through Hole  Termination Style  PC Pin	Switching Voltage	250VAC, 110VDC - Max
Operate Time20msRelease Time10msFeaturesInsulation - Class EMounting TypeThrough HoleTermination StylePC Pin	Turn On Voltage (Max)	4 VDC
Release Time 10ms Features Insulation - Class E Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	0.25 VDC
Features Insulation - Class E  Mounting Type Through Hole  Termination Style PC Pin	Operate Time	20ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	10ms
Termination Style PC Pin	Features	Insulation - Class E
•	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
Tepott offolis.		Report errors?

## **JQ1AP-5V-F Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **JQ1AP-5V-F Payment Methods**



















### **JQ1AP-5V-F Shipping Methods**













If you have any question about JQ1AP-5V-F, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com