

JR1AF-TMP-DC24V

JR1AF-TMP-DC24V Information

Heisener.com

Part Number JR1AF-TMP-DC24V

Manufacturer Panasonic Electric Works

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE SPST 16A 24V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









JR1AF-TMP-DC24V Specifications

Manufacturer Part Number Manufacturer Panasonic Electric Works Category Relays Power Relays, Over 2 Amps Package - Series JR Relay Type General Purpose Coil Type Non Latching Coil Current 22mA Coil Voltage 24VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 19.2 VDC Turn Off Voltage (Max) Turn On Voltage (Min) Operate Time Release Time 2ms Evalures - Laterian Works Panasonic Electric Works Relays Pomer Relays, Over 2 Amps Power Relays, Over 2 Amps Power Relays, Over 2 Amps Power Relays Power Amps Power Relays Power Relays Power Relays Power Amps Power Relays Power Amps P		
Category Relays Power Relays, Over 2 Amps Package - Series JR Relay Type General Purpose Coil Type Non Latching Coil Current 22mA Coil Voltage 24VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 10ms Release Time 2ms	Manufacturer Part Number	JR1AF-TMP-DC24V
Package - Series JR Relay Type General Purpose Coil Type Non Latching Coil Current 22mA Coil Voltage 24VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 10ms Release Time 2ms	Manufacturer	Panasonic Electric Works
Package - Series JR Relay Type General Purpose Coil Type Non Latching Coil Current 22mA Coil Voltage 24VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 10ms Release Time 2ms	Category	Relays
Series Relay Type General Purpose Coil Type Non Latching Coil Current 22mA Coil Voltage 24VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 10ms Release Time 2ms		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 22mA Coil Voltage 24VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 10ms Release Time 2ms	Package	-
Coil TypeNon LatchingCoil Current22mACoil Voltage24VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)16ASwitching Voltage250VAC, 30VDC - MaxTurn On Voltage (Max)19.2 VDCTurn Off Voltage (Min)2.4 VDCOperate Time10msRelease Time2ms	Series	JR
Coil Current 22mA Coil Voltage 24VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 10ms Release Time 2ms	Relay Type	General Purpose
Coil Voltage 24VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 10ms Release Time 2ms	Coil Type	Non Latching
Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 10ms Release Time 2ms	Coil Current	22mA
Contact Rating (Current) Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 10ms Release Time 2ms	Coil Voltage	24VDC
Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 10ms Release Time 2ms	Contact Form	SPST-NO (1 Form A)
Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 10ms Release Time 2ms	Contact Rating (Current)	16A
Turn Off Voltage (Min) Operate Time 10ms Release Time 2ms	Switching Voltage	250VAC, 30VDC - Max
Operate Time10msRelease Time2ms	Turn On Voltage (Max)	19.2 VDC
Release Time 2ms	Turn Off Voltage (Min)	2.4 VDC
	Operate Time	10ms
Features -	Release Time	2ms
1 cutates	Features	-
Mounting Type Through Hole	Mounting Type	Through Hole
Termination Style PC Pin, Quick Connect - 0.187" (4.7mm)	Termination Style	PC Pin, Quick Connect - 0.187" (4.7mm)
Report errors?		Report errors?

JR1AF-TMP-DC24V Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

JR1AF-TMP-DC24V Payment Methods



















JR1AF-TMP-DC24V Shipping Methods













If you have any question about JR1AF-TMP-DC24V, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com