



JRC16BP-7S(71) Information



For Reference Only

Part Number JRC16BP-7S(71)

Manufacturer Hirose Electric Co Ltd

Category Connectors, Interconnects
Circular Connectors

Description CONN PLUG 7 POS SOCKET SILVER

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









JRC16BP-7S(71) Specifications

Manufacturer Part NumberJRC16BP-7S(71)ManufacturerHirose Electric Co LtdCategoryConnectors, InterconnectsPackage-SeriesJRConnector TypePlug, Female SocketsNumber of Positions7Shell Size - Insert16Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolderFastening TypeBayonet LockOrientationKeyedIngress Protection-Shell Material, FinishAluminum Alloy, Nickel PlatedContact FinishSilverFeatures-Voltage - Rated250VAC, 350VDCCurrent Rating10A		
CategoryConnectors, InterconnectsPackage-SeriesJRConnector TypePlug, Female SocketsNumber of Positions7Shell Size - Insert16Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolderFastening TypeBayonet LockOrientationKeyedIngress Protection-Shell Material, FinishAluminum Alloy, Nickel PlatedContact FinishSilverFeatures-Voltage - Rated250VAC, 350VDCCurrent Rating10A	Manufacturer Part Number	JRC16BP-7S(71)
Package-SeriesJRConnector TypePlug, Female SocketsNumber of Positions7Shell Size - Insert16Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolderFastening TypeBayonet LockOrientationKeyedIngress Protection-Shell Material, FinishAluminum Alloy, Nickel PlatedContact FinishSilverFeatures-Voltage - Rated250VAC, 350VDCCurrent Rating10A	Manufacturer	Hirose Electric Co Ltd
Package-SeriesJRConnector TypePlug, Female SocketsNumber of Positions7Shell Size - Insert16Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolderFastening TypeBayonet LockOrientationKeyedIngress Protection-Shell Material, FinishAluminum Alloy, Nickel PlatedContact FinishSilverFeatures-Voltage - Rated250VAC, 350VDCCurrent Rating10A	Category	Connectors, Interconnects
SeriesJRConnector TypePlug, Female SocketsNumber of Positions7Shell Size - Insert16Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolderFastening TypeBayonet LockOrientationKeyedIngress Protection-Shell Material, FinishAluminum Alloy, Nickel PlatedContact FinishSilverFeatures-Voltage - Rated250VAC, 350VDCCurrent Rating10A		Circular Connectors
Connector TypePlug, Female SocketsNumber of Positions7Shell Size - Insert16Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolderFastening TypeBayonet LockOrientationKeyedIngress Protection-Shell Material, FinishAluminum Alloy, Nickel PlatedContact FinishSilverFeatures-Voltage - Rated250VAC, 350VDCCurrent Rating10A	Package	-
Number of Positions Shell Size - Insert 16 Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Fastening Type Bayonet Lock Orientation Keyed Ingress Protection Shell Material, Finish Aluminum Alloy, Nickel Plated Contact Finish Features - Voltage - Rated Current Rating 10A	Series	JR
Shell Size - Insert Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Fastening Type Bayonet Lock Orientation Keyed Ingress Protection Shell Material, Finish Aluminum Alloy, Nickel Plated Contact Finish Features - Voltage - Rated Current Rating 10A	Connector Type	Plug, Female Sockets
Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Fastening Type Bayonet Lock Orientation Keyed Ingress Protection - Shell Material, Finish Aluminum Alloy, Nickel Plated Contact Finish Silver Features - Voltage - Rated 250VAC, 350VDC Current Rating 10A	Number of Positions	7
Mounting TypeFree Hanging (In-Line)TerminationSolderFastening TypeBayonet LockOrientationKeyedIngress Protection-Shell Material, FinishAluminum Alloy, Nickel PlatedContact FinishSilverFeatures-Voltage - Rated250VAC, 350VDCCurrent Rating10A	Shell Size - Insert	16
Termination Solder Fastening Type Bayonet Lock Orientation Keyed Ingress Protection - Shell Material, Finish Aluminum Alloy, Nickel Plated Contact Finish Silver Features - Voltage - Rated 250VAC, 350VDC Current Rating 10A	Shell Size, MIL	-
Fastening Type Orientation Keyed Ingress Protection Shell Material, Finish Contact Finish Silver Features - Voltage - Rated Current Rating Bayonet Lock Keyed Aluminum Alloy, Nickel Plated Silver - 10A	Mounting Type	Free Hanging (In-Line)
Orientation Keyed Ingress Protection - Shell Material, Finish Aluminum Alloy, Nickel Plated Contact Finish Silver Features - Voltage - Rated 250VAC, 350VDC Current Rating 10A	Termination	Solder
Ingress Protection - Shell Material, Finish Aluminum Alloy, Nickel Plated Contact Finish Silver Features - Voltage - Rated 250VAC, 350VDC Current Rating 10A	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Silver Features - Voltage - Rated Current Rating Aluminum Alloy, Nickel Plated	Orientation	Keyed
Contact Finish Silver Features - Voltage - Rated Current Rating 10A	Ingress Protection	-
Features - Voltage - Rated 250VAC, 350VDC Current Rating 10A	Shell Material, Finish	Aluminum Alloy, Nickel Plated
Voltage - Rated 250VAC, 350VDC Current Rating 10A	Contact Finish	Silver
Current Rating 10A	Features	-
	Voltage - Rated	250VAC, 350VDC
Report errors?	Current Rating	10A
		Report errors?

JRC16BP-7S(71) Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

JRC16BP-7S(71) Payment Methods



















JRC16BP-7S(71) Shipping Methods













If you have any question about JRC16BP-7S(71), please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com