

JS1-B-12V-TV Information



For Reference Only

Part Number JS1-B-12V-TV

Manufacturer Panasonic Electric Works

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE SPDT 10A 12V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









JS1-B-12V-TV Specifications

Manufacturer Part NumberJS1-B-12V-TVManufacturerPanasonic Electric WorksCategoryRelaysPackage-SeriesJSRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current30mACoil Voltage12VDCContact FormSPDT (1 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 100VDC - MaxTurn On Voltage (Max)8.4 VDCTurn Off Voltage (Min)1.2 VDCOperate Time10msRelease Time10msFeaturesInsulation - Class B, Sealed - FullyMounting TypeThrough HoleTermination StylePC Pin		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesJSRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current30mACoil Voltage12VDCContact FormSPDT (1 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 100VDC - MaxTurn On Voltage (Max)8.4 VDCTurn Off Voltage (Min)1.2 VDCOperate Time10msRelease Time10msFeaturesInsulation - Class B, Sealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	JS1-B-12V-TV
Package-SeriesJSRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current30mACoil Voltage12VDCContact FormSPDT (1 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 100VDC - MaxTurn On Voltage (Max)8.4 VDCTurn Off Voltage (Min)1.2 VDCOperate Time10msRelease Time10msFeaturesInsulation - Class B, Sealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Manufacturer	Panasonic Electric Works
Package-SeriesJSRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current30mACoil Voltage12VDCContact FormSPDT (1 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 100VDC - MaxTurn On Voltage (Max)8.4 VDCTurn Off Voltage (Min)1.2 VDCOperate Time10msRelease Time10msFeaturesInsulation - Class B, Sealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Category	Relays
SeriesJSRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current30mACoil Voltage12VDCContact FormSPDT (1 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 100VDC - MaxTurn On Voltage (Max)8.4 VDCTurn Off Voltage (Min)1.2 VDCOperate Time10msRelease Time10msFeaturesInsulation - Class B, Sealed - FullyMounting TypeThrough HoleTermination StylePC Pin		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 30mA Coil Voltage 12VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 100VDC - Max Turn On Voltage (Max) 8.4 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 10ms Release Time 10ms Release Time 10ms Features Insulation - Class B, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Package	-
Coil TypeNon LatchingCoil Current30mACoil Voltage12VDCContact FormSPDT (1 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 100VDC - MaxTurn On Voltage (Max)8.4 VDCTurn Off Voltage (Min)1.2 VDCOperate Time10msRelease Time10msFeaturesInsulation - Class B, Sealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Series	JS
Coil Current 30mA Coil Voltage 12VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 100VDC - Max Turn On Voltage (Max) 8.4 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 10ms Release Time 10ms Features Insulation - Class B, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Relay Type	General Purpose
Coil Voltage 12VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 100VDC - Max Turn On Voltage (Max) 8.4 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 10ms Release Time 10ms Features Insulation - Class B, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Coil Type	Non Latching
Contact Form SPDT (1 Form C) Contact Rating (Current) Switching Voltage 250VAC, 100VDC - Max Turn On Voltage (Max) 8.4 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 10ms Release Time 10ms Features Insulation - Class B, Sealed - Fully Mounting Type Through Hole Termination Style	Coil Current	30mA
Contact Rating (Current) Switching Voltage 250VAC, 100VDC - Max 8.4 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 10ms Release Time 10ms Features Insulation - Class B, Sealed - Fully Mounting Type Through Hole Termination Style	Coil Voltage	12VDC
Switching Voltage Turn On Voltage (Max) 8.4 VDC Turn Off Voltage (Min) Operate Time 10ms Release Time 10ms Features Insulation - Class B, Sealed - Fully Mounting Type Through Hole Termination Style 250VAC, 100VDC - Max 8.4 VDC 1.2 VDC 10ms 10ms Possible Through Hole PC Pin	Contact Form	SPDT (1 Form C)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 10ms Release Time 10ms Features Insulation - Class B, Sealed - Fully Mounting Type Through Hole Termination Style 8.4 VDC 1.2 VDC 10ms 10ms PC Pin	Contact Rating (Current)	10A
Turn Off Voltage (Min) Operate Time 10ms Release Time 10ms Features Insulation - Class B, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Switching Voltage	250VAC, 100VDC - Max
Operate Time 10ms Release Time 10ms Features Insulation - Class B, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Turn On Voltage (Max)	8.4 VDC
Release Time 10ms Features Insulation - Class B, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	1.2 VDC
Features Insulation - Class B, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Operate Time	10ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	10ms
Termination Style PC Pin	Features	Insulation - Class B, Sealed - Fully
·	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
		Report errors?

JS1-B-12V-TV Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

JS1-B-12V-TV Payment Methods



















JS1-B-12V-TV Shipping Methods













If you have any question about JS1-B-12V-TV, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com