

JS1-B-18V Information



For Reference Only

Part Number JS1-B-18V

Manufacturer Panasonic Electric Works

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE SPDT 10A 18V

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









JS1-B-18V Specifications

| Manufacturer Part NumberJS1-B-18VManufacturerPanasonic Electric WorksCategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesJSRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current20mACoil Voltage18VDCContact FormSPDT (1 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 100VDC - MaxTurn On Voltage (Max)12.6 VDCTurn Off Voltage (Min)1.8 VDCOperate Time10msRelease Time10msFeaturesInsulation - Class B, Sealed - FullyMounting TypeThrough HoleTermination StylePC Pin | | |
|--|--------------------------|--------------------------------------|
| CategoryRelaysPackage-SeriesJSRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current20mACoil Voltage18VDCContact FormSPDT (1 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 100VDC - MaxTurn On Voltage (Max)12.6 VDCTurn Off Voltage (Min)1.8 VDCOperate Time10msRelease Time10msFeaturesInsulation - Class B, Sealed - FullyMounting TypeThrough Hole | Manufacturer Part Number | JS1-B-18V |
| Package - Series JS Relay Type General Purpose Coil Type Non Latching Coil Current 20mA Coil Voltage 18VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 100VDC - Max Turn On Voltage (Max) 12.6 VDC Turn Off Voltage (Min) 1.8 VDC Operate Time 10ms Release Time 10ms Features Insulation - Class B, Sealed - Fully Mounting Type Tripose | Manufacturer | Panasonic Electric Works |
| Package JS Relay Type General Purpose Coil Type Non Latching Coil Current 20mA Coil Voltage 18VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 100VDC - Max Turn On Voltage (Max) 12.6 VDC Turn Off Voltage (Min) 1.8 VDC Operate Time 10ms Release Time 10ms Features Insulation - Class B, Sealed - Fully Mounting Type Tripose | Category | Relays |
| SeriesJSRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current20mACoil Voltage18VDCContact FormSPDT (1 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 100VDC - MaxTurn On Voltage (Max)12.6 VDCTurn Off Voltage (Min)1.8 VDCOperate Time10msRelease Time10msFeaturesInsulation - Class B, Sealed - FullyMounting TypeThrough Hole | | Power Relays, Over 2 Amps |
| Relay Type General Purpose Coil Type Non Latching Coil Current 20mA Coil Voltage 18VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 100VDC - Max Turn On Voltage (Max) 12.6 VDC Turn Off Voltage (Min) 1.8 VDC Operate Time 10ms Release Time 10ms Features Insulation - Class B, Sealed - Fully Mounting Type Trhrough Hole | Package | - |
| Coil TypeNon LatchingCoil Current20mACoil Voltage18VDCContact FormSPDT (1 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 100VDC - MaxTurn On Voltage (Max)12.6 VDCTurn Off Voltage (Min)1.8 VDCOperate Time10msRelease Time10msFeaturesInsulation - Class B, Sealed - FullyMounting TypeThrough Hole | Series | JS |
| Coil Current 20mA Coil Voltage 18VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 100VDC - Max Turn On Voltage (Max) 12.6 VDC Turn Off Voltage (Min) 1.8 VDC Operate Time 10ms Release Time 10ms Release Time 10ms Features Insulation - Class B, Sealed - Fully Mounting Type Through Hole | Relay Type | General Purpose |
| Coil Voltage 18VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 100VDC - Max Turn On Voltage (Max) 12.6 VDC Turn Off Voltage (Min) 1.8 VDC Operate Time 10ms Release Time 10ms Features Insulation - Class B, Sealed - Fully Mounting Type Through Hole | Coil Type | Non Latching |
| Contact Form SPDT (1 Form C) Contact Rating (Current) Switching Voltage 250VAC, 100VDC - Max Turn On Voltage (Max) 12.6 VDC Turn Off Voltage (Min) 1.8 VDC Operate Time 10ms Release Time 10ms Features Insulation - Class B, Sealed - Fully Mounting Type Through Hole | Coil Current | 20mA |
| Contact Rating (Current) Switching Voltage 250VAC, 100VDC - Max Turn On Voltage (Max) 12.6 VDC Turn Off Voltage (Min) 1.8 VDC Operate Time 10ms Release Time 10ms Features Insulation - Class B, Sealed - Fully Mounting Type Through Hole | Coil Voltage | 18VDC |
| Switching Voltage 250VAC, 100VDC - Max Turn On Voltage (Max) 12.6 VDC Turn Off Voltage (Min) 1.8 VDC Operate Time 10ms Release Time 10ms Features Insulation - Class B, Sealed - Fully Mounting Type Through Hole | Contact Form | SPDT (1 Form C) |
| Turn On Voltage (Max) 12.6 VDC Turn Off Voltage (Min) 1.8 VDC Operate Time 10ms Release Time 10ms Features Insulation - Class B, Sealed - Fully Mounting Type Through Hole | Contact Rating (Current) | 10A |
| Turn Off Voltage (Min) Operate Time 10ms Release Time 10ms Features Insulation - Class B, Sealed - Fully Mounting Type Through Hole | Switching Voltage | 250VAC, 100VDC - Max |
| Operate Time10msRelease Time10msFeaturesInsulation - Class B, Sealed - FullyMounting TypeThrough Hole | Turn On Voltage (Max) | 12.6 VDC |
| Release Time 10ms Features Insulation - Class B, Sealed - Fully Mounting Type Through Hole | Turn Off Voltage (Min) | 1.8 VDC |
| Features Insulation - Class B, Sealed - Fully Mounting Type Through Hole | Operate Time | 10ms |
| Mounting Type Through Hole | Release Time | 10ms |
| | Features | Insulation - Class B, Sealed - Fully |
| Termination Style PC Pin | Mounting Type | Through Hole |
| | Termination Style | PC Pin |
| Report errors? | | Report errors? |

JS1-B-18V Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

JS1-B-18V Payment Methods




































If you have any question about JS1-B-18V, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com