

JS1-B-18V Information



For Reference Only

Part Number JS1-B-18V

Manufacturer Panasonic Electric Works

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE SPDT 10A 18V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









JS1-B-18V Specifications

Manufacturer Part NumberJS1-B-18VManufacturerPanasonic Electric WorksCategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesJSRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current20mACoil Voltage18VDCContact FormSPDT (1 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 100VDC - MaxTurn On Voltage (Max)12.6 VDCTurn Off Voltage (Min)1.8 VDCOperate Time10msRelease Time10msFeaturesInsulation - Class B, Sealed - FullyMounting TypeThrough HoleTermination StylePC Pin		
CategoryRelaysPackage-SeriesJSRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current20mACoil Voltage18VDCContact FormSPDT (1 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 100VDC - MaxTurn On Voltage (Max)12.6 VDCTurn Off Voltage (Min)1.8 VDCOperate Time10msRelease Time10msFeaturesInsulation - Class B, Sealed - FullyMounting TypeThrough Hole	Manufacturer Part Number	JS1-B-18V
Package - Series JS Relay Type General Purpose Coil Type Non Latching Coil Current 20mA Coil Voltage 18VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 100VDC - Max Turn On Voltage (Max) 12.6 VDC Turn Off Voltage (Min) 1.8 VDC Operate Time 10ms Release Time 10ms Features Insulation - Class B, Sealed - Fully Mounting Type Tripose	Manufacturer	Panasonic Electric Works
Package JS Relay Type General Purpose Coil Type Non Latching Coil Current 20mA Coil Voltage 18VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 100VDC - Max Turn On Voltage (Max) 12.6 VDC Turn Off Voltage (Min) 1.8 VDC Operate Time 10ms Release Time 10ms Features Insulation - Class B, Sealed - Fully Mounting Type Tripose	Category	Relays
SeriesJSRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current20mACoil Voltage18VDCContact FormSPDT (1 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 100VDC - MaxTurn On Voltage (Max)12.6 VDCTurn Off Voltage (Min)1.8 VDCOperate Time10msRelease Time10msFeaturesInsulation - Class B, Sealed - FullyMounting TypeThrough Hole		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 20mA Coil Voltage 18VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 100VDC - Max Turn On Voltage (Max) 12.6 VDC Turn Off Voltage (Min) 1.8 VDC Operate Time 10ms Release Time 10ms Features Insulation - Class B, Sealed - Fully Mounting Type Trhrough Hole	Package	-
Coil TypeNon LatchingCoil Current20mACoil Voltage18VDCContact FormSPDT (1 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 100VDC - MaxTurn On Voltage (Max)12.6 VDCTurn Off Voltage (Min)1.8 VDCOperate Time10msRelease Time10msFeaturesInsulation - Class B, Sealed - FullyMounting TypeThrough Hole	Series	JS
Coil Current 20mA Coil Voltage 18VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 100VDC - Max Turn On Voltage (Max) 12.6 VDC Turn Off Voltage (Min) 1.8 VDC Operate Time 10ms Release Time 10ms Release Time 10ms Features Insulation - Class B, Sealed - Fully Mounting Type Through Hole	Relay Type	General Purpose
Coil Voltage 18VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 100VDC - Max Turn On Voltage (Max) 12.6 VDC Turn Off Voltage (Min) 1.8 VDC Operate Time 10ms Release Time 10ms Features Insulation - Class B, Sealed - Fully Mounting Type Through Hole	Coil Type	Non Latching
Contact Form SPDT (1 Form C) Contact Rating (Current) Switching Voltage 250VAC, 100VDC - Max Turn On Voltage (Max) 12.6 VDC Turn Off Voltage (Min) 1.8 VDC Operate Time 10ms Release Time 10ms Features Insulation - Class B, Sealed - Fully Mounting Type Through Hole	Coil Current	20mA
Contact Rating (Current) Switching Voltage 250VAC, 100VDC - Max Turn On Voltage (Max) 12.6 VDC Turn Off Voltage (Min) 1.8 VDC Operate Time 10ms Release Time 10ms Features Insulation - Class B, Sealed - Fully Mounting Type Through Hole	Coil Voltage	18VDC
Switching Voltage 250VAC, 100VDC - Max Turn On Voltage (Max) 12.6 VDC Turn Off Voltage (Min) 1.8 VDC Operate Time 10ms Release Time 10ms Features Insulation - Class B, Sealed - Fully Mounting Type Through Hole	Contact Form	SPDT (1 Form C)
Turn On Voltage (Max) 12.6 VDC Turn Off Voltage (Min) 1.8 VDC Operate Time 10ms Release Time 10ms Features Insulation - Class B, Sealed - Fully Mounting Type Through Hole	Contact Rating (Current)	10A
Turn Off Voltage (Min) Operate Time 10ms Release Time 10ms Features Insulation - Class B, Sealed - Fully Mounting Type Through Hole	Switching Voltage	250VAC, 100VDC - Max
Operate Time10msRelease Time10msFeaturesInsulation - Class B, Sealed - FullyMounting TypeThrough Hole	Turn On Voltage (Max)	12.6 VDC
Release Time 10ms Features Insulation - Class B, Sealed - Fully Mounting Type Through Hole	Turn Off Voltage (Min)	1.8 VDC
Features Insulation - Class B, Sealed - Fully Mounting Type Through Hole	Operate Time	10ms
Mounting Type Through Hole	Release Time	10ms
	Features	Insulation - Class B, Sealed - Fully
Termination Style PC Pin	Mounting Type	Through Hole
	Termination Style	PC Pin
Report errors?		Report errors?

JS1-B-18V Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

JS1-B-18V Payment Methods



































If you have any question about JS1-B-18V, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com