

#### JS1-B-48V-F Information



For Reference Only

Part Number JS1-B-48V-F

Manufacturer Panasonic Electric Works

**Category** Relays

Power Relays, Over 2 Amps

**Description** RELAY GEN PURPOSE SPDT 10A 48V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **JS1-B-48V-F Specifications**

Manufacturer Part NumberJS1-B-48V-FManufacturerPanasonic Electric WorksCategoryRelaysPackage-SeriesJSRelay TypeGeneral PurposeCoil Current7.5mACoil Voltage48VDCContact FormSPDT (1 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 100VDC - MaxTurn On Voltage (Max)33.6 VDCTurn Off Voltage (Min)4.8 VDCOperate Time10msRelease Time10msFeaturesInsulation - Class B, Sealed - FullyMounting TypeThrough HoleTermination StylePC Pin		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesJSRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current7.5mACoil Voltage48VDCContact FormSPDT (1 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 100VDC - MaxTurn On Voltage (Max)33.6 VDCTurn Off Voltage (Min)4.8 VDCOperate Time10msRelease Time10msFeaturesInsulation - Class B, Sealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	JS1-B-48V-F
Package-SeriesJSRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current7.5mACoil Voltage48VDCContact FormSPDT (1 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 100VDC - MaxTurn On Voltage (Max)33.6 VDCTurn Off Voltage (Min)4.8 VDCOperate Time10msRelease Time10msFeaturesInsulation - Class B, Sealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Manufacturer	Panasonic Electric Works
Package-SeriesJSRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current7.5mACoil Voltage48VDCContact FormSPDT (1 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 100VDC - MaxTurn On Voltage (Max)33.6 VDCTurn Off Voltage (Min)4.8 VDCOperate Time10msRelease Time10msFeaturesInsulation - Class B, Sealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Category	Relays
SeriesJSRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current7.5mACoil Voltage48VDCContact FormSPDT (1 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 100VDC - MaxTurn On Voltage (Max)33.6 VDCTurn Off Voltage (Min)4.8 VDCOperate Time10msRelease Time10msFeaturesInsulation - Class B, Sealed - FullyMounting TypeThrough HoleTermination StylePC Pin		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 7.5mA Coil Voltage 48VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 100VDC - Max Turn On Voltage (Max) 33.6 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 10ms Release Time 10ms Release Time 10ms Features Insulation - Class B, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Package	-
Coil TypeNon LatchingCoil Current7.5mACoil Voltage48VDCContact FormSPDT (1 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 100VDC - MaxTurn On Voltage (Max)33.6 VDCTurn Off Voltage (Min)4.8 VDCOperate Time10msRelease Time10msFeaturesInsulation - Class B, Sealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Series	JS
Coil Current Coil Voltage 48VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 100VDC - Max Turn On Voltage (Max) 33.6 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 10ms Release Time 10ms Features Insulation - Class B, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Relay Type	General Purpose
Coil Voltage 48VDC  Contact Form SPDT (1 Form C)  Contact Rating (Current) 10A  Switching Voltage 250VAC, 100VDC - Max  Turn On Voltage (Max) 33.6 VDC  Turn Off Voltage (Min) 4.8 VDC  Operate Time 10ms  Release Time 10ms  Release Time 10ms  Features Insulation - Class B, Sealed - Fully  Mounting Type Through Hole  Termination Style PC Pin	Coil Type	Non Latching
Contact Form SPDT (1 Form C)  Contact Rating (Current)  Switching Voltage  250VAC, 100VDC - Max  Turn On Voltage (Max)  33.6 VDC  Turn Off Voltage (Min)  Operate Time  10ms  Release Time  10ms  Release Time  10ms  Features  Insulation - Class B, Sealed - Fully  Mounting Type  Through Hole  Termination Style	Coil Current	7.5mA
Contact Rating (Current)  Switching Voltage  250VAC, 100VDC - Max  Turn On Voltage (Max)  33.6 VDC  Turn Off Voltage (Min)  4.8 VDC  Operate Time  10ms  Release Time  10ms  Features  Insulation - Class B, Sealed - Fully  Mounting Type  Through Hole  Termination Style  PC Pin	Coil Voltage	48VDC
Switching Voltage  250VAC, 100VDC - Max  Turn On Voltage (Max)  33.6 VDC  Turn Off Voltage (Min)  4.8 VDC  Operate Time  10ms  Release Time  10ms  Features  Insulation - Class B, Sealed - Fully  Mounting Type  Through Hole  Termination Style  PC Pin	Contact Form	SPDT (1 Form C)
Turn On Voltage (Max)  Turn Off Voltage (Min)  4.8 VDC  Operate Time  10ms  Release Time  10ms  Features  Insulation - Class B, Sealed - Fully  Mounting Type  Through Hole  Termination Style  7 PC Pin	Contact Rating (Current)	10A
Turn Off Voltage (Min)  Operate Time  10ms  Release Time  10ms  Features  Insulation - Class B, Sealed - Fully  Mounting Type  Through Hole  Termination Style  PC Pin	Switching Voltage	250VAC, 100VDC - Max
Operate Time 10ms Release Time 10ms Features Insulation - Class B, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Turn On Voltage (Max)	33.6 VDC
Release Time 10ms Features Insulation - Class B, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	4.8 VDC
Features Insulation - Class B, Sealed - Fully  Mounting Type Through Hole  Termination Style PC Pin	Operate Time	10ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	10ms
Termination Style PC Pin	Features	Insulation - Class B, Sealed - Fully
·	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
		Report errors?

#### JS1-B-48V-F Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### JS1-B-48V-F Payment Methods



















# JS1-B-48V-F Shipping Methods













If you have any question about JS1-B-48V-F, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com