

JS1AF-B-6V Information

Heisener.com

Part Number JS1AF-B-6V

Manufacturer Panasonic Electric Works

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE SPST 10A 6V

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









JS1AF-B-6V Specifications

Manufacturer Part Number Manufacturer Panasonic Electric Works Category Relays Power Relays, Over 2 Amps Package - Series JS Relay Type General Purpose Coil Type Non Latching Coil Current 60mA Coil Voltage Contact Form SPST-NO (1 Form A) Contact Rating (Current) Switching Voltage 250VAC, 100VDC - Max
Category Relays Power Relays, Over 2 Amps Package Series JS Relay Type General Purpose Coil Type Non Latching Coil Current 60mA Coil Voltage 6VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 10A
Package - Series JS Relay Type General Purpose Coil Type Non Latching Coil Current 60mA Coil Voltage 6VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 10A
Package - Series JS Relay Type General Purpose Coil Type Non Latching Coil Current 60mA Coil Voltage 6VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 10A
Series JS Relay Type General Purpose Coil Type Non Latching Coil Current 60mA Coil Voltage 6VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 10A
Relay Type General Purpose Coil Type Non Latching Coil Current 60mA Coil Voltage 6VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 10A
Coil Type Non Latching Coil Current 60mA Coil Voltage 6VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 10A
Coil Current 60mA Coil Voltage 6VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 10A
Coil Voltage 6VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 10A
Contact Form SPST-NO (1 Form A) Contact Rating (Current) 10A
Contact Rating (Current) 10A
Switching Voltage 250VAC 100VDC - Max
5 whening votage
Turn On Voltage (Max) 4.2 VDC
Turn Off Voltage (Min) 0.6 VDC
Operate Time 10ms
Release Time 10ms
Features Insulation - Class B, Sealed - Flux Protection
Mounting Type Through Hole
Termination Style PC Pin
Report errors?

JS1AF-B-6V Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

JS1AF-B-6V Payment Methods



















JS1AF-B-6V Shipping Methods













If you have any question about JS1AF-B-6V, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com