

JS1AF-F-48V-F Information

Heisener.com

Part Number JS1AF-F-48V-F

Manufacturer Panasonic Electric Works

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE SPST 10A 48V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









JS1AF-F-48V-F Specifications

Manufacturer Part Number Manufacturer Panasonic Electric Works Relays Power Relays, Over 2 Amps Package Series JS Relay Type General Purpose Non Latching Coil Current 7.5mA Coil Voltage 48VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) Switching Voltage 10A Switching Voltage (Max) Turn On Voltage (Min) Operate Time 10ms Release Time 10ms Release Time Insulation - Class F, Sealed - Flux Protection Mounting Type Through Hole PC Pin Report errors?		
Category Relays Power Relays, Over 2 Amps Package - Series JS Relay Type General Purpose Coil Type Non Latching Coil Current 7.5mA Coil Voltage 48VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 10A Switching Voltage 250VAC, 100VDC - Max Turn On Voltage (Max) 33.6 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 10ms Release Time 10ms Features Insulation - Class F, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Manufacturer Part Number	JS1AF-F-48V-F
Power Relays, Over 2 Amps Package - Series JS Relay Type General Purpose Coil Type Non Latching Coil Current 7.5mA Coil Voltage 48VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 10A Switching Voltage 250VAC, 100VDC - Max Turn On Voltage (Max) 33.6 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 10ms Release Time 10ms Features Insulation - Class F, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Manufacturer	Panasonic Electric Works
Package - Series JS Relay Type General Purpose Coil Type Non Latching Coil Current 7.5mA Coil Voltage 48VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 10A Switching Voltage 250VAC, 100VDC - Max Turn On Voltage (Max) 33.6 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 10ms Release Time 10ms Features Insulation - Class F, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Category	Relays
Series JS Relay Type General Purpose Coil Type Non Latching Coil Current 7.5mA Coil Voltage 48VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 10A Switching Voltage 250VAC, 100VDC - Max Turn On Voltage (Max) 33.6 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 10ms Release Time 10ms Features Insulation - Class F, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 7.5mA Coil Voltage 48VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 10A Switching Voltage 250VAC, 100VDC - Max Turn On Voltage (Max) 33.6 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 10ms Release Time 10ms Features Insulation - Class F, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Package	-
Coil Type Non Latching Coil Current 7.5mA Coil Voltage 48VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 10A Switching Voltage 250VAC, 100VDC - Max Turn On Voltage (Max) 33.6 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 10ms Release Time 10ms Features Insulation - Class F, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Series	JS
Coil Current Coil Voltage 48VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 10A Switching Voltage 250VAC, 100VDC - Max Turn On Voltage (Max) 33.6 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 10ms Release Time 10ms Features Insulation - Class F, Sealed - Flux Protection Mounting Type Through Hole Termination Style	Relay Type	General Purpose
Coil Voltage 48VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 10A Switching Voltage 250VAC, 100VDC - Max Turn On Voltage (Max) 33.6 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 10ms Release Time 10ms Features Insulation - Class F, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Coil Type	Non Latching
Contact Form SPST-NO (1 Form A) Contact Rating (Current) 10A Switching Voltage 250VAC, 100VDC - Max Turn On Voltage (Max) 33.6 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 10ms Release Time 10ms Features Insulation - Class F, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Coil Current	7.5mA
Contact Rating (Current) Switching Voltage 250VAC, 100VDC - Max Turn On Voltage (Max) 33.6 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 10ms Release Time 10ms Features Insulation - Class F, Sealed - Flux Protection Mounting Type Through Hole Termination Style	Coil Voltage	48VDC
Switching Voltage Turn On Voltage (Max) 33.6 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 10ms Release Time 10ms Features Insulation - Class F, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Contact Form	SPST-NO (1 Form A)
Turn On Voltage (Max) Turn Off Voltage (Min) 4.8 VDC Operate Time 10ms Release Time 10ms Features Insulation - Class F, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Contact Rating (Current)	10A
Turn Off Voltage (Min) 4.8 VDC Operate Time 10ms Release Time 10ms Features Insulation - Class F, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Switching Voltage	250VAC, 100VDC - Max
Operate Time 10ms Release Time 10ms Features Insulation - Class F, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Turn On Voltage (Max)	33.6 VDC
Release Time 10ms Features Insulation - Class F, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	4.8 VDC
Features Insulation - Class F, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Operate Time	10ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	10ms
Termination Style PC Pin	Features	Insulation - Class F, Sealed - Flux Protection
	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
		Report errors?

JS1AF-F-48V-F Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

JS1AF-F-48V-F Payment Methods





















JS1AF-F-48V-F Shipping Methods













If you have any question about JS1AF-F-48V-F, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com