

JT7-1104NL Information



For Reference Only

Part Number JT7-1104NL

Manufacturer Pulse Electronics Network
Category Connectors, Interconnects

Modular Connectors - Jacks With Magnetics

Description CONN MAGJACK 1PORT 10G BASE-T

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









JT7-1104NL Specifications

Manufacturer Part Number JTT-1104NL Manufacturer Pulse Electronics Network Category Connectors, Interconnects Modular Connectors - Jacks With Magnetics Package - Series PULSEJACK? JT7 Connector Type RJ45 Number of Ports 1 Number of Rows 1 Applications 10G Base-T, AutoMDIX Mounting Type Through Hole Orientation 90° Angle (Right) Termination Solder Height Above Board 0.525" (13.33mm) LED Color Green, Yellow - Green Number of Cores per Jack 8 Shielding Shielded, EMI Finger Features Board Guide Tab Direction Up Contact Material Phosphor Bronze Contact Finish Gold Operating Temperature 0°C ~ 70°C		
Category Connectors, Interconnects Modular Connectors - Jacks With Magnetics Package - Series PULSEJACK? JT7 Connector Type RJ45 Number of Ports 1 Number of Rows 1 Applications 10G Base-T, AutoMDIX Mounting Type Through Hole Orientation 90° Angle (Right) Termination Solder Height Above Board 0.525" (13.33mm) LED Color Green, Yellow - Green Number of Cores per Jack 8 Shielding Shielded, EMI Finger Features Board Guide Tab Direction Up Contact Material Orientain Gold Operating Temperature 0°C ~ 70°C	Manufacturer Part Number	JT7-1104NL
Package-SeriesPULSEJACK? JT7Connector TypeRJ45Number of Ports1Number of Rows1Applications10G Base-T, AutoMDIXMounting TypeThrough HoleOrientation90° Angle (Right)TerminationSolderHeight Above Board0.525" (13.33mm)LED ColorGreen, Yellow - GreenNumber of Cores per Jack8ShieldingShielded, EMI FingerFeaturesBoard GuideTab DirectionUpContact MaterialPhosphor BronzeContact FinishGoldOperating Temperature0°C ~ 70°C	Manufacturer	Pulse Electronics Network
Package-SeriesPULSEJACK? JT7Connector TypeRJ45Number of Ports1Number of Rows1Applications10G Base-T, AutoMDIXMounting TypeThrough HoleOrientation90° Angle (Right)TerminationSolderHeight Above Board0.525" (13.33mm)LED ColorGreen, Yellow - GreenNumber of Cores per Jack8ShieldingShielded, EMI FingerFeaturesBoard GuideTab DirectionUpContact MaterialPhosphor BronzeContact FinishGoldOperating Temperature0°C ~ 70°C	Category	Connectors, Interconnects
SeriesPULSEJACK? JT7Connector TypeRJ45Number of Ports1Number of Rows1Applications10G Base-T, AutoMDIXMounting TypeThrough HoleOrientation90° Angle (Right)TerminationSolderHeight Above Board0.525" (13.33mm)LED ColorGreen, Yellow - GreenNumber of Cores per Jack8ShieldingShielded, EMI FingerFeaturesBoard GuideTab DirectionUpContact MaterialPhosphor BronzeContact FinishGoldOperating Temperature0°C ~ 70°C		Modular Connectors - Jacks With Magnetics
Connector TypeRJ45Number of Ports1Number of Rows1Applications10G Base-T, AutoMDIXMounting TypeThrough HoleOrientation90° Angle (Right)TerminationSolderHeight Above Board0.525" (13.33mm)LED ColorGreen, Yellow - GreenNumber of Cores per Jack8ShieldingShielded, EMI FingerFeaturesBoard GuideTab DirectionUpContact MaterialPhosphor BronzeContact FinishGoldOperating Temperature0°C ~ 70°C	Package	-
Number of Ports1Number of Rows1Applications10G Base-T, AutoMDIXMounting TypeThrough HoleOrientation90° Angle (Right)TerminationSolderHeight Above Board0.525" (13.33mm)LED ColorGreen, Yellow - GreenNumber of Cores per Jack8ShieldingShielded, EMI FingerFeaturesBoard GuideTab DirectionUpContact MaterialPhosphor BronzeContact FinishGoldOperating Temperature0°C ~ 70°C	Series	PULSEJACK? JT7
Number of Rows1Applications10G Base-T, AutoMDIXMounting TypeThrough HoleOrientation90° Angle (Right)TerminationSolderHeight Above Board0.525" (13.33mm)LED ColorGreen, Yellow - GreenNumber of Cores per Jack8ShieldingShielded, EMI FingerFeaturesBoard GuideTab DirectionUpContact MaterialPhosphor BronzeContact FinishGoldOperating Temperature0°C ~ 70°C	Connector Type	RJ45
Applications Mounting Type Through Hole Orientation 90° Angle (Right) Termination Solder Height Above Board LED Color Green, Yellow - Green Number of Cores per Jack Shielding Shielded, EMI Finger Features Board Guide Tab Direction Up Contact Material Phosphor Bronze Contact Finish Operating Temperature 10G Base-T, AutoMDIX Through Hole Green, AutoMDIX 10G Base-T, AutoMD	Number of Ports	1
Mounting TypeThrough HoleOrientation90° Angle (Right)TerminationSolderHeight Above Board0.525" (13.33mm)LED ColorGreen, Yellow - GreenNumber of Cores per Jack8ShieldingShielded, EMI FingerFeaturesBoard GuideTab DirectionUpContact MaterialPhosphor BronzeContact FinishGoldOperating Temperature0°C ~ 70°C	Number of Rows	1
Orientation 90° Angle (Right) Termination Solder Height Above Board 0.525" (13.33mm) LED Color Green, Yellow - Green Number of Cores per Jack 8 Shielding Shielded, EMI Finger Features Board Guide Tab Direction Up Contact Material Phosphor Bronze Contact Finish Gold Operating Temperature 0°C ~ 70°C	Applications	10G Base-T, AutoMDIX
Termination Solder Height Above Board 0.525" (13.33mm) LED Color Green, Yellow - Green Number of Cores per Jack Shielding Shielded, EMI Finger Features Board Guide Tab Direction Up Contact Material Phosphor Bronze Contact Finish Gold Operating Temperature Solder 0.525" (13.33mm) Green, Yellow - Green Board B	Mounting Type	Through Hole
Height Above Board LED Color Green, Yellow - Green Number of Cores per Jack 8 Shielding Shielded, EMI Finger Features Board Guide Tab Direction Up Contact Material Phosphor Bronze Contact Finish Gold Operating Temperature 0°C ~ 70°C	Orientation	90° Angle (Right)
LED ColorGreen, Yellow - GreenNumber of Cores per Jack8ShieldingShielded, EMI FingerFeaturesBoard GuideTab DirectionUpContact MaterialPhosphor BronzeContact FinishGoldOperating Temperature0°C ~ 70°C	Termination	Solder
Number of Cores per Jack Shielding Shielded, EMI Finger Features Board Guide Tab Direction Up Contact Material Phosphor Bronze Contact Finish Gold Operating Temperature 8 Shielded, EMI Finger Board Guide Up Cord Operating Temperature 8 Shielded, EMI Finger Board Guide Up Cord Operating Temperature	Height Above Board	0.525" (13.33mm)
Shielding Shielded, EMI Finger Features Board Guide Tab Direction Up Contact Material Phosphor Bronze Contact Finish Gold Operating Temperature 0°C ~ 70°C	LED Color	Green, Yellow - Green
Features Board Guide Tab Direction Up Contact Material Phosphor Bronze Contact Finish Gold Operating Temperature 0°C ~ 70°C	Number of Cores per Jack	8
Tab DirectionUpContact MaterialPhosphor BronzeContact FinishGoldOperating Temperature 0° C ~ 70° C	Shielding	Shielded, EMI Finger
Contact Material Phosphor Bronze Contact Finish Gold Operating Temperature 0°C ~ 70°C	Features	Board Guide
Contact Finish Gold Operating Temperature $0^{\circ}\text{C} \sim 70^{\circ}\text{C}$	Tab Direction	Up
Operating Temperature $0^{\circ}\text{C} \sim 70^{\circ}\text{C}$	Contact Material	Phosphor Bronze
	Contact Finish	Gold
Report errors?	Operating Temperature	0°C ~ 70°C
		Report errors?

JT7-1104NL Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

JT7-1104NL Payment Methods



















JT7-1104NL Shipping Methods













If you have any question about JT7-1104NL, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com