



JTN1AS-PA-F-DC6V Information



For Reference Only

Part Number JTN1AS-PA-F-DC6V

Manufacturer Panasonic Electric Works

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE SPST 30A 6V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









JTN1AS-PA-F-DC6V Specifications

Manufacturer Part Number JTN1AS-PA-F-DC6V Manufacturer Panasonic Electric Works Category Relays Power Relays, Over 2 Amps Package - Series JT-N Relay Type General Purpose Coil Type Non Latching Coil Current 133.3mA Coil Voltage 6VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 30A Switching Voltage 277VAC - Max Turn On Voltage (Max) 4.5 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 20ms Release Time 10ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin		
CategoryRelaysPackage-SeriesJT-NRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current133.3mACoil Voltage6VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)30ASwitching Voltage277VAC - MaxTurn On Voltage (Max)4.5 VDCTurn Off Voltage (Min)0.6 VDCOperate Time20msRelease Time10msFeaturesInsulation - Class F, Sealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	JTN1AS-PA-F-DC6V
Package-SeriesJT-NRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current133.3mACoil Voltage6VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)30ASwitching Voltage277VAC - MaxTurn On Voltage (Max)4.5 VDCTurn Off Voltage (Min)0.6 VDCOperate Time20msRelease Time10msFeaturesInsulation - Class F, Sealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Manufacturer	Panasonic Electric Works
Package - Series JT-N Relay Type General Purpose Coil Type Non Latching Coil Current 133.3mA Coil Voltage 6VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 30A Switching Voltage 277VAC - Max Turn On Voltage (Max) 4.5 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 20ms Release Time 10ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Category	Relays
SeriesJT-NRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current133.3mACoil Voltage6VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)30ASwitching Voltage277VAC - MaxTurn On Voltage (Max)4.5 VDCTurn Off Voltage (Min)0.6 VDCOperate Time20msRelease Time10msFeaturesInsulation - Class F, Sealed - FullyMounting TypeThrough HoleTermination StylePC Pin		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 133.3mA Coil Voltage 6VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 30A Switching Voltage 277VAC - Max Turn On Voltage (Max) 4.5 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 20ms Release Time 10ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Package	-
Coil TypeNon LatchingCoil Current133.3mACoil Voltage6VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)30ASwitching Voltage277VAC - MaxTurn On Voltage (Max)4.5 VDCTurn Off Voltage (Min)0.6 VDCOperate Time20msRelease Time10msFeaturesInsulation - Class F, Sealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Series	JT-N
Coil Current 133.3mA Coil Voltage 6VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 30A Switching Voltage 277VAC - Max Turn On Voltage (Max) 4.5 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 20ms Release Time 10ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Relay Type	General Purpose
Coil Voltage 6VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 30A Switching Voltage 277VAC - Max Turn On Voltage (Max) 4.5 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 20ms Release Time 10ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Coil Type	Non Latching
Contact Form SPST-NO (1 Form A) Contact Rating (Current) 30A Switching Voltage 277VAC - Max Turn On Voltage (Max) 4.5 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 20ms Release Time 10ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Coil Current	133.3mA
Contact Rating (Current) Switching Voltage 277VAC - Max Turn On Voltage (Max) 4.5 VDC Turn Off Voltage (Min) Operate Time 20ms Release Time 10ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole Termination Style	Coil Voltage	6VDC
Switching Voltage Turn On Voltage (Max) 4.5 VDC Turn Off Voltage (Min) Operate Time 20ms Release Time 10ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole Termination Style 277VAC - Max 4.5 VDC 0.6 VDC 10ms For time 20ms 10ms For time PC Pin	Contact Form	SPST-NO (1 Form A)
Turn On Voltage (Max) 4.5 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 20ms Release Time 10ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Contact Rating (Current)	30A
Turn Off Voltage (Min) Operate Time 20ms Release Time 10ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Switching Voltage	277VAC - Max
Operate Time 20ms Release Time 10ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Turn On Voltage (Max)	4.5 VDC
Release Time 10ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	0.6 VDC
Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Operate Time	20ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	10ms
Termination Style PC Pin	Features	Insulation - Class F, Sealed - Fully
	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
		Report errors?

JTN1AS-PA-F-DC6V Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

JTN1AS-PA-F-DC6V Payment Methods



















JTN1AS-PA-F-DC6V Shipping Methods













If you have any question about JTN1AS-PA-F-DC6V, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com