

JTN1AS-TMP-F-DC9V

JTN1AS-TMP-F-DC9V Information



For Reference Only

Part Number JTN1AS-TMP-F-DC9V

Manufacturer Panasonic Electric Works

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE SPST 30A 9V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









JTN1AS-TMP-F-DC9V Specifications

Manufacturer Part NumberJTNIAS-TMP-F-DC9VManufacturerPanasonic Electric WorksCategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesJT-NRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current88.9mACoil Voltage9VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)30ASwitching Voltage277VAC - MaxTurn On Voltage (Max)6.75 VDCTurn Off Voltage (Min)0.9 VDCOperate Time20msRelease Time10msFeaturesInsulation - Class F, Sealed - FullyMounting TypeThrough HoleTermination StylePC Pin, Quick Connect - 0.250" (6.3mm)		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesJT-NRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current88.9mACoil Voltage9VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)30ASwitching Voltage277VAC - MaxTurn On Voltage (Max)6.75 VDCTurn Off Voltage (Min)0.9 VDCOperate Time20msRelease Time10msFeaturesInsulation - Class F, Sealed - FullyMounting TypeThrough HoleTermination StylePC Pin, Quick Connect - 0.250" (6.3mm)	Manufacturer Part Number	JTN1AS-TMP-F-DC9V
Package - Series JT-N Relay Type General Purpose Coil Type Non Latching Coil Current 88.9mA Coil Voltage 9VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 30A Switching Voltage 277VAC - Max Turn On Voltage (Max) 6.75 VDC Turn Off Voltage (Min) 0.9 VDC Operate Time 20ms Release Time 10ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole Termination Style PC Contact Canada Survey (6.3mm)	Manufacturer	Panasonic Electric Works
Package - Series JT-N Relay Type General Purpose Coil Type Non Latching Coil Current 88.9mA Coil Voltage 9VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 30A Switching Voltage 277VAC - Max Turn On Voltage (Max) 6.75 VDC Turn Off Voltage (Min) 0.9 VDC Operate Time 20ms Release Time 10ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.250" (6.3mm)	Category	Relays
SeriesJT-NRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current88.9mACoil Voltage9VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)30ASwitching Voltage277VAC - MaxTurn On Voltage (Max)6.75 VDCTurn Off Voltage (Min)0.9 VDCOperate Time20msRelease Time10msFeaturesInsulation - Class F, Sealed - FullyMounting TypeThrough HoleTermination StylePC Pin, Quick Connect - 0.250" (6.3mm)		Power Relays, Over 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current88.9mACoil Voltage9VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)30ASwitching Voltage277VAC - MaxTurn On Voltage (Max)6.75 VDCTurn Off Voltage (Min)0.9 VDCOperate Time20msRelease Time10msFeaturesInsulation - Class F, Sealed - FullyMounting TypeThrough HoleTermination StylePC Pin, Quick Connect - 0.250" (6.3mm)	Package	-
Coil TypeNon LatchingCoil Current88.9mACoil Voltage9VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)30ASwitching Voltage277VAC - MaxTurn On Voltage (Max)6.75 VDCTurn Off Voltage (Min)0.9 VDCOperate Time20msRelease Time10msFeaturesInsulation - Class F, Sealed - FullyMounting TypeThrough HoleTermination StylePC Pin, Quick Connect - 0.250" (6.3mm)	Series	JT-N
Coil Current Coil Voltage 9VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 30A Switching Voltage 277VAC - Max Turn On Voltage (Max) 6.75 VDC Turn Off Voltage (Min) 0.9 VDC Operate Time 20ms Release Time 10ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.250" (6.3mm)	Relay Type	General Purpose
Coil Voltage 9VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 30A Switching Voltage 277VAC - Max Turn On Voltage (Max) 6.75 VDC Turn Off Voltage (Min) 0.9 VDC Operate Time 20ms Release Time 10ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.250" (6.3mm)	Coil Type	Non Latching
Contact Form SPST-NO (1 Form A) Contact Rating (Current) 30A Switching Voltage 277VAC - Max Turn On Voltage (Max) 6.75 VDC Turn Off Voltage (Min) 0.9 VDC Operate Time 20ms Release Time 10ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.250" (6.3mm)	Coil Current	88.9mA
Contact Rating (Current) Switching Voltage 277VAC - Max 6.75 VDC Turn Off Voltage (Min) Operate Time 20ms Release Time 10ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.250" (6.3mm)	Coil Voltage	9VDC
Switching Voltage 277VAC - Max Turn On Voltage (Max) 6.75 VDC Turn Off Voltage (Min) 0.9 VDC Operate Time 20ms Release Time 10ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.250" (6.3mm)	Contact Form	SPST-NO (1 Form A)
Turn On Voltage (Max) Furn Off Voltage (Min) Operate Time 20ms Release Time 10ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole Termination Style 6.75 VDC 6.75 VDC 6.75 VDC 1.94 VDC 1.95 VDC 1.96 VDC 1.9	Contact Rating (Current)	30A
Turn Off Voltage (Min) Operate Time 20ms Release Time 10ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.250" (6.3mm)	Switching Voltage	277VAC - Max
Operate Time 20ms Release Time 10ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.250" (6.3mm)	Turn On Voltage (Max)	6.75 VDC
Release Time 10ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.250" (6.3mm)	Turn Off Voltage (Min)	0.9 VDC
Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.250" (6.3mm)	Operate Time	20ms
Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.250" (6.3mm)	Release Time	10ms
Termination Style PC Pin, Quick Connect - 0.250" (6.3mm)	Features	Insulation - Class F, Sealed - Fully
•	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin, Quick Connect - 0.250" (6.3mm)
		Report errors?

JTN1AS-TMP-F-DC9V Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

JTN1AS-TMP-F-DC9V Payment Methods



















JTN1AS-TMP-F-DC9V Shipping Methods













If you have any question about JTN1AS-TMP-F-DC9V, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com