



#### JTN1S-PA-F-DC24V Information



For Reference Only

Part Number JTN1S-PA-F-DC24V

Manufacturer Panasonic Electric Works

**Category** Relays

Power Relays, Over 2 Amps

**Description** RELAY GEN PURPOSE SPDT 20A 24V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## JTN1S-PA-F-DC24V Specifications

Manufacturer Part Number  Manufacturer  Panasonic Electric Works  Relays  Power Relays, Over 2 Amps  Package  - Series  JT-N  Relay Type  General Purpose  Coil Current  33.3mA  Coil Voltage  Contact Form  SPDT (1 Form C)  Contact Rating (Current)  20A  Switching Voltage  Turn On Voltage (Max)  Turn On Voltage (Max)  Turn Off Voltage (Min)  Operate Time  Release Time  1 Ioms  Features  Insulation - Class F, Sealed - Fully  Mounting Type  Termination Style  Panasonic Electric Works  Relays  Panasonic Electric Works  Relays  Relays  Panasonic Electric Works  Relays  Panasonic Electric Works  Relays  Panasonic Electric Works  Relays  Power Relays  Power Relays  Power Relays  Power 2 Amps  Power Relays  JT-N  Sampa  Power Relays  Power Relays  Power Relays  Power Relays  Power Relays  Panasonic Electric Works  Selays  Relays  Power Relays  Insulation - Class F, Sealed - Fully  Mounting Type  Through Hole  Pc Pin		
CategoryRelaysPackage-SeriesJT-NRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current33.3mACoil Voltage24VDCContact FormSPDT (1 Form C)Contact Rating (Current)20ASwitching Voltage277VAC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)2.4 VDCOperate Time20msRelease Time10msFeaturesInsulation - Class F, Sealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	JTN1S-PA-F-DC24V
Package-SeriesJT-NRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current33.3mACoil Voltage24VDCContact FormSPDT (1 Form C)Contact Rating (Current)20ASwitching Voltage277VAC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)2.4 VDCOperate Time20msRelease Time10msFeaturesInsulation - Class F, Sealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Manufacturer	Panasonic Electric Works
Package-SeriesJT-NRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current33.3mACoil Voltage24VDCContact FormSPDT (1 Form C)Contact Rating (Current)20ASwitching Voltage277VAC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)2.4 VDCOperate Time20msRelease Time10msFeaturesInsulation - Class F, Sealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Category	Relays
SeriesJT-NRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current33.3mACoil Voltage24VDCContact FormSPDT (1 Form C)Contact Rating (Current)20ASwitching Voltage277VAC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)2.4 VDCOperate Time20msRelease Time10msFeaturesInsulation - Class F, Sealed - FullyMounting TypeThrough HoleTermination StylePC Pin		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 33.3mA Coil Voltage 24VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 20A Switching Voltage 277VAC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 20ms Release Time 10ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Package	-
Coil TypeNon LatchingCoil Current33.3mACoil Voltage24VDCContact FormSPDT (1 Form C)Contact Rating (Current)20ASwitching Voltage277VAC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)2.4 VDCOperate Time20msRelease Time10msFeaturesInsulation - Class F, Sealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Series	JT-N
Coil Current Coil Voltage 24VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 20A Switching Voltage 277VAC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 20ms Release Time 10ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Relay Type	General Purpose
Coil Voltage 24VDC  Contact Form SPDT (1 Form C)  Contact Rating (Current) 20A  Switching Voltage 277VAC - Max  Turn On Voltage (Max) 18 VDC  Turn Off Voltage (Min) 2.4 VDC  Operate Time 20ms  Release Time 10ms  Features Insulation - Class F, Sealed - Fully  Mounting Type Through Hole  Termination Style PC Pin	Coil Type	Non Latching
Contact Form SPDT (1 Form C)  Contact Rating (Current)  Switching Voltage  277VAC - Max  Turn On Voltage (Max)  18 VDC  Turn Off Voltage (Min)  2.4 VDC  Operate Time  20ms  Release Time  10ms  Features  Insulation - Class F, Sealed - Fully  Mounting Type  Through Hole  Termination Style	Coil Current	33.3mA
Contact Rating (Current)  Switching Voltage  277VAC - Max  Turn On Voltage (Max)  18 VDC  Turn Off Voltage (Min)  2.4 VDC  Operate Time  20ms  Release Time  10ms  Features  Insulation - Class F, Sealed - Fully  Mounting Type  Through Hole  Termination Style	Coil Voltage	24VDC
Switching Voltage  Turn On Voltage (Max)  18 VDC  Turn Off Voltage (Min)  Operate Time  20ms  Release Time  10ms  Features  Insulation - Class F, Sealed - Fully  Mounting Type  Through Hole  Termination Style  277VAC - Max  18 VDC  2.4 VDC  10ms  For a company to the company	Contact Form	SPDT (1 Form C)
Turn On Voltage (Max)  18 VDC  Turn Off Voltage (Min)  2.4 VDC  Operate Time  20ms  Release Time  10ms  Features  Insulation - Class F, Sealed - Fully  Mounting Type  Through Hole  Termination Style  PC Pin	Contact Rating (Current)	20A
Turn Off Voltage (Min)  Operate Time  20ms  Release Time  10ms  Features  Insulation - Class F, Sealed - Fully  Mounting Type  Through Hole  Termination Style  PC Pin	Switching Voltage	277VAC - Max
Operate Time20msRelease Time10msFeaturesInsulation - Class F, Sealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Turn On Voltage (Max)	18 VDC
Release Time 10ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	2.4 VDC
Features Insulation - Class F, Sealed - Fully  Mounting Type Through Hole  Termination Style PC Pin	Operate Time	20ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	10ms
Termination Style PC Pin	Features	Insulation - Class F, Sealed - Fully
	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
		Report errors?

#### JTN1S-PA-F-DC24V Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### JTN1S-PA-F-DC24V Payment Methods



















### JTN1S-PA-F-DC24V Shipping Methods













If you have any question about JTN1S-PA-F-DC24V, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com