

JTNV1AS-PA-F-DC15V

JTNV1AS-PA-F-DC15V Information



For Reference Only

Part Number JTNV1AS-PA-F-DC15V

Manufacturer Panasonic Electric Works

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE SPST 30A 15V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









JTNV1AS-PA-F-DC15V Specifications

Manufacturer Part Number Manufacturer Panasonic Electric Works Relays Power Relays, Over 2 Amps Package - Series JT-N Relay Type General Purpose Coil Type Non Latching Coil Current 53.3mA Coil Voltage 15VDC Contact Form SPST-NO (1 Form A) Switching Voltage 277VAC - Max Turn On Voltage (Max) Turn Off Voltage (Min) 1.5 VDC		
Category Relays Power Relays, Over 2 Amps Package - Series JT-N Relay Type General Purpose Coil Type Non Latching Coil Current 53.3mA Coil Voltage 15VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 30A Switching Voltage 277VAC - Max Turn On Voltage (Max) 11.25 VDC Turn Off Voltage (Min) 1.5 VDC	Manufacturer Part Number	JTNV1AS-PA-F-DC15V
Power Relays, Over 2 Amps Package Series JT-N Relay Type General Purpose Coil Type Non Latching Coil Current 53.3mA Coil Voltage 15VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 30A Switching Voltage 277VAC - Max Turn On Voltage (Max) Turn Off Voltage (Min) 1.5 VDC	Manufacturer	Panasonic Electric Works
Package - Series JT-N Relay Type General Purpose Coil Type Non Latching Coil Current 53.3mA Coil Voltage 15VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 30A Switching Voltage 277VAC - Max Turn On Voltage (Max) 11.25 VDC Turn Off Voltage (Min) 1.5 VDC	Category	Relays
Series JT-N Relay Type General Purpose Coil Type Non Latching Coil Current 53.3mA Coil Voltage 15VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 30A Switching Voltage 277VAC - Max Turn On Voltage (Max) 11.25 VDC Turn Off Voltage (Min) 1.5 VDC		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 53.3mA Coil Voltage 15VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 30A Switching Voltage 277VAC - Max Turn On Voltage (Max) 11.25 VDC Turn Off Voltage (Min) 1.5 VDC	Package	-
Coil Type Non Latching Coil Current 53.3mA Coil Voltage 15VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 30A Switching Voltage 277VAC - Max Turn On Voltage (Max) 11.25 VDC Turn Off Voltage (Min) 1.5 VDC	Series	JT-N
Coil Current 53.3mA Coil Voltage 15VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 30A Switching Voltage 277VAC - Max Turn On Voltage (Max) 11.25 VDC Turn Off Voltage (Min) 1.5 VDC	Relay Type	General Purpose
Coil Voltage 15VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 30A Switching Voltage 277VAC - Max Turn On Voltage (Max) 11.25 VDC Turn Off Voltage (Min) 1.5 VDC	Coil Type	Non Latching
Contact Form SPST-NO (1 Form A) Contact Rating (Current) 30A Switching Voltage 277VAC - Max Turn On Voltage (Max) 11.25 VDC Turn Off Voltage (Min) 1.5 VDC	Coil Current	53.3mA
Contact Rating (Current) Switching Voltage 277VAC - Max Turn On Voltage (Max) 11.25 VDC Turn Off Voltage (Min) 1.5 VDC	Coil Voltage	15VDC
Switching Voltage 277VAC - Max Turn On Voltage (Max) 11.25 VDC Turn Off Voltage (Min) 1.5 VDC	Contact Form	SPST-NO (1 Form A)
Turn On Voltage (Max) 11.25 VDC Turn Off Voltage (Min) 1.5 VDC	Contact Rating (Current)	30A
Turn Off Voltage (Min) 1.5 VDC	Switching Voltage	277VAC - Max
	Turn On Voltage (Max)	11.25 VDC
	Turn Off Voltage (Min)	1.5 VDC
Operate Time 20ms	Operate Time	20ms
Release Time 10ms	Release Time	10ms
Features Insulation - Class F, Sealed - Fully	Features	Insulation - Class F, Sealed - Fully
Mounting Type Through Hole	Mounting Type	Through Hole
Termination Style PC Pin	Termination Style	PC Pin
Report errors?		Report errors?

JTNV1AS-PA-F-DC15V Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

JTNV1AS-PA-F-DC15V Payment Methods

































If you have any question about JTNV1AS-PA-F-DC15V, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com