

JTNV1AS-PA-F-DC6V

JTNV1AS-PA-F-DC6V Information



For Reference Only

Part Number JTNV1AS-PA-F-DC6V

Manufacturer Panasonic Electric Works

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE SPST 30A 6V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









JTNV1AS-PA-F-DC6V Specifications

Manufacturer Part NumberJTNV1AS-PA-F-DC6VManufacturerPanasonic Electric WorksCategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesJT-NRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current133.3mACoil Voltage6VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)30ASwitching Voltage277VAC - MaxTurn On Voltage (Max)4.5 VDCTurn Off Voltage (Min)0.6 VDCOperate Time20msRelease Time10msFeaturesInsulation - Class F, Sealed - FullyMounting TypeThrough HoleTermination StylePC Pin		
CategoryRelaysPackage-SeriesJT-NRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current133.3mACoil Voltage6VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)30ASwitching Voltage277VAC - MaxTurn On Voltage (Max)4.5 VDCTurn Off Voltage (Min)0.6 VDCOperate Time20msRelease Time10msFeaturesInsulation - Class F, Sealed - FullyMounting TypeThrough Hole	Manufacturer Part Number	JTNV1AS-PA-F-DC6V
Package - Series JT-N Relay Type General Purpose Coil Type Non Latching Coil Current 133.3mA Coil Voltage 6VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 30A Switching Voltage 277VAC - Max Turn On Voltage (Max) 4.5 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 20ms Release Time 10ms Features Insulation - Class F, Sealed - Fully Mounting Type Trous Commended to the series of t	Manufacturer	Panasonic Electric Works
Package JT-N Relay Type General Purpose Coil Type Non Latching Coil Current 133.3mA Coil Voltage 6VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 30A Switching Voltage 277VAC - Max Turn On Voltage (Max) 4.5 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 20ms Release Time 10ms Features Insulation - Class F, Sealed - Fully Mounting Type Trhrough Hole	Category	Relays
SeriesJT-NRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current133.3mACoil Voltage6VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)30ASwitching Voltage277VAC - MaxTurn On Voltage (Max)4.5 VDCTurn Off Voltage (Min)0.6 VDCOperate Time20msRelease Time10msFeaturesInsulation - Class F, Sealed - FullyMounting TypeThrough Hole		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 133.3mA Coil Voltage 6VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 30A Switching Voltage 277VAC - Max Turn On Voltage (Max) 4.5 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 20ms Release Time 10ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole	Package	-
Coil Type Non Latching Coil Current 133.3mA Coil Voltage 6VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 30A Switching Voltage 277VAC - Max Turn On Voltage (Max) 4.5 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 20ms Release Time 10ms Features Insulation - Class F, Sealed - Fully Mounting Type Trhrough Hole	Series	JT-N
Coil Current 133.3mA Coil Voltage 6VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 30A Switching Voltage 277VAC - Max Turn On Voltage (Max) 4.5 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 20ms Release Time 10ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole	Relay Type	General Purpose
Coil Voltage 6VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 30A Switching Voltage 277VAC - Max Turn On Voltage (Max) 4.5 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 20ms Release Time 10ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole	Coil Type	Non Latching
Contact Form SPST-NO (1 Form A) Contact Rating (Current) 30A Switching Voltage 277VAC - Max Turn On Voltage (Max) 4.5 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 20ms Release Time 10ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole	Coil Current	133.3mA
Contact Rating (Current) Switching Voltage 277VAC - Max Turn On Voltage (Max) 4.5 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 20ms Release Time 10ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole	Coil Voltage	6VDC
Switching Voltage 277VAC - Max Turn On Voltage (Max) 4.5 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 20ms Release Time 10ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole	Contact Form	SPST-NO (1 Form A)
Turn On Voltage (Max) 4.5 VDC Turn Off Voltage (Min) Operate Time 20ms Release Time 10ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole	Contact Rating (Current)	30A
Turn Off Voltage (Min) Operate Time 20ms Release Time 10ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole	Switching Voltage	277VAC - Max
Operate Time 20ms Release Time 10ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole	Turn On Voltage (Max)	4.5 VDC
Release Time 10ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole	Turn Off Voltage (Min)	0.6 VDC
Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole	Operate Time	20ms
Mounting Type Through Hole	Release Time	10ms
	Features	Insulation - Class F, Sealed - Fully
Termination Style PC Pin	Mounting Type	Through Hole
	Termination Style	PC Pin
Report errors?		Report errors?

JTNV1AS-PA-F-DC6V Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

JTNV1AS-PA-F-DC6V Payment Methods



















JTNV1AS-PA-F-DC6V Shipping Methods













If you have any question about JTNV1AS-PA-F-DC6V, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com