



JTV1AS-TMP-12V Information



For Reference Only

Part Number JTV1AS-TMP-12V

Manufacturer Panasonic Electric Works

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE SPST 30A 12V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









JTV1AS-TMP-12V Specifications

Manufacturer Part Number JTVIAS-TMP-12V Manufacturer Panasonic Electric Works Category Relays Power Relays, Over 2 Amps Package - Series JT-V Relay Type General Purpose Coil Type Non Latching Coil Current 83.3mA Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 30A Switching Voltage 277VAC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 15ms Release Time 10ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.250" (6.3mm) Report errors?		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesJT-VRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current83.3mACoil Voltage12VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)30ASwitching Voltage277VAC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)1.2 VDCOperate Time15msRelease Time10msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin, Quick Connect - 0.250" (6.3mm)	Manufacturer Part Number	JTV1AS-TMP-12V
Package - Series JT-V Relay Type General Purpose Coil Type Non Latching Coil Current 83.3mA Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 30A Switching Voltage 277VAC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 15ms Release Time 10ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.250" (6.3mm)	Manufacturer	Panasonic Electric Works
Package-SeriesJT-VRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current83.3mACoil Voltage12VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)30ASwitching Voltage277VAC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)1.2 VDCOperate Time15msRelease Time10msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin, Quick Connect - 0.250" (6.3mm)	Category	Relays
Series JT-V Relay Type General Purpose Coil Type Non Latching Coil Current 83.3mA Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 30A Switching Voltage 277VAC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 15ms Release Time 10ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.250" (6.3mm)		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 83.3mA Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 30A Switching Voltage 277VAC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 15ms Release Time 10ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.250" (6.3mm)	Package	-
Coil TypeNon LatchingCoil Current83.3mACoil Voltage12VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)30ASwitching Voltage277VAC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)1.2 VDCOperate Time15msRelease Time10msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin, Quick Connect - 0.250" (6.3mm)	Series	JT-V
Coil Current Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 30A Switching Voltage 277VAC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 15ms Release Time 10ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.250" (6.3mm)	Relay Type	General Purpose
Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 30A Switching Voltage 277VAC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 15ms Release Time 10ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.250" (6.3mm)	Coil Type	Non Latching
Contact Form SPST-NO (1 Form A) Contact Rating (Current) 30A Switching Voltage 277VAC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 15ms Release Time 10ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.250" (6.3mm)	Coil Current	83.3mA
Contact Rating (Current) Switching Voltage 277VAC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 15ms Release Time 10ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.250" (6.3mm)	Coil Voltage	12VDC
Switching Voltage Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 15ms Release Time 10ms Features Sealed - Fully Mounting Type Through Hole Termination Style 277VAC - Max 9 VDC 1.2 VDC 1.2 VDC 1.3 Max 1.2 VDC 1.5 ms 1.5 ms 1.6 ms 1.7 ms 1.8 ms 1	Contact Form	SPST-NO (1 Form A)
Turn On Voltage (Max) 7 Urn Off Voltage (Min) 1.2 VDC Operate Time 15ms Release Time 10ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.250" (6.3mm)	Contact Rating (Current)	30A
Turn Off Voltage (Min) 1.2 VDC Operate Time 15ms Release Time 10ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.250" (6.3mm)	Switching Voltage	277VAC - Max
Operate Time 15ms Release Time 10ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.250" (6.3mm)	Turn On Voltage (Max)	9 VDC
Release Time 10ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.250" (6.3mm)	Turn Off Voltage (Min)	1.2 VDC
Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.250" (6.3mm)	Operate Time	15ms
Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.250" (6.3mm)	Release Time	10ms
Termination Style PC Pin, Quick Connect - 0.250" (6.3mm)	Features	Sealed - Fully
·	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin, Quick Connect - 0.250" (6.3mm)
		Report errors?

JTV1AS-TMP-12V Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

JTV1AS-TMP-12V Payment Methods



















JTV1AS-TMP-12V Shipping Methods













If you have any question about JTV1AS-TMP-12V, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com