

JV1AP-100V Information



For Reference Only

Part Number JV1AP-100V

Manufacturer Panasonic Electric Works

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE SPST 16A 100V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









JV1AP-100V Specifications

Manufacturer Part NumberJV1AP-100VManufacturerPanasonic Electric WorksCategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesJVRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current6mACoil Voltage100VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)16ASwitching Voltage125VAC - MaxTurn On Voltage (Max)48 VDCTurn Off Voltage (Min)3 VDCOperate Time5msRelease Time4msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin		
CategoryRelaysPackage-SeriesJVRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current6mACoil Voltage100VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)16ASwitching Voltage125VAC - MaxTurn On Voltage (Max)48 VDCTurn Off Voltage (Min)3 VDCOperate Time5msRelease Time4msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	JV1AP-100V
Package - Series JV Relay Type General Purpose Coil Type Non Latching Coil Current 6mA Coil Voltage 100VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 125VAC - Max Turn On Voltage (Max) 48 VDC Turn Off Voltage (Min) 3 VDC Operate Time 5ms Release Time 4ms Features Sealed - Fully Mounting Type Through Hole Termination Style Purpose	Manufacturer	Panasonic Electric Works
Package-SeriesJVRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current6mACoil Voltage100VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)16ASwitching Voltage125VAC - MaxTurn On Voltage (Max)48 VDCTurn Off Voltage (Min)3 VDCOperate Time5msRelease Time4msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Category	Relays
SeriesJVRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current6mACoil Voltage100VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)16ASwitching Voltage125VAC - MaxTurn On Voltage (Max)48 VDCTurn Off Voltage (Min)3 VDCOperate Time5msRelease Time4msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 6mA Coil Voltage 100VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 125VAC - Max Turn On Voltage (Max) 48 VDC Turn Off Voltage (Min) 3 VDC Operate Time 5ms Release Time 4ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Package	-
Coil TypeNon LatchingCoil Current6mACoil Voltage100VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)16ASwitching Voltage125VAC - MaxTurn On Voltage (Max)48 VDCTurn Off Voltage (Min)3 VDCOperate Time5msRelease Time4msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Series	JV
Coil Current Coil Voltage 100VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 125VAC - Max Turn On Voltage (Max) 48 VDC Turn Off Voltage (Min) 3 VDC Operate Time 5ms Release Time 4ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Relay Type	General Purpose
Coil Voltage 100VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 125VAC - Max Turn On Voltage (Max) 48 VDC Turn Off Voltage (Min) 3 VDC Operate Time 5ms Release Time 4ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Coil Type	Non Latching
Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 125 VAC - Max Turn On Voltage (Max) 48 VDC Turn Off Voltage (Min) 3 VDC Operate Time 5ms Release Time 4ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Coil Current	6mA
Contact Rating (Current) Switching Voltage 125VAC - Max Turn On Voltage (Max) 48 VDC Turn Off Voltage (Min) 3 VDC Operate Time 5ms Release Time 4ms Features Sealed - Fully Mounting Type Through Hole Termination Style	Coil Voltage	100VDC
Switching Voltage Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time Sms Release Time 4ms Features Sealed - Fully Mounting Type Through Hole Termination Style 125VAC - Max 48 VDC 3 VDC 3 VDC 5ms 4ms Fentures Pentures Sealed - Fully Through Hole PC Pin	Contact Form	SPST-NO (1 Form A)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time Sms Release Time 4ms Features Sealed - Fully Mounting Type Through Hole Termination Style 48 VDC 5ms Sex Sex Forms Forms Sex Freatures Freature	Contact Rating (Current)	16A
Turn Off Voltage (Min) Operate Time Sms Release Time 4ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Switching Voltage	125VAC - Max
Operate Time5msRelease Time4msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Turn On Voltage (Max)	48 VDC
Release Time 4ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	3 VDC
Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Operate Time	5ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	4ms
Termination Style PC Pin	Features	Sealed - Fully
•	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
		Report errors?

JV1AP-100V Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

JV1AP-100V Payment Methods



















JV1AP-100V Shipping Methods













If you have any question about JV1AP-100V, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com