

JVN1A-4.5V Information



For Reference Only

Part Number JVN1A-4.5V

Manufacturer Panasonic Electric Works

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE SPST 16A 4.5V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









JVN1A-4.5V Specifications

Manufacturer Part NumberJVN1A-4.5VManufacturerPanasonic Electric WorksCategoryRelaysPackage-SeriesJV-NRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current44.4mACoil Voltage4.5VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)16ASwitching Voltage277VAC, 30VDC - MaxTurn On Voltage (Max)3.38 VDCTurn Off Voltage (Min)0.23 VDCOperate Time12msRelease Time5msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin		
CategoryRelaysPackage-SeriesJV-NRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current44.4mACoil Voltage4.5VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)16ASwitching Voltage277VAC, 30VDC - MaxTurn On Voltage (Max)3.38 VDCTurn Off Voltage (Min)0.23 VDCOperate Time12msRelease Time5msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	JVN1A-4.5V
Package - Series JV-N Relay Type General Purpose Coil Type Non Latching Coil Current 44.4mA Coil Voltage 4.5VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 277VAC, 30VDC - Max Turn On Voltage (Max) 3.38 VDC Turn Off Voltage (Min) 0.23 VDC Operate Time 12ms Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style Purpose	Manufacturer	Panasonic Electric Works
Package-SeriesJV-NRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current44.4mACoil Voltage4.5VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)16ASwitching Voltage277VAC, 30VDC - MaxTurn On Voltage (Max)3.38 VDCTurn Off Voltage (Min)0.23 VDCOperate Time12msRelease Time5msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Category	Relays
SeriesJV-NRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current44.4mACoil Voltage4.5VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)16ASwitching Voltage277VAC, 30VDC - MaxTurn On Voltage (Max)3.38 VDCTurn Off Voltage (Min)0.23 VDCOperate Time12msRelease Time5msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 44.4mA Coil Voltage 4.5VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 277VAC, 30VDC - Max Turn On Voltage (Max) 3.38 VDC Turn Off Voltage (Min) 0.23 VDC Operate Time 12ms Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Package	-
Coil TypeNon LatchingCoil Current44.4mACoil Voltage4.5VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)16ASwitching Voltage277VAC, 30VDC - MaxTurn On Voltage (Max)3.38 VDCTurn Off Voltage (Min)0.23 VDCOperate Time12msRelease Time5msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Series	JV-N
Coil Current 44.4mA Coil Voltage 4.5VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 277VAC, 30VDC - Max Turn On Voltage (Max) 3.38 VDC Turn Off Voltage (Min) 0.23 VDC Operate Time 12ms Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Relay Type	General Purpose
Coil Voltage 4.5VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 277VAC, 30VDC - Max Turn On Voltage (Max) 3.38 VDC Turn Off Voltage (Min) 0.23 VDC Operate Time 12ms Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Coil Type	Non Latching
Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 277VAC, 30VDC - Max Turn On Voltage (Max) 3.38 VDC Turn Off Voltage (Min) 0.23 VDC Operate Time 12ms Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Coil Current	44.4mA
Contact Rating (Current) Switching Voltage 277VAC, 30VDC - Max Turn On Voltage (Max) 3.38 VDC Turn Off Voltage (Min) 0.23 VDC Operate Time 12ms Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style	Coil Voltage	4.5VDC
Switching Voltage 277VAC, 30VDC - Max Turn On Voltage (Max) 3.38 VDC Turn Off Voltage (Min) 0.23 VDC Operate Time 12ms Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Contact Form	SPST-NO (1 Form A)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 12ms Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style 3.38 VDC 0.23 VDC 0.26 VDC 12ms Foms Poms Po	Contact Rating (Current)	16A
Turn Off Voltage (Min) Operate Time 12ms Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Switching Voltage	277VAC, 30VDC - Max
Operate Time12msRelease Time5msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Turn On Voltage (Max)	3.38 VDC
Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	0.23 VDC
Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Operate Time	12ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	5ms
Termination Style PC Pin	Features	Sealed - Fully
•	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
		Report errors?

JVN1A-4.5V Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

JVN1A-4.5V Payment Methods



















JVN1A-4.5V Shipping Methods













If you have any question about JVN1A-4.5V, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com