



JVN1AF-12V-F Information

Heisener.com

Part Number JVN1AF-12V-F

Manufacturer Panasonic Electric Works

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE SPST 16A 12V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com

Request a Quote



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









JVN1AF-12V-F Specifications

Manufacturer Part NumberJVN1AF-12V-FManufacturerPanasonic Electric WorksCategoryRelaysPackage-SeriesJV-NRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current16.7mACoil Voltage12VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)16ASwitching Voltage277VAC, 30VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)0.6 VDCOperate Time12msRelease Time5msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesJV-NRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current16.7mACoil Voltage12VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)16ASwitching Voltage277VAC, 30VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)0.6 VDCOperate Time12msRelease Time5msFeaturesSealed - Flux ProtectionMounting TypeThrough Hole	Manufacturer Part Number	JVN1AF-12V-F
Package - Series JV-N Relay Type General Purpose Coil Type Non Latching Coil Current 16.7mA Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 277VAC, 30VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 12ms Release Time 5ms Features Sealed - Flux Protection Mounting Type Trons SPST-NO (1 Form SPST-NO	Manufacturer	Panasonic Electric Works
Package-SeriesJV-NRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current16.7mACoil Voltage12VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)16ASwitching Voltage277VAC, 30VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)0.6 VDCOperate Time12msRelease Time5msFeaturesSealed - Flux ProtectionMounting TypeThrough Hole	Category	Relays
Series JV-N Relay Type General Purpose Coil Type Non Latching Coil Current 16.7mA Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 277VAC, 30VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 12ms Release Time 5ms Features Sealed - Flux Protection Mounting Type Trhrough Hole		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 16.7mA Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 277VAC, 30VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 12ms Release Time 5ms Features Sealed - Flux Protection Mounting Type Through Hole	Package	-
Coil Type Non Latching Coil Current 16.7mA Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 277VAC, 30VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 12ms Release Time 5ms Features Sealed - Flux Protection Mounting Type Through Hole	Series	JV-N
Coil Current 16.7mA Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 277VAC, 30VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 12ms Release Time 5ms Features Sealed - Flux Protection Mounting Type Through Hole	Relay Type	General Purpose
Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 277VAC, 30VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 12ms Release Time 5ms Features Sealed - Flux Protection Mounting Type Through Hole	Coil Type	Non Latching
Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 277VAC, 30VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 12ms Release Time 5ms Features Sealed - Flux Protection Mounting Type Through Hole	Coil Current	16.7mA
Contact Rating (Current) Switching Voltage 277VAC, 30VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 12ms Release Time 5ms Features Sealed - Flux Protection Mounting Type Through Hole	Coil Voltage	12VDC
Switching Voltage 277VAC, 30VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 12ms Release Time 5ms Features Sealed - Flux Protection Mounting Type Through Hole	Contact Form	SPST-NO (1 Form A)
Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 12ms Release Time 5ms Features Sealed - Flux Protection Mounting Type Through Hole	Contact Rating (Current)	16A
Turn Off Voltage (Min) Operate Time 12ms Release Time 5ms Features Sealed - Flux Protection Mounting Type Through Hole	Switching Voltage	277VAC, 30VDC - Max
Operate Time 12ms Release Time 5ms Features Sealed - Flux Protection Mounting Type Through Hole	Turn On Voltage (Max)	9 VDC
Release Time 5ms Features Sealed - Flux Protection Mounting Type Through Hole	Turn Off Voltage (Min)	0.6 VDC
Features Sealed - Flux Protection Mounting Type Through Hole	Operate Time	12ms
Mounting Type Through Hole	Release Time	5ms
	Features	Sealed - Flux Protection
Termination Style PC Pin	Mounting Type	Through Hole
	Termination Style	PC Pin
Report errors?		Report errors?

JVN1AF-12V-F Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

JVN1AF-12V-F Payment Methods



















JVN1AF-12V-F Shipping Methods













If you have any question about JVN1AF-12V-F, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com