



### **JW1FSN-DC6V Information**



For Reference Only

Part Number JW1FSN-DC6V

Manufacturer Panasonic Electric Works

**Category** Relays

Power Relays, Over 2 Amps

**Description** RELAY GEN PURPOSE SPDT 10A 6V

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **JW1FSN-DC6V Specifications**

Manufacturer Part NumberJW1FSN-DC6VManufacturerPanasonic Electric WorksCategoryRelaysPackage-SeriesJWRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current88mACoil Voltage6VDCContact FormSPDT (1 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 30VDC - MaxTurn On Voltage (Max)4.2 VDCTurn Off Voltage (Min)0.6 VDCOperate Time15msRelease Time5msFeaturesSealed - Fully		
CategoryRelaysPackage-SeriesJWRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current88mACoil Voltage6VDCContact FormSPDT (1 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 30VDC - MaxTurn On Voltage (Max)4.2 VDCTurn Off Voltage (Min)0.6 VDCOperate Time15msRelease Time5ms	Manufacturer Part Number	JW1FSN-DC6V
Package - Series JW Relay Type General Purpose Coil Type Non Latching Coil Current 88mA Coil Voltage Contact Form SPDT (1 Form C) Contact Rating (Current) Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time Release Time Poseer Relays, Over 2 Amps	Manufacturer	Panasonic Electric Works
Package - Series JW Relay Type General Purpose Coil Type Non Latching Coil Current 88mA Coil Voltage 6VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 10A Switching Voltage Max) 4.2 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 15ms Release Time 55ms	Category	Relays
Series JW Relay Type General Purpose Coil Type Non Latching Coil Current 88mA Coil Voltage 6VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 15ms Release Time 5ms		Power Relays, Over 2 Amps
Relay Type General Purpose Non Latching Coil Type Non Latching Coil Current 88mA Coil Voltage 6VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 15ms Release Time 5ms	Package	-
Coil TypeNon LatchingCoil Current88mACoil Voltage6VDCContact FormSPDT (1 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 30VDC - MaxTurn On Voltage (Max)4.2 VDCTurn Off Voltage (Min)0.6 VDCOperate Time15msRelease Time5ms	Series	JW
Coil Current 88mA  Coil Voltage 6VDC  Contact Form SPDT (1 Form C)  Contact Rating (Current) 10A  Switching Voltage 250VAC, 30VDC - Max  Turn On Voltage (Max) 4.2 VDC  Turn Off Voltage (Min) 0.6 VDC  Operate Time 15ms  Release Time 5ms	Relay Type	General Purpose
Coil Voltage 6VDC  Contact Form SPDT (1 Form C)  Contact Rating (Current) 10A  Switching Voltage 250VAC, 30VDC - Max  Turn On Voltage (Max) 4.2 VDC  Turn Off Voltage (Min) 0.6 VDC  Operate Time 15ms  Release Time 5ms	Coil Type	Non Latching
Contact Form SPDT (1 Form C)  Contact Rating (Current)  Switching Voltage  250VAC, 30VDC - Max  Turn On Voltage (Max)  4.2 VDC  Turn Off Voltage (Min)  0.6 VDC  Operate Time  15ms  Release Time  5ms	Coil Current	88mA
Contact Rating (Current)  Switching Voltage  250VAC, 30VDC - Max  Turn On Voltage (Max)  4.2 VDC  Turn Off Voltage (Min)  0.6 VDC  Operate Time  15ms  Release Time  5ms	Coil Voltage	6VDC
Switching Voltage 250VAC, 30VDC - Max  Turn On Voltage (Max) 4.2 VDC  Turn Off Voltage (Min) 0.6 VDC  Operate Time 15ms  Release Time 5ms	Contact Form	SPDT (1 Form C)
Turn On Voltage (Max)  4.2 VDC  Turn Off Voltage (Min)  Operate Time  15ms  Release Time  5ms	Contact Rating (Current)	10A
Turn Off Voltage (Min)  Operate Time  15ms  Release Time  5ms	Switching Voltage	250VAC, 30VDC - Max
Operate Time 15ms Release Time 5ms	Turn On Voltage (Max)	4.2 VDC
Release Time 5ms	Turn Off Voltage (Min)	0.6 VDC
	Operate Time	15ms
Features Sealed - Fully	Release Time	5ms
	Features	Sealed - Fully
Mounting Type Through Hole	Mounting Type	Through Hole
Termination Style PC Pin	Termination Style	PC Pin
Report errors?		Report errors?

#### **JW1FSN-DC6V Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **JW1FSN-DC6V Payment Methods**





















## **JW1FSN-DC6V Shipping Methods**













If you have any question about JW1FSN-DC6V, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com