



JW1FSN-DC6V Information



For Reference Only

Part Number JW1FSN-DC6V

Manufacturer Panasonic Electric Works

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE SPDT 10A 6V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









JW1FSN-DC6V Specifications

| Manufacturer Part NumberJW1FSN-DC6VManufacturerPanasonic Electric WorksCategoryRelaysPackage-SeriesJWRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current88mACoil Voltage6VDCContact FormSPDT (1 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 30VDC - MaxTurn On Voltage (Max)4.2 VDCTurn Off Voltage (Min)0.6 VDCOperate Time15msRelease Time5msFeaturesSealed - Fully | | |
|---|--------------------------|---------------------------|
| CategoryRelaysPackage-SeriesJWRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current88mACoil Voltage6VDCContact FormSPDT (1 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 30VDC - MaxTurn On Voltage (Max)4.2 VDCTurn Off Voltage (Min)0.6 VDCOperate Time15msRelease Time5ms | Manufacturer Part Number | JW1FSN-DC6V |
| Package - Series JW Relay Type General Purpose Coil Type Non Latching Coil Current 88mA Coil Voltage Contact Form SPDT (1 Form C) Contact Rating (Current) Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time Release Time Poseer Relays, Over 2 Amps | Manufacturer | Panasonic Electric Works |
| Package - Series JW Relay Type General Purpose Coil Type Non Latching Coil Current 88mA Coil Voltage 6VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 10A Switching Voltage Max) 4.2 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 15ms Release Time 55ms | Category | Relays |
| Series JW Relay Type General Purpose Coil Type Non Latching Coil Current 88mA Coil Voltage 6VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 15ms Release Time 5ms | | Power Relays, Over 2 Amps |
| Relay Type General Purpose Non Latching Coil Type Non Latching Coil Current 88mA Coil Voltage 6VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 15ms Release Time 5ms | Package | - |
| Coil TypeNon LatchingCoil Current88mACoil Voltage6VDCContact FormSPDT (1 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 30VDC - MaxTurn On Voltage (Max)4.2 VDCTurn Off Voltage (Min)0.6 VDCOperate Time15msRelease Time5ms | Series | JW |
| Coil Current 88mA Coil Voltage 6VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 15ms Release Time 5ms | Relay Type | General Purpose |
| Coil Voltage 6VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 15ms Release Time 5ms | Coil Type | Non Latching |
| Contact Form SPDT (1 Form C) Contact Rating (Current) Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 15ms Release Time 5ms | Coil Current | 88mA |
| Contact Rating (Current) Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 15ms Release Time 5ms | Coil Voltage | 6VDC |
| Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 15ms Release Time 5ms | Contact Form | SPDT (1 Form C) |
| Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) Operate Time 15ms Release Time 5ms | Contact Rating (Current) | 10A |
| Turn Off Voltage (Min) Operate Time 15ms Release Time 5ms | Switching Voltage | 250VAC, 30VDC - Max |
| Operate Time 15ms Release Time 5ms | Turn On Voltage (Max) | 4.2 VDC |
| Release Time 5ms | Turn Off Voltage (Min) | 0.6 VDC |
| | Operate Time | 15ms |
| Features Sealed - Fully | Release Time | 5ms |
| | Features | Sealed - Fully |
| Mounting Type Through Hole | Mounting Type | Through Hole |
| Termination Style PC Pin | Termination Style | PC Pin |
| Report errors? | | Report errors? |

JW1FSN-DC6V Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

JW1FSN-DC6V Payment Methods





















JW1FSN-DC6V Shipping Methods













If you have any question about JW1FSN-DC6V, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com