



JWS1005/R Information

Heisener.com

Part Number JWS1005/R

Manufacturer TDK-Lambda Americas Inc.

Power Supplies - External/Internal (Off-Board) Category

AC DC Converters

Description AC/DC CONVERTER 5V 100W

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









JWS1005/R Specifications

Manufacturer Part Number JWS1005/R Manufacturer TDK-Lambda Americas Inc. Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series JWS Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 20A Power (Watts) 100W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 75% Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 7.40" L x 3.62" W x 1.97" H (188.0mm x 91.9mm x 50.0mm)			
Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series JWS Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 20A Power (Watts) 100W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 75% Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 7.40° L x 3.62° W x 1.97° H (188.0mm x 91.9mm x 50.0mm)	Manufacturer Part Number	JWS1005/R	
Package - Series JWS Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 20A Power (Watts) 100W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 75% Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 7.40" L x 3.62" W x 1.97" H (188.0mm x 91.9mm x 50.0mm)	Manufacturer	TDK-Lambda Americas Inc.	
Package - Series JWS Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 20A Power (Watts) 100W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 75% Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 7.40" L x 3.62" W x 1.97" H (188.0mm x 91.9mm x 50.0mm)	Category	Power Supplies - External/Internal (Off-Board)	
Series JWS Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 20A Power (Watts) 100W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 75% Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 7.40" L x 3.62" W x 1.97" H (188.0mm x 91.9mm x 50.0mm)		AC DC Converters	
Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 20A Power (Watts) 100W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 75% Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 7.40" L x 3.62" W x 1.97" H (188.0mm x 91.9mm x 50.0mm)	Package	-	
Number of Outputs Voltage - Input 85 ~ 265 VAC Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 75% Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Remote Sense, Universal Input Mounting Type Size / Dimension 7.40" L x 3.62" W x 1.97" H (188.0mm x 91.9mm x 50.0mm)	Series	JWS	
Voltage - Input 85 ~ 265 VAC Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 20A Power (Watts) 100W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 75% Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 7.40" L x 3.62" W x 1.97" H (188.0mm x 91.9mm x 50.0mm)	Туре	Enclosed	
Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 20A Power (Watts) 100W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 75% Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 7.40" L x 3.62" W x 1.97" H (188.0mm x 91.9mm x 50.0mm)	Number of Outputs	1	
Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 7.40" L x 3.62" W x 1.97" H (188.0mm x 91.9mm x 50.0mm)	Voltage - Input	85 ~ 265 VAC	
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 75% Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 7.40" L x 3.62" W x 1.97" H (188.0mm x 91.9mm x 50.0mm)	Voltage - Output 1	5V	
Voltage - Output 4 Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 75% Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 7.40" L x 3.62" W x 1.97" H (188.0mm x 91.9mm x 50.0mm)	Voltage - Output 2	-	
Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 75% Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 7.40" L x 3.62" W x 1.97" H (188.0mm x 91.9mm x 50.0mm)	Voltage - Output 3	-	
Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 75% Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 7.40" L x 3.62" W x 1.97" H (188.0mm x 91.9mm x 50.0mm)	Voltage - Output 4	-	
$ \begin{array}{cccccccccccccccccccccccccccccccccccc$	Current - Output (Max)	20A	
Voltage - Isolation 3kV (3000V) Efficiency 75% Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 7.40" L x 3.62" W x 1.97" H (188.0mm x 91.9mm x 50.0mm)	Power (Watts)	100W	
Efficiency 75% Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 7.40" L x 3.62" W x 1.97" H (188.0mm x 91.9mm x 50.0mm)	Applications	ITE (Commercial)	
Operating Temperature -10°C ~ 60°C (With Derating) Adjustable Output, DC Input Capable, PFC, Remote Sense, Universal Input Mounting Type Chassis Mount 7.40" L x 3.62" W x 1.97" H (188.0mm x 91.9mm x 50.0mm)	Voltage - Isolation	3kV (3000V)	
Features Adjustable Output, DC Input Capable, PFC, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 7.40" L x 3.62" W x 1.97" H (188.0mm x 91.9mm x 50.0mm)	Efficiency	75%	
Mounting Type Chassis Mount Size / Dimension 7.40" L x 3.62" W x 1.97" H (188.0mm x 91.9mm x 50.0mm)	Operating Temperature	-10° C ~ 60° C (With Derating)	
Size / Dimension 7.40" L x 3.62" W x 1.97" H (188.0mm x 91.9mm x 50.0mm)	Features	Adjustable Output, DC Input Capable, PFC, Remote Sense, Universal Input	
	Mounting Type	Chassis Mount	
Report errors?	Size / Dimension	7.40" L x 3.62" W x 1.97" H (188.0mm x 91.9mm x 50.0mm)	
			Report errors?

JWS1005/R Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

JWS1005/R Payment Methods



















JWS1005/R Shipping Methods













If you have any question about JWS1005/R, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com