

JWS60012 Information



For Reference Only

Part Number JWS60012

Manufacturer TDK-Lambda Americas Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Converters

Description AC/DC CONVERTER 12V 600W

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









JWS60012 Specifications

Manufacturer TDK-Lambda Americas Inc. Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series JWS Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 53A Power (Watts) 600W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 80% Operating Temperature -10°C ~ 65°C (With Derating)			
Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series JWS Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 53A Power (Watts) 600W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 80% Operating Temperature -10°C ~ 65°C (With Derating)	Manufacturer Part Number	JWS60012	
Package - Series JWS Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 53A Power (Watts) 600W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 80% Operating Temperature -10°C ~ 65°C (With Derating)	Manufacturer	TDK-Lambda Americas Inc.	
Package - Series JWS Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 53A Power (Watts) 600W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 80% Operating Temperature -10°C ~ 65°C (With Derating)	Category	Power Supplies - External/Internal (Off-Board)	
Series JWS Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 53A Power (Watts) 600W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 80% Operating Temperature -10°C ~ 65°C (With Derating)		AC DC Converters	
Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 53A Power (Watts) 600W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 80% Operating Temperature -10°C ~ 65°C (With Derating)	Package	-	
Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency Operating Temperature - 10°C ~ 65°C (With Derating)	Series	JWS	
Voltage - Input 85 ~ 265 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 53A Power (Watts) Applications ITE (Commercial) Voltage - Isolation SkV (3000V) Efficiency 80% Operating Temperature -10°C ~ 65°C (With Derating)	Type	Enclosed	
Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation Efficiency 80% Operating Temperature 12V	Number of Outputs	1	
Voltage - Output 2 Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Fower (Watts) Applications ITE (Commercial) Voltage - Isolation SkV (3000V) Efficiency 80% Operating Temperature -10°C ~ 65°C (With Derating)	Voltage - Input	85 ~ 265 VAC	
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Fower (Watts) Applications Voltage - Isolation SkV (3000V) Efficiency Operating Temperature -10°C ~ 65°C (With Derating)	Voltage - Output 1	12V	
Voltage - Output 4-Current - Output (Max) $53A$ Power (Watts) $600W$ ApplicationsITE (Commercial)Voltage - Isolation $3kV (3000V)$ Efficiency 80% Operating Temperature $-10^{\circ}C \sim 65^{\circ}C$ (With Derating)	Voltage - Output 2	-	
Current - Output (Max) $53A$ Power (Watts) $600W$ ApplicationsITE (Commercial)Voltage - Isolation $3kV (3000V)$ Efficiency 80% Operating Temperature $-10^{\circ}C \sim 65^{\circ}C$ (With Derating)	Voltage - Output 3	-	
Power (Watts) $600W$ Applications ITE (Commercial) Voltage - Isolation $3kV (3000V)$ Efficiency 80% Operating Temperature $-10^{\circ}\text{C} \sim 65^{\circ}\text{C}$ (With Derating)	Voltage - Output 4	-	
Applications ITE (Commercial) Voltage - Isolation $3kV (3000V)$ Efficiency 80% Operating Temperature $-10^{\circ}\text{C} \sim 65^{\circ}\text{C}$ (With Derating)	Current - Output (Max)	53A	
Voltage - Isolation $3kV (3000V)$ Efficiency 80% Operating Temperature $-10^{\circ}\text{C} \sim 65^{\circ}\text{C}$ (With Derating)	Power (Watts)	600W	
Efficiency 80% Operating Temperature $-10^{\circ}\text{C} \sim 65^{\circ}\text{C}$ (With Derating)	Applications	ITE (Commercial)	
Operating Temperature $-10^{\circ}\text{C} \sim 65^{\circ}\text{C}$ (With Derating)	Voltage - Isolation	3kV (3000V)	
• • •	Efficiency	80%	
Features Adjustable Output DC Input Capable PEC Remote Sense, Universal Input	Operating Temperature	-10° C ~ 65° C (With Derating)	
regulation output, De input cupulie, 11 c, remote bense, outversur input	Features	Adjustable Output, DC Input Capable, PFC, Remote Sense, Universal Input	
Mounting Type Chassis Mount	Mounting Type	Chassis Mount	
Size / Dimension 7.90" L x 6.29" W x 3.62" H (200.6mm x 159.8mm x 92.0mm)	Size / Dimension	7.90" L x 6.29" W x 3.62" H (200.6mm x 159.8mm x 92.0mm)	
Report errors?			Report errors?

JWS60012 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

JWS60012 Payment Methods





















JWS60012 Shipping Methods













If you have any question about JWS60012, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com