

JWS7524/B Information

Heisener.com

Part Number JWS7524/B

Manufacturer TDK-Lambda Americas Inc.

Power Supplies - External/Internal (Off-Board) Category

AC DC Converters

Description AC/DC CONVERTER 24V 75W

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









JWS7524/B Specifications

Manufacturer Part Number JWS7524/B Manufacturer TDK-Lambda Americas Inc. Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series JWS Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) - Power (Watts) 75W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 79% Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 6.88" L x 3.62" W x 1.65" H (174.8mm x 91.9mm x 41.9mm)		
Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series JWS Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) - Power (Watts) 75W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 79% Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 6.88" L x 3.62" W x 1.65" H (174.8mm x 91.9mm x 41.9mm)	Manufacturer Part Number	JWS7524/B
Package - Series JWS Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) - Power (Watts) 75W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 79% Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 6.88" L x 3.62" W x 1.65" H (174.8mm x 91.9mm x 41.9mm)	Manufacturer	TDK-Lambda Americas Inc.
Package - Series JWS Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) - Power (Watts) 75W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 79% Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 6.88" L x 3.62" W x 1.65" H (174.8mm x 91.9mm x 41.9mm)	Category	Power Supplies - External/Internal (Off-Board)
Series JWS Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) - Power (Watts) 75W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 79% Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 6.88" L x 3.62" W x 1.65" H (174.8mm x 91.9mm x 41.9mm)		AC DC Converters
Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) - Power (Watts) 75W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 79% Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 6.88" L x 3.62" W x 1.65" H (174.8mm x 91.9mm x 41.9mm)	Package	-
Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) - Power (Watts) 75W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 79% Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 6.88" L x 3.62" W x 1.65" H (174.8mm x 91.9mm x 41.9mm)	Series	JWS
Voltage - Input85 ~ 265 VACVoltage - Output 124VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)-Power (Watts)75WApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency79%Operating Temperature-10°C ~ 60°C (With Derating)FeaturesAdjustable Output, DC Input Capable, PFC, Universal InputMounting TypeChassis MountSize / Dimension6.88" L x 3.62" W x 1.65" H (174.8mm x 91.9mm x 41.9mm)	Туре	Open Frame
Voltage - Output 1 Voltage - Output 2 - Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation Site / One atting Temperature Features Adjustable Output, DC Input Capable, PFC, Universal Input Mounting Type Size / Dimension 24V 24V Current - Output (Max) - - - - - - - - - - - - -	Number of Outputs	1
Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 6.88" L x 3.62" W x 1.65" H (174.8mm x 91.9mm x 41.9mm)	Voltage - Input	85 ~ 265 VAC
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension - Output A diversal March 100 (174.8mm x 91.9mm x 41.9mm)	Voltage - Output 1	24V
Voltage - Output 4 Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 79% Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 6.88" L x 3.62" W x 1.65" H (174.8mm x 91.9mm x 41.9mm)	Voltage - Output 2	-
Current - Output (Max) Power (Watts) 75W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 79% Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 6.88" L x 3.62" W x 1.65" H (174.8mm x 91.9mm x 41.9mm)	Voltage - Output 3	-
Power (Watts) 75W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 79% Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 6.88" L x 3.62" W x 1.65" H (174.8mm x 91.9mm x 41.9mm)	Voltage - Output 4	-
Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 79% Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 6.88" L x 3.62" W x 1.65" H (174.8mm x 91.9mm x 41.9mm)	Current - Output (Max)	-
Voltage - Isolation 3kV (3000V) Efficiency 79% Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 6.88" L x 3.62" W x 1.65" H (174.8mm x 91.9mm x 41.9mm)	Power (Watts)	75W
Efficiency 79% Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 6.88" L x 3.62" W x 1.65" H (174.8mm x 91.9mm x 41.9mm)	Applications	ITE (Commercial)
Operating Temperature -10°C ~ 60°C (With Derating) Adjustable Output, DC Input Capable, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 6.88" L x 3.62" W x 1.65" H (174.8mm x 91.9mm x 41.9mm)	Voltage - Isolation	3kV (3000V)
Features Adjustable Output, DC Input Capable, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 6.88" L x 3.62" W x 1.65" H (174.8mm x 91.9mm x 41.9mm)	Efficiency	79%
Mounting Type Chassis Mount Size / Dimension 6.88" L x 3.62" W x 1.65" H (174.8mm x 91.9mm x 41.9mm)	Operating Temperature	$-10^{\circ}\text{C} \sim 60^{\circ}\text{C}$ (With Derating)
Size / Dimension 6.88" L x 3.62" W x 1.65" H (174.8mm x 91.9mm x 41.9mm)	Features	Adjustable Output, DC Input Capable, PFC, Universal Input
	Mounting Type	Chassis Mount
Report errors?	Size / Dimension	6.88" L x 3.62" W x 1.65" H (174.8mm x 91.9mm x 41.9mm)
		Report errors?

JWS7524/B Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

JWS7524/B Payment Methods



















JWS7524/B Shipping Methods













If you have any question about JWS7524/B, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com