



JWT75525/C Information



For Reference Only

Part Number JWT75525/C

Manufacturer TDK-Lambda Americas Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Converters

Description AC/DC CONVERTER 5V 12V -5V 75W

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









JWT75525/C Specifications

Manufacturer Part Number JWT75525/C Manufacturer TDK-Lambda Americas Inc. Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series JWT Type Enclosed Number of Outputs 3 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 5V Voltage - Output 2 12V Voltage - Output 3 -5V Voltage - Output 4 - Current - Output (Max) 8A, 4A, 500mA Power (Watts) 75W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 72% Operating Temperature -10°C ~ 65°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 7.40" L x 3.62" W x 1.65" H (188.0mm x 92.0mm x 42.0mm)		
Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series JWT Type Enclosed Number of Outputs 3 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 5V Voltage - Output 2 12V Voltage - Output 3 -5V Voltage - Output 4 - Current - Output (Max) 8A, 4A, 500mA Power (Watts) 75W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 72% Operating Temperature -10°C ~ 65°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 7.40" L x 3.62" W x 1.65" H (188.0mm x 92.0mm x 42.0mm)	Manufacturer Part Number	JWT75525/C
Package - Series JWT Type Enclosed Number of Outputs 3 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 5V Voltage - Output 2 12V Voltage - Output 3 -5V Voltage - Output 4 - Current - Output (Max) 8A, 4A, 500mA Power (Watts) 75W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 72% Operating Temperature -10°C ~ 65°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 7.40" L x 3.62" W x 1.65" H (188.0mm x 92.0mm x 42.0mm)	Manufacturer	TDK-Lambda Americas Inc.
Package - Series JWT Type Enclosed Number of Outputs 3 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 5V Voltage - Output 2 12V Voltage - Output 3 -5V Voltage - Output 4 - Current - Output (Max) 8A, 4A, 500mA Power (Watts) 75W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 72% Operating Temperature -10°C ~ 65°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 7.40" L x 3.62" W x 1.65" H (188.0mm x 92.0mm x 42.0mm)	Category	Power Supplies - External/Internal (Off-Board)
Series JWT Type Enclosed Number of Outputs 3 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 5V Voltage - Output 2 12V Voltage - Output 3 -5V Voltage - Output 4 - Current - Output (Max) 8A, 4A, 500mA Power (Watts) 75W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 72% Operating Temperature -10°C ~ 65°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 7.40" L x 3.62" W x 1.65" H (188.0mm x 92.0mm x 42.0mm)		AC DC Converters
Type Enclosed Number of Outputs 3 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 5V Voltage - Output 2 12V Voltage - Output 3 -5V Voltage - Output 4 - Current - Output (Max) 8A, 4A, 500mA Power (Watts) 75W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 72% Operating Temperature -10°C ~ 65°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 7.40" L x 3.62" W x 1.65" H (188.0mm x 92.0mm x 42.0mm)	Package	-
Number of Outputs 3 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 5V Voltage - Output 2 12V Voltage - Output 3 -5V Voltage - Output 4 - Current - Output (Max) 8A, 4A, 500mA Power (Watts) 75W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 72% Operating Temperature -10°C ~ 65°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 7.40" L x 3.62" W x 1.65" H (188.0mm x 92.0mm x 42.0mm)	Series	JWT
Voltage - Input 85 ~ 265 VAC Voltage - Output 1 5V Voltage - Output 2 12V Voltage - Output 3 -5V Voltage - Output 4 - Current - Output (Max) 8A, 4A, 500mA Power (Watts) 75W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 72% Operating Temperature -10°C ~ 65°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 7.40" L x 3.62" W x 1.65" H (188.0mm x 92.0mm x 42.0mm)	Туре	Enclosed
Voltage - Output 1 Voltage - Output 2 12V Voltage - Output 3 -5V Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency Operating Temperature -10°C ~ 65°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Universal Input Mounting Type Size / Dimension 5V 12V 12V 12V 12V 12V 12V 12V	Number of Outputs	3
Voltage - Output 2 Voltage - Output 3 -5V Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency Operating Temperature Features Adjustable Output, DC Input Capable, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 12V 12V 12V 12V 12V 12V 15V 15V	Voltage - Input	85 ~ 265 VAC
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Applications ITE (Commercial) Voltage - Isolation Sire / Dimension -5V -5V -5V -5V -5V -5V -6V -6V	Voltage - Output 1	5V
Voltage - Output 4 Current - Output (Max) 8A, 4A, 500mA Power (Watts) 75W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 72% Operating Temperature -10°C ~ 65°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 7.40" L x 3.62" W x 1.65" H (188.0mm x 92.0mm x 42.0mm)	Voltage - Output 2	12V
Current - Output (Max) 8A, 4A, 500mA Power (Watts) 75W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 72% Operating Temperature -10°C ~ 65°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 7.40" L x 3.62" W x 1.65" H (188.0mm x 92.0mm x 42.0mm)	Voltage - Output 3	-5V
Power (Watts) 75W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 72% Operating Temperature -10°C ~ 65°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 7.40" L x 3.62" W x 1.65" H (188.0mm x 92.0mm x 42.0mm)	Voltage - Output 4	-
Applications ITE (Commercial) Voltage - Isolation $3kV (3000V)$ Efficiency 72% Operating Temperature $-10^{\circ}\text{C} \sim 65^{\circ}\text{C}$ (With Derating) Features Adjustable Output, DC Input Capable, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension $7.40'' \text{L x } 3.62'' \text{W x } 1.65'' \text{H } (188.0 \text{mm x } 92.0 \text{mm x } 42.0 \text{mm})$	Current - Output (Max)	8A, 4A, 500mA
Voltage - Isolation 3kV (3000V) Efficiency 72% Operating Temperature -10°C ~ 65°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 7.40" L x 3.62" W x 1.65" H (188.0mm x 92.0mm x 42.0mm)	Power (Watts)	75W
Efficiency 72% Operating Temperature -10°C ~ 65°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 7.40" L x 3.62" W x 1.65" H (188.0mm x 92.0mm x 42.0mm)	Applications	ITE (Commercial)
Operating Temperature -10°C ~ 65°C (With Derating) Adjustable Output, DC Input Capable, PFC, Universal Input Mounting Type Chassis Mount 7.40" L x 3.62" W x 1.65" H (188.0mm x 92.0mm x 42.0mm)	Voltage - Isolation	3kV (3000V)
Features Adjustable Output, DC Input Capable, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 7.40" L x 3.62" W x 1.65" H (188.0mm x 92.0mm x 42.0mm)	Efficiency	72%
Mounting Type Chassis Mount Size / Dimension 7.40" L x 3.62" W x 1.65" H (188.0mm x 92.0mm x 42.0mm)	Operating Temperature	-10° C ~ 65° C (With Derating)
Size / Dimension 7.40" L x 3.62" W x 1.65" H (188.0mm x 92.0mm x 42.0mm)	Features	Adjustable Output, DC Input Capable, PFC, Universal Input
	Mounting Type	Chassis Mount
Report errors?	Size / Dimension	7.40" L x 3.62" W x 1.65" H (188.0mm x 92.0mm x 42.0mm)
		Report errors?

JWT75525/C Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

JWT75525/C Payment Methods



















JWT75525/C Shipping Methods













If you have any question about JWT75525/C, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com