



### JX0B-3051NL Information

Heisener.com

Part Number JX0B-3051NL

Manufacturer Pulse Electronics Network
Category Connectors, Interconnects

Modular Connectors - Jacks With Magnetics

**Description** CONN MAGJACK 8PORT 1000 BASE-T

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **JX0B-3051NL Specifications**

Manufacturer Part Number         JX0B-3051NL           Manufacturer         Pulse Electronics Network           Category         Connectors, Interconnects           Modular Connectors - Jacks With Magnetics           Package         -           Series         PULSEJACK? JX0B           Connector Type         RJ45           Number of Ports         8           Number of Rows         2           Applications         10/100/1000 Base-T, Power over Ethernet+ (PoE+)           Mounting Type         Through Hole           Orientation         90° Angle (Right)           Termination         Solder           Height Above Board         1.005" (25.53mm)           LED Color         Green, Yellow - Green, Yellow           Number of Cores per Jack         9           Shielding         Shielded, EMI Finger           Features         Board Guide           Tab Direction         Up and Down           Contact Material         Phosphor Bronze           Contact Finish         Gold           Operating Temperature         -40°C ~ 85°C		
Category         Connectors, Interconnects           Package         -           Series         PULSEJACK? JX0B           Connector Type         RJ45           Number of Ports         8           Number of Rows         2           Applications         10/100/1000 Base-T, Power over Ethernet+ (PoE+)           Mounting Type         Through Hole           Orientation         90° Angle (Right)           Termination         Solder           Height Above Board         1.005" (25.53mm)           LED Color         Green, Yellow - Green, Yellow           Number of Cores per Jack         9           Shielding         Shielded, EMI Finger           Features         Board Guide           Tab Direction         Up and Down           Contact Material         Phosphor Bronze           Contact Finish         Gold           Operating Temperature         -40°C ~ 85°C	Manufacturer Part Number	JX0B-3051NL
Package-SeriesPULSEJACK? JX0BConnector TypeRJ45Number of Ports8Number of Rows2Applications10/100/1000 Base-T, Power over Ethernet+ (PoE+)Mounting TypeThrough HoleOrientation90° Angle (Right)TerminationSolderHeight Above Board1.005" (25.53mm)LED ColorGreen, Yellow - Green, YellowNumber of Cores per Jack9ShieldingShielded, EMI FingerFeaturesBoard GuideTab DirectionUp and DownContact MaterialPhosphor BronzeContact FinishGoldOperating Temperature-40°C ~ 85°C	Manufacturer	Pulse Electronics Network
Package         -           Series         PULSEJACK? JX0B           Connector Type         RJ45           Number of Ports         8           Number of Rows         2           Applications         10/100/1000 Base-T, Power over Ethernet+ (PoE+)           Mounting Type         Through Hole           Orientation         90° Angle (Right)           Termination         Solder           Height Above Board         1.005" (25.53mm)           LED Color         Green, Yellow - Green, Yellow           Number of Cores per Jack         9           Shielding         Shielded, EMI Finger           Features         Board Guide           Tab Direction         Up and Down           Contact Material         Phosphor Bronze           Contact Finish         Gold           Operating Temperature         -40°C ~ 85°C	Category	Connectors, Interconnects
SeriesPULSEJACK? JX0BConnector TypeRJ45Number of Ports8Number of Rows2Applications10/100/1000 Base-T, Power over Ethernet+ (PoE+)Mounting TypeThrough HoleOrientation90° Angle (Right)TerminationSolderHeight Above Board1.005" (25.53mm)LED ColorGreen, Yellow - Green, YellowNumber of Cores per Jack9ShieldingShielded, EMI FingerFeaturesBoard GuideTab DirectionUp and DownContact MaterialPhosphor BronzeContact FinishGoldOperating Temperature-40°C ~ 85°C		Modular Connectors - Jacks With Magnetics
Connector TypeRJ45Number of Ports8Number of Rows2Applications10/100/1000 Base-T, Power over Ethernet+ (PoE+)Mounting TypeThrough HoleOrientation90° Angle (Right)TerminationSolderHeight Above Board1.005" (25.53mm)LED ColorGreen, Yellow - Green, YellowNumber of Cores per Jack9ShieldingShielded, EMI FingerFeaturesBoard GuideTab DirectionUp and DownContact MaterialPhosphor BronzeContact FinishGoldOperating Temperature-40°C ~ 85°C	Package	-
Number of Ports8Number of Rows2Applications10/100/1000 Base-T, Power over Ethernet+ (PoE+)Mounting TypeThrough HoleOrientation90° Angle (Right)TerminationSolderHeight Above Board1.005" (25.53mm)LED ColorGreen, Yellow - Green, YellowNumber of Cores per Jack9ShieldingShielded, EMI FingerFeaturesBoard GuideTab DirectionUp and DownContact MaterialPhosphor BronzeContact FinishGoldOperating Temperature-40°C ~ 85°C	Series	PULSEJACK? JX0B
Number of Rows2Applications10/100/1000 Base-T, Power over Ethernet+ (PoE+)Mounting TypeThrough HoleOrientation90° Angle (Right)TerminationSolderHeight Above Board1.005" (25.53mm)LED ColorGreen, Yellow - Green, YellowNumber of Cores per Jack9ShieldingShielded, EMI FingerFeaturesBoard GuideTab DirectionUp and DownContact MaterialPhosphor BronzeContact FinishGoldOperating Temperature-40°C ~ 85°C	Connector Type	RJ45
Applications 10/100/1000 Base-T, Power over Ethernet+ (PoE+)  Mounting Type Through Hole  Orientation 90° Angle (Right)  Termination Solder  Height Above Board 1.005" (25.53mm)  LED Color Green, Yellow - Green, Yellow  Number of Cores per Jack 9  Shielding Shielded, EMI Finger  Features Board Guide  Tab Direction Up and Down  Contact Material Phosphor Bronze  Contact Finish Gold  Operating Temperature -40°C ~ 85°C	Number of Ports	8
Mounting Type Orientation 90° Angle (Right) Termination Solder Height Above Board 1.005" (25.53mm) LED Color Green, Yellow - Green, Yellow Number of Cores per Jack 9 Shielding Shielded, EMI Finger Features Board Guide Tab Direction Up and Down Contact Material Phosphor Bronze Contact Finish Gold Operating Temperature -40°C ~ 85°C	Number of Rows	2
Orientation 90° Angle (Right) Termination Solder Height Above Board 1.005" (25.53mm)  LED Color Green, Yellow - Green, Yellow Number of Cores per Jack 9 Shielding Shielded, EMI Finger Features Board Guide Tab Direction Up and Down Contact Material Phosphor Bronze Contact Finish Gold Operating Temperature -40°C ~ 85°C	Applications	10/100/1000 Base-T, Power over Ethernet+ (PoE+)
Termination Solder  Height Above Board 1.005" (25.53mm)  LED Color Green, Yellow - Green, Yellow  Number of Cores per Jack 9  Shielding Shielded, EMI Finger  Features Board Guide  Tab Direction Up and Down  Contact Material Phosphor Bronze  Contact Finish Gold  Operating Temperature -40°C ~ 85°C	Mounting Type	Through Hole
Height Above Board  LED Color  Green, Yellow - Green, Yellow  Number of Cores per Jack  9  Shielding  Shielded, EMI Finger  Features  Board Guide  Tab Direction  Up and Down  Contact Material  Phosphor Bronze  Contact Finish  Gold  Operating Temperature  1.005" (25.53mm)  Bronze  9  Core, Yellow  9  Shieldw  9  Corean, Yellow  9  Shieldw  9  Corean, Yellow  9  Shieldw  9  Shieldw  9  Shielded, EMI Finger  Board Guide  Corean Guide  1.005" (25.53mm)  9  Shieldw  9  Shiel	Orientation	90° Angle (Right)
LED ColorGreen, Yellow - Green, YellowNumber of Cores per Jack9ShieldingShielded, EMI FingerFeaturesBoard GuideTab DirectionUp and DownContact MaterialPhosphor BronzeContact FinishGoldOperating Temperature-40°C ~ 85°C	Termination	Solder
Number of Cores per Jack  Shielding  Shielded, EMI Finger  Features  Board Guide  Tab Direction  Up and Down  Contact Material  Phosphor Bronze  Contact Finish  Gold  Operating Temperature  9  Shielded, EMI Finger  Board Guide  Up and Down  Up and Down  Phosphor Bronze  Contact Finish  Gold	Height Above Board	1.005" (25.53mm)
Shielding Shielded, EMI Finger  Features Board Guide  Tab Direction Up and Down  Contact Material Phosphor Bronze  Contact Finish Gold  Operating Temperature -40°C ~ 85°C	LED Color	Green, Yellow - Green, Yellow
Features Board Guide  Tab Direction Up and Down  Contact Material Phosphor Bronze  Contact Finish Gold  Operating Temperature -40°C ~ 85°C	Number of Cores per Jack	9
Tab Direction Up and Down Contact Material Phosphor Bronze Contact Finish Gold Operating Temperature -40°C ~ 85°C	Shielding	Shielded, EMI Finger
Contact Material Phosphor Bronze  Contact Finish Gold  Operating Temperature -40°C ~ 85°C	Features	Board Guide
Contact Finish Gold  Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$	Tab Direction	Up and Down
Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$	Contact Material	Phosphor Bronze
	Contact Finish	Gold
Report errors?	Operating Temperature	-40°C ~ 85°C
		Report errors?

#### **JX0B-3051NL** Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **JX0B-3051NL Payment Methods**



















### **JX0B-3051NL Shipping Methods**













If you have any question about JX0B-3051NL, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com