



### K123K15X7RK53L2 Information

Part Number K123K15X7RK53L2 Manufacturer Vishay BC Components

Category Capacitors

**Ceramic Capacitors** 

**Description** CAP CER 0.012UF 200V X7R RADIAL

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

www.flaiseger.com

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## K123K15X7RK53L2 Specifications

Manufacturer Part Number         K123K15X7RK53L2           Manufacturer         Vishay BC Components           Category         Capacitors           Package         Radial           Series         Mono-Kap? K           Capacitance         0.012µF           Tolerance         ±10%           Voltage - Rated         200V           Temperature Coefficient         X7R           Operating Temperature         -55°C ~ 125°C           Features         -           Ratings         -           Applications         General Purpose           Failure Rate         -           Mounting Type         Through Hole           Package / Case         Radial           Size / Dimension         0.157" L x 0.098" W (4.00mm x 2.50mm)           Height - Seated (Max)         0.062" (1.58mm)           Thickness (Max)         -           Lead Spacing         0.098" (2.50mm)           Lead Style         Straight		
Category         Capacitors           Package         Radial           Series         Mono-Kap? K           Capacitance         0.012µF           Tolerance         ±10%           Voltage - Rated         200V           Temperature Coefficient         X7R           Operating Temperature         -55°C ~ 125°C           Features         -           Applications         General Purpose           Failure Rate         -           Mounting Type         Through Hole           Package / Case         Radial           Size / Dimension         0.157" L x 0.098" W (4.00mm x 2.50mm)           Height - Seated (Max)         0.062" (1.58mm)           Thickness (Max)         -           Lead Spacing         0.098" (2.50mm)           Lead Style         Straight	Manufacturer Part Number	K123K15X7RK53L2
Package         Radial           Series         Mono-Kap? K           Capacitance         0.012μF           Tolerance         ±10%           Voltage - Rated         200V           Temperature Coefficient         X7R           Operating Temperature         -55°C ~ 125°C           Features         -           Applications         General Purpose           Failure Rate         -           Mounting Type         Through Hole           Package / Case         Radial           Size / Dimension         0.157" L x 0.098" W (4.00mm x 2.50mm)           Height - Seated (Max)         0.062" (1.58mm)           Thickness (Max)         -           Lead Spacing         0.098" (2.50mm)           Lead Style         Straight	Manufacturer	Vishay BC Components
Package         Radial           Series         Mono-Kap? K           Capacitance         0.012µF           Tolerance         ±10%           Voltage - Rated         200V           Temperature Coefficient         X7R           Operating Temperature         -55°C ~ 125°C           Features         -           Ratings         -           Applications         General Purpose           Failure Rate         -           Mounting Type         Through Hole           Package / Case         Radial           Size / Dimension         0.157" L x 0.098" W (4.00mm x 2.50mm)           Height - Seated (Max)         0.062" (1.58mm)           Thickness (Max)         -           Lead Spacing         0.098" (2.50mm)           Lead Style         Straight	Category	Capacitors
Series         Mono-Kap? K           Capacitance         0.012µF           Tolerance         ±10%           Voltage - Rated         200V           Temperature Coefficient         X7R           Operating Temperature         -55°C ~ 125°C           Features         -           Ratings         -           Applications         General Purpose           Failure Rate         -           Mounting Type         Through Hole           Package / Case         Radial           Size / Dimension         0.157" L x 0.098" W (4.00mm x 2.50mm)           Height - Seated (Max)         0.062" (1.58mm)           Thickness (Max)         -           Lead Spacing         0.098" (2.50mm)           Lead Style         Straight		Ceramic Capacitors
Capacitance         0.012μF           Tolerance         ±10%           Voltage - Rated         200V           Temperature Coefficient         X7R           Operating Temperature         -55°C ~ 125°C           Features         -           Ratings         -           Applications         General Purpose           Failure Rate         -           Mounting Type         Through Hole           Package / Case         Radial           Size / Dimension         0.157" L x 0.098" W (4.00mm x 2.50mm)           Height - Seated (Max)         0.062" (1.58mm)           Thickness (Max)         -           Lead Spacing         0.098" (2.50mm)           Lead Style         Straight	Package	Radial
Tolerance ±10%  Voltage - Rated 200V  Temperature Coefficient X7R  Operating Temperature -55°C ~ 125°C  Features - Case Radial  Size / Dimension 0.157" L x 0.098" W (4.00mm x 2.50mm)  Height - Seated (Max) 0.098" (2.50mm)  Lead Spacing 0.098" (2.50mm)  Lead Style 1.000 - STR	Series	Mono-Kap? K
Voltage - Rated200VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.157" L x 0.098" W (4.00mm x 2.50mm)Height - Seated (Max)0.062" (1.58mm)Thickness (Max)-Lead Spacing0.098" (2.50mm)Lead StyleStraight	Capacitance	0.012μF
Temperature Coefficient  Operating Temperature  -55°C ~ 125°C  Features  - Ratings  - Applications  General Purpose  Failure Rate  - Mounting Type  Through Hole  Package / Case  Radial  Size / Dimension  Height - Seated (Max)  Thickness (Max)  Lead Spacing  Lead Style  X7R  6-125°C  - 125°C  - 125°C	Tolerance	±10%
Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style - Straight - Straight - Straight - Seated (Max) - Straight - Straigh	Voltage - Rated	200V
Features Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style Straight - Straigh	Temperature Coefficient	X7R
Ratings - General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.157" L x 0.098" W (4.00mm x 2.50mm) Height - Seated (Max) 0.062" (1.58mm) Thickness (Max) - Lead Spacing 0.098" (2.50mm) Lead Style Straight	Operating Temperature	-55°C ~ 125°C
Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.157" L x 0.098" W (4.00mm x 2.50mm) Height - Seated (Max) 0.062" (1.58mm) Thickness (Max) - Lead Spacing 0.098" (2.50mm) Lead Style Straight	Features	-
Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.157" L x 0.098" W (4.00mm x 2.50mm) Height - Seated (Max) 0.062" (1.58mm) Thickness (Max) - Lead Spacing 0.098" (2.50mm) Lead Style Straight	Ratings	-
Mounting Type Through Hole  Package / Case Radial  Size / Dimension 0.157" L x 0.098" W (4.00mm x 2.50mm)  Height - Seated (Max) 0.062" (1.58mm)  Thickness (Max) -  Lead Spacing 0.098" (2.50mm)  Lead Style Straight	Applications	General Purpose
Package / Case Radial Size / Dimension 0.157" L x 0.098" W (4.00mm x 2.50mm) Height - Seated (Max) 0.062" (1.58mm)  Thickness (Max) - Lead Spacing 0.098" (2.50mm) Lead Style Straight	Failure Rate	-
Size / Dimension       0.157" L x 0.098" W (4.00mm x 2.50mm)         Height - Seated (Max)       0.062" (1.58mm)         Thickness (Max)       -         Lead Spacing       0.098" (2.50mm)         Lead Style       Straight	Mounting Type	Through Hole
Height - Seated (Max)  Thickness (Max)  Lead Spacing  Lead Style  0.062" (1.58mm)  -  Under Company (2.50mm)  Straight	Package / Case	Radial
Thickness (Max)  Lead Spacing  0.098" (2.50mm)  Lead Style  Straight	Size / Dimension	0.157" L x 0.098" W (4.00mm x 2.50mm)
Lead Spacing0.098" (2.50mm)Lead StyleStraight	Height - Seated (Max)	0.062" (1.58mm)
Lead Style Straight	Thickness (Max)	-
	Lead Spacing	0.098" (2.50mm)
Report errors?	Lead Style	Straight
		Report errors?

#### K123K15X7RK53L2 Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### K123K15X7RK53L2 Payment Methods


































If you have any question about K123K15X7RK53L2, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com