

K393K20X7RL5UH5

K393K20X7RL5UH5 Information



For Reference Only

Part Number K393K20X7RL5UH5
Manufacturer Vishay BC Components

Category Capacitors

Ceramic Capacitors

Description CAP CER 0.039UF 500V X7R RADIAL

Package Radia

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









K393K20X7RL5UH5 Specifications

Manufacturer Part NumberK393K20X7RL5UH5ManufacturerVishay BC ComponentsCategoryCapacitorsPackageRadialSeriesMono-Kap? KCapacitance0.039µFTolerance±10%Voltage - Rated500VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough Hole
CategoryCapacitorsPackageRadialSeriesMono-Kap? KCapacitance $0.039\mu F$ Tolerance $\pm 10\%$ Voltage - Rated $500V$ Temperature Coefficient $X7R$ Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$ Features-Ratings-ApplicationsGeneral PurposeFailure Rate-
PackageRadialSeriesMono-Kap? KCapacitance $0.039μF$ Tolerance $±10%$ Voltage - Rated $500V$ Temperature Coefficient $X7R$ Operating Temperature $-55°C \sim 125°C$ Features-Ratings-ApplicationsGeneral PurposeFailure Rate-
PackageRadialSeriesMono-Kap? KCapacitance0.039μFTolerance±10%Voltage - Rated500VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-
Series Mono-Kap? K Capacitance $0.039\mu F$ Tolerance $\pm 10\%$ Voltage - Rated $500V$ Temperature Coefficient $X7R$ Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$ Features - Ratings - Applications General Purpose Failure Rate -
Capacitance $0.039μF$ Tolerance $±10\%$ Voltage - Rated $500V$ Temperature Coefficient $X7R$ Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$ Features-Ratings-ApplicationsGeneral PurposeFailure Rate-
Tolerance $\pm 10\%$ Voltage - Rated $500V$ Temperature Coefficient $X7R$ Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$ Features-Ratings-ApplicationsGeneral PurposeFailure Rate-
Voltage - Rated500VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-
Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate -
Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate -
Features - Ratings - Applications General Purpose Failure Rate -
Ratings - Applications General Purpose Failure Rate -
Applications General Purpose Failure Rate -
Failure Rate -
Mounting Type Through Hole
÷ ••
Package / Case Radial
Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm)
Height - Seated (Max) 0.100" (2.54mm)
Thickness (Max)
Lead Spacing 0.197" (5.00mm)
Lead Style Formed Leads
Report error

K393K20X7RL5UH5 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

K393K20X7RL5UH5 Payment Methods



















K393K20X7RL5UH5 Shipping Methods













If you have any question about K393K20X7RL5UH5, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com