



K683K15X7RF53L2 Information

www.flaiseger.com

Part Number K683K15X7RF53L2

Manufacturer Vishay BC Components

Cottogory Consoitors

Category Capacitors

Ceramic Capacitors

Description CAP CER 0.068UF 50V X7R RADIAL

Package Radia

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com

Request a Quote



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









K683K15X7RF53L2 Specifications

Manufacturer Part Number K683K15X7RF531.2 Manufacturer Vishay BC Components Category Capacitors Package Radial Series Mono-Kap? K Capacitance 0.068µF Tolerance ±10% Voltage - Rated 50V Temperature Coefficient X7R Operating Temperature -5°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.157" L x 0.098" W (4.00mm x 2.50mm) Height - Seated (Max) 0.062" (1.58mm) Thickness (Max) - Lead Spacing 0.098" (2.50mm) Lead Style Straight		
Category Capacitors Package Radial Series Mono-Kap? K Capacitance 0.068µF Tolerance ±10% Voltage - Rated 50V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.157" L x 0.098" W (4.00mm x 2.50mm) Height - Seated (Max) 0.062" (1.58mm) Thickness (Max) - Lead Spacing 0.098" (2.50mm) Lead Style Straight	Manufacturer Part Number	K683K15X7RF53L2
Package Radial Series Mono-Kap? K Capacitance 0.068μF Tolerance ±10% Voltage - Rated 50V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.157" L x 0.098" W (4.00mm x 2.50mm) Height - Seated (Max) 0.062" (1.58mm) Thickness (Max) - Lead Spacing 0.098" (2.50mm) Lead Style Straight	Manufacturer	Vishay BC Components
Package Radial Series Mono-Kap? K Capacitance 0.068µF Tolerance ±10% Voltage - Rated 50V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.157" L x 0.098" W (4.00mm x 2.50mm) Height - Seated (Max) 0.062" (1.58mm) Thickness (Max) - Lead Spacing 0.098" (2.50mm) Lead Style Straight	Category	Capacitors
Series Mono-Kap? K Capacitance 0.068µF Tolerance ±10% Voltage - Rated 50V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.157" L x 0.098" W (4.00mm x 2.50mm) Height - Seated (Max) 0.062" (1.58mm) Thickness (Max) - Lead Spacing 0.098" (2.50mm) Lead Style Straight		Ceramic Capacitors
Capacitance 0.068μF Tolerance ±10% Voltage - Rated 50V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.157" L x 0.098" W (4.00mm x 2.50mm) Height - Seated (Max) 0.062" (1.58mm) Thickness (Max) - Lead Spacing 0.098" (2.50mm) Lead Style Straight	Package	Radial
Tolerance ±10% Voltage - Rated 50V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features Ratings Applications General Purpose Failure Rate Mounting Type Through Hole Package / Case Radial Size / Dimension 0.157" L x 0.098" W (4.00mm x 2.50mm) Height - Seated (Max) 0.062" (1.58mm) Thickness (Max) Lead Spacing 0.098" (2.50mm) Lead Style Straight	Series	Mono-Kap? K
Voltage - Rated50VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.157" L x 0.098" W (4.00mm x 2.50mm)Height - Seated (Max)0.062" (1.58mm)Thickness (Max)-Lead Spacing0.098" (2.50mm)Lead StyleStraight	Capacitance	0.068μF
Temperature Coefficient Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style X7R 6-125°C - 125°C - 125°C	Tolerance	±10%
Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style - Straight - Straight - Straight - Seated (Max) - Straight - Straigh	Voltage - Rated	50V
Features Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style Straight - Straigh	Temperature Coefficient	X7R
Ratings - General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.157" L x 0.098" W (4.00mm x 2.50mm) Height - Seated (Max) 0.062" (1.58mm) Thickness (Max) - Lead Spacing 0.098" (2.50mm) Lead Style Straight	Operating Temperature	-55°C ~ 125°C
Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.157" L x 0.098" W (4.00mm x 2.50mm) Height - Seated (Max) 0.062" (1.58mm) Thickness (Max) - Lead Spacing 0.098" (2.50mm) Lead Style Straight	Features	-
Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.157" L x 0.098" W (4.00mm x 2.50mm) Height - Seated (Max) 0.062" (1.58mm) Thickness (Max) - Lead Spacing 0.098" (2.50mm) Lead Style Straight	Ratings	-
Mounting Type Through Hole Package / Case Radial Size / Dimension 0.157" L x 0.098" W (4.00mm x 2.50mm) Height - Seated (Max) 0.062" (1.58mm) Thickness (Max) - Lead Spacing 0.098" (2.50mm) Lead Style Straight	Applications	General Purpose
Package / Case Radial Size / Dimension 0.157" L x 0.098" W (4.00mm x 2.50mm) Height - Seated (Max) 0.062" (1.58mm) Thickness (Max) - Lead Spacing 0.098" (2.50mm) Lead Style Straight	Failure Rate	-
Size / Dimension 0.157" L x 0.098" W (4.00mm x 2.50mm) Height - Seated (Max) 0.062" (1.58mm) Thickness (Max) - Lead Spacing 0.098" (2.50mm) Lead Style Straight	Mounting Type	Through Hole
Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style 0.062" (1.58mm) - Lead Spacing 0.098" (2.50mm) Straight	Package / Case	Radial
Thickness (Max) Lead Spacing 0.098" (2.50mm) Lead Style Straight	Size / Dimension	0.157" L x 0.098" W (4.00mm x 2.50mm)
Lead Spacing0.098" (2.50mm)Lead StyleStraight	Height - Seated (Max)	0.062" (1.58mm)
Lead Style Straight	Thickness (Max)	-
	Lead Spacing	0.098" (2.50mm)
Report errors?	Lead Style	Straight
		Report errors?

K683K15X7RF53L2 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

K683K15X7RF53L2 Payment Methods



















K683K15X7RF53L2 Shipping Methods













If you have any question about K683K15X7RF53L2, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com